

# Revised<sup>5.95</sup> Report on the Algorithmic Language Scheme

## — Standard Libraries —

MICHAEL SPERBER

WILLIAM CLINGER, R. KENT DYBVIG, MATTHEW FLATT, ANTON VAN STRAATEN

(*Editors*)

RICHARD KELSEY, WILLIAM CLINGER, JONATHAN REES

(*Editors, Revised<sup>5</sup> Report on the Algorithmic Language Scheme*)

**24 June 2007**

This report frequently refers back to the *Revised<sup>6</sup> Report on the Algorithmic Language Scheme* [9]; references to the report are identified by designations such as “report section” or “report chapter”.

Parts of the library report are derived from earlier revisions of the report [6]. We gratefully acknowledge their authors for their contributions. More detailed information on authorship can be found at the beginning of the *Revised<sup>6</sup> Report on the Algorithmic Language Scheme*.

We intend this report to belong to the entire Scheme community, and so we grant permission to copy it in whole or in part without fee. In particular, we encourage implementors of Scheme to use this report as a starting point for manuals and other documentation, modifying it as necessary.

**\*\*\* DRAFT\*\*\***

This is a preliminary draft. It is intended to reflect the decisions taken by the editors’ committee, but likely contains many mistakes, ambiguities and inconsistencies.

## CONTENTS

|  |    |  |    |
|--|----|--|----|
| 1 Unicode . . . . .                                    | 3  | 15 Composite library . . . . .   | 60 |
| 1.1 Characters . . . . .                               | 3  | 16 <code>eval</code> . . . . .   | 60 |
| 1.2 Strings . . . . .                                  | 4  | 17 Mutable pairs . . . . .   | 60 |
| 2 Bytevectors . . . . .                                | 5  | 18 Mutable strings . . . . .   | 61 |
| 2.1 Endianness . . . . .                               | 5  | 19 R <sup>5</sup> RS compatibility . . . . .   | 61 |
| 2.2 General operations . . . . .                       | 5  | References . . . . .   | 62 |
| 2.3 Operations on bytes and octets . . . . .           | 6  | Alphabetic index of definitions of concepts, key-<br>words, and procedures . . . . . | 64 |
| 2.4 Operations on integers of arbitrary size . . . . . | 6  |  |    |
| 2.5 Operations on 16-bit integers . . . . .            | 7  |  |    |
| 2.6 Operations on 32-bit integers . . . . .            | 8  |  |    |
| 2.7 Operations on 64-bit integers . . . . .            | 8  |  |    |
| 2.8 Operations on IEEE-754 representations . . . . .   | 9  |  |    |
| 2.9 Operations on strings . . . . .                    | 9  |  |    |
| 3 List utilities . . . . .                             | 10 |  |    |
| 4 Sorting . . . . .                                    | 13 |  |    |
| 5 Control structures . . . . .                         | 13 |  |    |
| 6 Records . . . . .                                    | 15 |  |    |
| 6.1 Mutability and equivalence . . . . .               | 15 |  |    |
| 6.2 Procedural layer . . . . .                         | 16 |  |    |
| 6.3 Syntactic layer . . . . .                          | 19 |  |    |
| 6.4 Inspection . . . . .                               | 21 |  |    |
| 7 Exceptions and conditions . . . . .                  | 22 |  |    |
| 7.1 Exceptions . . . . .                               | 22 |  |    |
| 7.2 Conditions . . . . .                               | 24 |  |    |
| 7.3 Standard condition types . . . . .                 | 26 |  |    |
| 8 I/O . . . . .  | 27 |  |    |
| 8.1 Condition types . . . . .                          | 27 |  |    |
| 8.2 Port I/O . . . . .                                 | 29 |  |    |
| 8.3 Simple I/O . . . . .                               | 39 |  |    |
| 9 File system . . . . .                                | 41 |  |    |
| 10 Command-line access and exit values . . . . .       | 41 |  |    |
| 11 Arithmetic . . . . .                                | 41 |  |    |
| 11.1 Fixnums . . . . .                                 | 41 |  |    |
| 11.2 Flonums . . . . .                                 | 44 |  |    |
| 11.3 Exact bitwise arithmetic . . . . .                | 46 |  |    |
| 12 <code>syntax-case</code> . . . . .                  | 48 |  |    |
| 12.1 Hygiene . . . . .                                 | 48 |  |    |
| 12.2 Syntax objects . . . . .                          | 49 |  |    |
| 12.3 Transformers . . . . .                            | 49 |  |    |
| 12.4 Parsing input and producing output . . . . .      | 49 |  |    |
| 12.5 Identifier predicates . . . . .                   | 51 |  |    |
| 12.6 Syntax-object and datum conversions . . . . .     | 53 |  |    |
| 12.7 Generating lists of temporaries . . . . .         | 54 |  |    |
| 12.8 Derived forms and procedures . . . . .            | 54 |  |    |
| 12.9 Syntax violations . . . . .                       | 56 |  |    |
| 13 Hashtables . . . . .                                | 56 |  |    |
| 13.1 Constructors . . . . .                            | 56 |  |    |
| 13.2 Procedures . . . . .                              | 57 |  |    |
| 13.3 Inspection . . . . .                              | 57 |  |    |
| 13.4 Hash functions . . . . .                          | 58 |  |    |
| 14 Enumerations . . . . .                              | 58 |  |    |

## 1. Unicode

The procedures exported by the (`rnrs unicode (6)`) library provide access to some aspects of the Unicode semantics for characters and strings: category information, case-independent comparisons, case mappings, and normalization [10].

Some of the procedures that operate on characters or strings ignore the difference between upper case and lower case. The procedures that ignore case have “-ci” (for “case insensitive”) embedded in their names.

### 1.1. Characters

|                                    |           |
|------------------------------------|-----------|
| <code>(char-upcase char)</code>    | procedure |
| <code>(char-downcase char)</code>  | procedure |
| <code>(char-titlecase char)</code> | procedure |
| <code>(char-foldcase char)</code>  | procedure |

These procedures take a character argument and return a character result. If the argument is an upper case or title case character, and if there is a single character that is its lower case form, then `char-downcase` returns that character. If the argument is a lower case or title case character, and there is a single character that is its upper case form, then `char-upcase` returns that character. If the argument is a lower case or upper case character, and there is a single character that is its title case form, then `char-titlecase` returns that character. If the argument is not a title case character and there is no single character that is its title case form, then `char-titlecase` returns the upper case form of the argument. Finally, if the character has a case-folded character, then `char-foldcase` returns that character. Otherwise the character returned is the same as the argument. For Turkic characters İ (#\x130) and ı (#\x131), `char-foldcase` behaves as the identity function; otherwise `char-foldcase` is the same as `char-downcase` composed with `char-upcase`.

|                                       |                       |
|---------------------------------------|-----------------------|
| <code>(char-upcase #\i)</code>        | $\Rightarrow$ #\I     |
| <code>(char-downcase #\i)</code>      | $\Rightarrow$ #\i     |
| <code>(char-titlecase #\i)</code>     | $\Rightarrow$ #\I     |
| <code>(char-foldcase #\i)</code>      | $\Rightarrow$ #\i     |
| <br>                                  |                       |
| <code>(char-upcase #\ß)</code>        | $\Rightarrow$ #\ß     |
| <code>(char-downcase #\ß)</code>      | $\Rightarrow$ #\ß     |
| <code>(char-titlecase #\ß)</code>     | $\Rightarrow$ #\ß     |
| <code>(char-foldcase #\ß)</code>      | $\Rightarrow$ #\ß     |
| <br>                                  |                       |
| <code>(char-upcase #\Sigma)</code>    | $\Rightarrow$ #\Sigma |
| <code>(char-downcase #\Sigma)</code>  | $\Rightarrow$ #\sigma |
| <code>(char-titlecase #\Sigma)</code> | $\Rightarrow$ #\Sigma |
| <code>(char-foldcase #\Sigma)</code>  | $\Rightarrow$ #\sigma |
| <br>                                  |                       |
| <code>(char-upcase #\ç)</code>        | $\Rightarrow$ #\Ç     |
| <code>(char-downcase #\ç)</code>      | $\Rightarrow$ #\ç     |

|                                   |                       |
|-----------------------------------|-----------------------|
| <code>(char-titlecase #\ç)</code> | $\Rightarrow$ #\Sigma |
| <code>(char-foldcase #\ç)</code>  | $\Rightarrow$ #\sigma |

*Note:* Note that `char-titlecase` does not always return a title case character.

*Note:* These procedures are consistent with Unicode’s locale-independent mappings from scalar values to scalar values for upcase, downcase, titlecase, and case-folding operations. These mappings can be extracted from `UnicodeData.txt` and `CaseFolding.txt` from the Unicode Consortium, ignoring Turkic mappings in the latter.

Note that these character-based procedures are an incomplete approximation to case conversion, even ignoring the user’s locale. In general, case mappings require the context of a string, both in arguments and in result. The `string-upcase`, `string-downcase`, `string-titlecase`, and `string-foldcase` procedures (section 1.2) perform more general case conversion.

|   |           |
|---|-----------|
| <code>(char-ci=? char<sub>1</sub> char<sub>2</sub> char<sub>3</sub> ...)</code>     | procedure |
| <code>(char-ci&lt;? char<sub>1</sub> char<sub>2</sub> char<sub>3</sub> ...)</code>  | procedure |
| <code>(char-ci&gt;? char<sub>1</sub> char<sub>2</sub> char<sub>3</sub> ...)</code>  | procedure |
| <code>(char-ci&lt;=? char<sub>1</sub> char<sub>2</sub> char<sub>3</sub> ...)</code> | procedure |
| <code>(char-ci&gt;=? char<sub>1</sub> char<sub>2</sub> char<sub>3</sub> ...)</code> | procedure |

These procedures are similar to `char=?`, etc., but operate on the case-folded versions of the characters.

|                                      |                  |
|--------------------------------------|------------------|
| <code>(char-ci&lt;? #\z #\Z)</code>  | $\Rightarrow$ #f |
| <code>(char-ci=? #\z #\Z)</code>     | $\Rightarrow$ #t |
| <code>(char-ci=? #\ç #\sigma)</code> | $\Rightarrow$ #t |

|                                      |           |
|--------------------------------------|-----------|
| <code>(char-alphabetic? char)</code> | procedure |
| <code>(char-numeric? char)</code>    | procedure |
| <code>(char-whitespace? char)</code> | procedure |
| <code>(char-upper-case? char)</code> | procedure |
| <code>(char-lower-case? char)</code> | procedure |
| <code>(char-title-case? char)</code> | procedure |

These procedures return #t if their arguments are alphabetic, numeric, whitespace, upper case, lower case, or title case characters, respectively; otherwise they return #f.

A character is alphabetic if it has the Unicode “Alphabetic” property. A character is numeric if it has the Unicode “Numeric” property. A character is whitespace if it has the Unicode “White\_Space” property. A character is upper case if it has the Unicode “Uppercase” property, lower case if it has the “Lowercase” property, and title case if it is in the Lt general category.

|   |                  |
|---|------------------|
| <code>(char-alphabetic? #\a)</code>     | $\Rightarrow$ #t |
| <code>(char-numeric? #\1)</code>        | $\Rightarrow$ #t |
| <code>(char-whitespace? #\space)</code> | $\Rightarrow$ #t |
| <code>(char-whitespace? #\x00A0)</code> | $\Rightarrow$ #t |
| <code>(char-upper-case? #\Sigma)</code> | $\Rightarrow$ #t |

```
(char-lower-case? #\σ)    ⇒ #t
(char-lower-case? #\x00AA) ⇒ #t
(char-title-case? #\I)   ⇒ #f
(char-title-case? #\x01C5) ⇒ #t
```

```
(char-general-category char)      procedure
```

Returns a symbol representing the Unicode general category of *char*, one of Lu, Ll, Lt, Lm, Lo, Mn, Mc, Me, Nd, Nl, No, Ps, Pe, Pi, Pf, Pd, Pc, Po, Sc, Sm, Sk, So, Zs, Zp, Zl, Cc, Cf, Cs, Co, or Cn.

```
(char-general-category #\a) ⇒ Ll
(char-general-category #\space)
  ⇒ Zs
(char-general-category #\x10FFFF)
  ⇒ Cn
```

## 1.2. Strings

```
(string-upcase string)      procedure
(string-downcase string)    procedure
(string-titlecase string)   procedure
(string-foldcase string)    procedure
```

These procedures take a string argument and return a string result. They are defined in terms of Unicode’s locale-independent case mappings from Unicode-scalar-value sequences to scalar-value sequences. In particular, the length of the result string can be different from the length of the input string. When the specified result is equal in the sense of `string=?` to the argument, these procedures may return the argument instead of a newly allocated string.

The `string-upcase` procedure converts a string to upper case; `string-downcase` converts a string to lower case. The `string-foldcase` procedure converts the string to its case-folded counterpart, using the full case-folding mapping, but without the special mappings for Turkic languages. The `string-titlecase` procedure converts the first cased character of each word via `char-titlecase`, and downcases all other cased characters.

```
(string-upcase "Hi")      ⇒ "HI"
(string-downcase "Hi")    ⇒ "hi"
(string-foldcase "Hi")    ⇒ "hi"

(string-upcase "Straße")  ⇒ "STRASSE"
(string-downcase "Straße") ⇒ "straße"
(string-foldcase "Straße") ⇒ "strasse"
(string-downcase "STRASSE") ⇒ "strasse"

(string-downcase "Σ")     ⇒ "σ"
```

; Chi Alpha Omicron Sigma:

```
(string-upcase "XAOΣ")    ⇒ "XAOΣ"
(string-downcase "XAOΣ")  ⇒ "χαος"
(string-downcase "XAOΣΣ") ⇒ "χαοσς"
(string-downcase "XAOΣ Σ") ⇒ "χαος σ"
(string-foldcase "XAOΣΣ") ⇒ "χαοσσ"
(string-upcase "χαος")    ⇒ "XAOΣ"
(string-upcase "χαοσ")    ⇒ "XAOΣ"
```

```
(string-titlecase "kNock kNoCK")
  ⇒ "Knock Knock"
(string-titlecase "who’s there?")
  ⇒ "Who’s There?"
(string-titlecase "r6rs")  ⇒ "R6Rs"
(string-titlecase "R6RS") ⇒ "R6Rs"
```

*Note:* The case mappings needed for implementing these procedures can be extracted from `UnicodeData.txt`, `SpecialCasing.txt`, `WordBreakProperty.txt` (the “MidLetter” property partly defines case-ignorable characters), and `CaseFolding.txt` from the Unicode Consortium.

Since these procedures are locale-independent, they may not be appropriate for some locales.

*Note:* Word breaking, as needed for the correct casing of  $\Sigma$  and for `string-titlecase`, is specified in Unicode Standard Annex #29 [5].

```
(string-ci=? string1 string2 string3 ...) procedure
(string-ci<? string1 string2 string3 ...) procedure
(string-ci>? string1 string2 string3 ...) procedure
(string-ci<=? string1 string2 string3 ...) procedure
(string-ci>=? string1 string2 string3 ...) procedure
```

These procedures are similar to `string=?`, etc., but operate on the case-folded versions of the strings.

```
(string-ci<? "z" "Z")      ⇒ #f
(string-ci=? "z" "Z")     ⇒ #t
(string-ci=? "Straße" "Strasse")
  ⇒ #t
(string-ci=? "Straße" "STRASSE")
  ⇒ #t
(string-ci=? "XAOΣ" "χαοσ")
  ⇒ #t
```

```
(string-normalize-nfd string)  procedure
(string-normalize-nfkd string) procedure
(string-normalize-nfc string)  procedure
(string-normalize-nfkc string) procedure
```

These procedures take a string argument and return a string result, which is the input string normalized to Unicode normalization form D, KD, C, or KC, respectively. When the specified result is equal in the sense of `string=?` to the argument, these procedures may return the argument instead of a newly allocated string.

```
(string-normalize-nfd "\xE9;")
    ⇒ "\x65;\x301;"
(string-normalize-nfc "\xE9;")
    ⇒ "\xE9;"
(string-normalize-nfd "\x65;\x301;")
    ⇒ "\x65;\x301;"
(string-normalize-nfc "\x65;\x301;")
    ⇒ "\xE9;"
```

## 2. Bytevectors

Many applications deal with blocks of binary data by accessing them in various ways—extracting signed or unsigned numbers of various sizes. Therefore, the `(rnrs bytevector (6))` library provides a single type for blocks of binary data with multiple ways to access that data. It deals with integers and floating-point representations in various sizes with specified endianness, because these are the most frequent applications.

Bytevectors are objects of a disjoint type. Conceptually, a bytevector represents a sequence of 8-bit bytes. The description of bytevectors uses the term *byte* for an exact integer object in the interval  $\{-128, \dots, 127\}$  and the term *octet* for an exact integer object in the interval  $\{0, \dots, 255\}$ . A byte corresponds to its two's complement representation as an octet.

The length of a bytevector is the number of bytes it contains. This number is fixed. A valid index into a bytevector is an exact, non-negative integer object. The first byte of a bytevector has index 0; the last byte has an index one less than the length of the bytevector.

Generally, the access procedures come in different flavors according to the size of the represented integer and the endianness of the representation. The procedures also distinguish signed and unsigned representations. The signed representations all use two's complement.

Like list and vector literals, literals representing bytevectors must be quoted:

```
'#vu8(12 23 123)    ⇒ #vu8(12 23 123)
```

### 2.1. Endianness

Many operations described in this chapter accept an *endianness* argument. Endianness describes the encoding of exact integer objects as several contiguous bytes in a bytevector [4]. For this purpose, the binary representation of the integer object is split into consecutive bytes. The little-endian encoding places the least significant byte of an integer first, with the other bytes following in increasing order of significance. The big-endian encoding places the most significant byte of an integer first, with the other bytes following in decreasing order of significance.

This terminology also applies to IEEE-754 numbers: IEEE-754 describes how to represent a floating-point number as an exact integer object, and endianness describes how the bytes of such an integer are laid out in a bytevector.

*Note:* Little- and big-endianness are only the most common kinds of endianness. Some architectures distinguish between the endianness at different levels of a binary representation.

### 2.2. General operations

`(endianness <endianness symbol>)` syntax

`<Endianness symbol>` must be a symbol describing an endianness. An implementation must support at least the symbols `big` and `little`, but may support other endianness symbols. `(endianness <endianness symbol>)` evaluates to the symbol named `<endianness symbol>`. Whenever one of the procedures operating on bytevectors accepts an endianness as an argument, that argument must be one of these symbols. It is a syntax violation for `<endianness symbol>` to be anything other than an endianness symbol supported by the implementation.

*Note:* Implementors are encouraged to use widely accepted designations for endianness symbols other than `big` and `little`.

`(native-endianness)` procedure

Returns the endianness symbol associated implementation's preferred endianness (usually that of the underlying machine architecture). This may be any `<endianness symbol>`, including a symbol other than `big` and `little`.

`(bytevector? obj)` procedure

Returns `#t` if `obj` is a bytevector, otherwise returns `#f`.

`(make-bytevector k)` procedure

`(make-bytevector k fill)` procedure

Returns a newly allocated bytevector of `k` bytes.

If the `fill` argument is missing, the initial contents of the returned bytevector are unspecified.

If the `fill` argument is present, it must be an exact integer object in the interval  $\{-128, \dots, 255\}$  that specifies the initial value for the bytes of the bytevector: If `fill` is positive, it is interpreted as an octet; if it is negative, it is interpreted as a byte.

`(bytevector-length bytevector)` procedure

Returns, as an exact integer object, the number of bytes in `bytevector`.

(bytevector=? *bytevector*<sub>1</sub> *bytevector*<sub>2</sub>)      procedure

Returns #t if *bytevector*<sub>1</sub> and *bytevector*<sub>2</sub> are equal—that is, if they have the same length and equal bytes at all valid indices. It returns #f otherwise.

(bytevector-fill! *bytevector fill*)

The *fill* argument is as in the description of the `make-bytevector` procedure. Stores *fill* in every element of *bytevector* and returns unspecified values. Analogous to `vector-fill!`.

(bytevector-copy! *source source-start*      procedure  
                  *target target-start k*)

*Source* and *target* must be bytevectors. *Source-start*, *target-start*, and *k* must be non-negative exact integer objects that satisfy

$$\begin{aligned} 0 &\leq \textit{source-start} \leq \textit{source-start} + k \leq l_{\textit{source}} \\ 0 &\leq \textit{target-start} \leq \textit{target-start} + k \leq l_{\textit{target}} \end{aligned}$$

where  $l_{\textit{source}}$  is the length of *source* and  $l_{\textit{target}}$  is the length of *target*.

The `bytevector-copy!` procedure copies the bytes from *source* at indices

$$\{\textit{source-start}, \dots, \textit{source-start} + k - 1\}$$

to consecutive indices in *target* starting at *target-index*.

This must work even if the memory regions for the source and the target overlap, i.e., the bytes at the target location after the copy must be equal to the bytes at the source location before the copy.

This returns unspecified values.

```
(let ((b (u8-list->bytevector '(1 2 3 4 5 6 7 8))))
  (bytevector-copy! b 0 b 3 4)
  (bytevector->u8-list b)) => (1 2 3 1 2 3 4 8)
```

(bytevector-copy *bytevector*)      procedure

Returns a newly allocated copy of *bytevector*.

### 2.3. Operations on bytes and octets

(bytevector-u8-ref *bytevector k*)      procedure

(bytevector-s8-ref *bytevector k*)      procedure

*K* must be a valid index of *bytevector*.

The `bytevector-u8-ref` procedure returns the byte at index *k* of *bytevector*, as an octet.

The `bytevector-s8-ref` procedure returns the byte at index *k* of *bytevector*, as a (signed) byte.

```
(let ((b1 (make-bytevector 16 -127))
      (b2 (make-bytevector 16 255)))
```

```
(list
  (bytevector-s8-ref b1 0)
  (bytevector-u8-ref b1 0)
  (bytevector-s8-ref b2 0)
  (bytevector-u8-ref b2 0))=> (-127 129 -1 255)
```

(bytevector-u8-set! *bytevector k octet*)      procedure

(bytevector-s8-set! *bytevector k byte*)      procedure

*K* must be a valid index of *bytevector*.

The `bytevector-u8-set!` procedure stores *octet* in element *k* of *bytevector*.

The `bytevector-s8-set!` procedure stores the two's complement representation of *byte* in element *k* of *bytevector*.

Both procedures return unspecified values.

```
(let ((b (make-bytevector 16 -127)))
```

```
(bytevector-s8-set! b 0 -126)
(bytevector-u8-set! b 1 246)

(list
  (bytevector-s8-ref b 0)
  (bytevector-u8-ref b 0)
  (bytevector-s8-ref b 1)
  (bytevector-u8-ref b 1))=> (-126 130 -10 246)
```

(bytevector->u8-list *bytevector*)      procedure

(u8-list->bytevector *list*)      procedure

*List* must be a list of octets.

The `bytevector->u8-list` procedure returns a newly allocated list of the octets of *bytevector* in the same order.

The `u8-list->bytevector` procedure returns a newly allocated bytevector whose elements are the elements of *list*, in the same order. It is analogous to `list->vector`.

### 2.4. Operations on integers of arbitrary size

(bytevector-uint-ref *bytevector k endianness size*)      procedure

(bytevector-sint-ref *bytevector k endianness size*)      procedure

(bytevector-uint-set! *bytevector k n endianness size*)      procedure

(bytevector-sint-set! *bytevector k n endianness size*)      procedure

*Size* must be a positive exact integer object.  $\{k, \dots, k + \textit{size} - 1\}$  must be valid indices of *bytevector*.

The `bytevector-uint-ref` procedure retrieves the exact integer object corresponding to the unsigned representation of size *size* and specified by *endianness* at indices  $\{k, \dots, k + size - 1\}$ .

The `bytevector-sint-ref` procedure retrieves the exact integer object corresponding to the two's complement representation of size *size* and specified by *endianness* at indices  $\{k, \dots, k + size - 1\}$ .

For `bytevector-uint-set!`, *n* must be an exact integer object in the interval  $\{0, \dots, 256^{size} - 1\}$ .

`bytevector-uint-set!` stores the unsigned representation of size *size* and specified by *endianness* into *bytevector* at indices  $\{k, \dots, k + size - 1\}$ .

For `bytevector-sint-set!`, *n* must be an exact integer object in the interval  $\{-256^{size}/2, \dots, 256^{size}/2 - 1\}$ . `bytevector-sint-set!` stores the two's complement representation of size *size* and specified by *endianness* into *bytevector* at indices  $\{k, \dots, k + size - 1\}$ .

The ...-set! procedures return unspecified values.

```
(define b (make-bytevector 16 -127))

(bytevector-uint-set! b 0 (- (expt 2 128) 3)
  (endianness little) 16)

(bytevector-uint-ref b 0 (endianness little) 16)
  =>
  #xfffffffffffffffffffffffffffffff

(bytevector-sint-ref b 0 (endianness little) 16)
  => -3

(bytevector->u8-list b)
  => (253 255 255 255 255 255 255 255
     255 255 255 255 255 255 255 255)

(bytevector-uint-set! b 0 (- (expt 2 128) 3)
  (endianness big) 16)

(bytevector-uint-ref b 0 (endianness big) 16)
  =>
  #xfffffffffffffffffffffffffffffff

(bytevector-sint-ref b 0 (endianness big) 16)
  => -3

(bytevector->u8-list b)
  => (255 255 255 255 255 255 255 255
     255 255 255 255 255 255 253)

(bytevector->uint-list bytevector endianness size)
  procedure
(bytevector->sint-list bytevector endianness size)
  procedure
```

```
(uint-list->bytevector list endianness size)
  procedure
(sint-list->bytevector list endianness size)
  procedure
```

*Size* must be a positive exact integer object. For `uint-list->bytevector`, *list* must be a list of exact integer objects in the interval  $\{0, \dots, 256^{size} - 1\}$ . For `sint-list->bytevector`, *list* must be a list of exact integer objects in the interval  $\{-256^{size}/2, \dots, 256^{size}/2 - 1\}$ . The length of *bytevector* or, respectively, of *list* must be divisible by *size*.

These procedures convert between lists of integer objects and their consecutive representations according to *size* and *endianness* in the *bytevector* objects in the same way as `bytevector->u8-list` and `u8-list->bytevector` do for one-byte representations.

```
(let ((b (u8-list->bytevector '(1 2 3 255 1 2 1 2))))
  (bytevector->sint-list b (endianness little) 2))
  => (513 -253 513 513)

(let ((b (u8-list->bytevector '(1 2 3 255 1 2 1 2))))
  (bytevector->uint-list b (endianness little) 2))
  => (513 65283 513 513)
```

## 2.5. Operations on 16-bit integers

```
(bytevector-u16-ref bytevector k endianness)
  procedure
(bytevector-s16-ref bytevector k endianness)
  procedure
(bytevector-u16-native-ref bytevector k)
  procedure
(bytevector-s16-native-ref bytevector k)
  procedure
(bytevector-u16-set! bytevector k n endianness)
  procedure
(bytevector-s16-set! bytevector k n endianness)
  procedure
(bytevector-u16-native-set! bytevector k n)
  procedure
(bytevector-s16-native-set! bytevector k n)
  procedure
```

*K* must be a valid index of *bytevector*; so must *k* + 1. For `bytevector-u16-set!` and `bytevector-u16-native-set!`, *n* must be an exact integer object in the interval  $\{0, \dots, 2^{16} - 1\}$ . For `bytevector-s16-set!` and `bytevector-s16-native-set!`, *n* must be an exact integer object in the interval  $\{-2^{15}, \dots, 2^{15} - 1\}$ .

These retrieve and set two-byte representations of numbers at indices *k* and *k* + 1, according to the endianness specified by *endianness*. The procedures with u16 in their

names deal with the unsigned representation; those with `s16` in their names deal with the two's complement representation.

The procedures with `native` in their names employ the native endianness, and work only at aligned indices:  $k$  must be a multiple of 2.

The ...-set! procedures return unspecified values.

```
(define b
  (u8-list->bytevector
    '(255 255 255 255 255 255 255 255
      255 255 255 255 255 255 255 253)))

(bytevector-u16-ref b 14 (endianness little))
  => 65023
(bytevector-s16-ref b 14 (endianness little))
  => -513
(bytevector-u16-ref b 14 (endianness big))
  => 65533
(bytevector-s16-ref b 14 (endianness big))
  => -3

(bytevector-u16-set! b 0 12345 (endianness little))
(bytevector-u16-ref b 0 (endianness little))
  => 12345

(bytevector-u16-native-set! b 0 12345)
(bytevector-u16-native-ref b 0) 12345

(bytevector-u16-ref b 0 (endianness little))
  => unspecified
```

## 2.6. Operations on 32-bit integers

```
(bytevector-u32-ref bytevector k endianness)
  procedure
(bytevector-s32-ref bytevector k endianness)
  procedure
(bytevector-u32-native-ref bytevector k) procedure
(bytevector-s32-native-ref bytevector k) procedure
(bytevector-u32-set! bytevector k n endianness)
  procedure
(bytevector-s32-set! bytevector k n endianness)
  procedure
(bytevector-u32-native-set! bytevector k n)
  procedure
(bytevector-s32-native-set! bytevector k n)
  procedure
```

$\{k, \dots, k + 3\}$  must be valid indices of *bytevector*. For `bytevector-u32-set!` and `bytevector-u32-native-set!`,  $n$  must be an exact integer object in the interval  $\{0, \dots, 2^{32} - 1\}$ . For `bytevector-s32-set!` and

`bytevector-s32-native-set!`,  $n$  must be an exact integer object in the interval  $\{-2^{31}, \dots, 2^{32} - 1\}$ .

These retrieve and set four-byte representations of numbers at indices  $\{k, \dots, k + 3\}$ , according to the endianness specified by *endianness*. The procedures with `u32` in their names deal with the unsigned representation; those with `s32` with the two's complement representation.

The procedures with `native` in their names employ the native endianness, and work only at aligned indices:  $k$  must be a multiple of 4.

The ...-set! procedures return unspecified values.

```
(define b
  (u8-list->bytevector
    '(255 255 255 255 255 255 255 255
      255 255 255 255 255 255 255 253)))

(bytevector-u32-ref b 12 (endianness little))
  => 4261412863
(bytevector-s32-ref b 12 (endianness little))
  => -33554433
(bytevector-u32-ref b 12 (endianness big))
  => 4294967293
(bytevector-s32-ref b 12 (endianness big))
  => -3
```

## 2.7. Operations on 64-bit integers

```
(bytevector-u64-ref bytevector k endianness)
  procedure
(bytevector-s64-ref bytevector k endianness)
  procedure
(bytevector-u64-native-ref bytevector k) procedure
(bytevector-s64-native-ref bytevector k) procedure
(bytevector-u64-set! bytevector k n endianness)
  procedure
(bytevector-s64-set! bytevector k n endianness)
  procedure
(bytevector-u64-native-set! bytevector k n)
  procedure
(bytevector-s64-native-set! bytevector k n)
  procedure
```

$\{k, \dots, k + 7\}$  must be valid indices of *bytevector*. For `bytevector-u64-set!` and `bytevector-u64-native-set!`,  $n$  must be an exact integer object in the interval  $\{0, \dots, 2^{64} - 1\}$ . For `bytevector-s64-set!` and `bytevector-s64-native-set!`,  $n$  must be an exact integer object in the interval  $\{-2^{63}, \dots, 2^{64} - 1\}$ .

These retrieve and set eight-byte representations of numbers at indices  $\{k, \dots, k + 7\}$ , according to the endianness specified by *endianness*. The procedures with `u64` in their

names deal with the unsigned representation; those with `s64` with the two's complement representation.

The procedures with `native` in their names employ the native endianness, and work only at aligned indices:  $k$  must be a multiple of 8.

The ...-`set!` procedures return unspecified values.

```
(define b
  (u8-list->bytevector
    '(255 255 255 255 255 255 255 255
      255 255 255 255 255 255 253)))

(bytevector-u64-ref b 8 (endianness little))
  => 18302628885633695743
(bytevector-s64-ref b 8 (endianness little))
  => -144115188075855873
(bytevector-u64-ref b 8 (endianness big))
  => 18446744073709551613
(bytevector-s64-ref b 8 (endianness big))
  => -3
```

## 2.8. Operations on IEEE-754 representations

```
(bytevector-ieee-single-native-ref bytevector k)
  procedure
(bytevector-ieee-single-ref bytevector k endianness)
  procedure
```

$\{k, \dots, k + 3\}$  must be valid indices of *bytevector*. For `bytevector-ieee-single-native-ref`,  $k$  must be a multiple of 4.

These procedures return the inexact real number object that best represents the IEEE-754 single precision number represented by the four bytes beginning at index  $k$ .

```
(bytevector-ieee-double-native-ref bytevector k)
  procedure
(bytevector-ieee-double-ref bytevector k endianness)
  procedure
```

$\{k, \dots, k + 7\}$  must be valid indices of *bytevector*. For `bytevector-ieee-double-native-ref`,  $k$  must be a multiple of 8.

These procedures return the inexact real number object that best represents the IEEE-754 single precision number represented by the eight bytes beginning at index  $k$ .

```
(bytevector-ieee-single-native-set! bytevector k x)
  procedure
(bytevector-ieee-single-set! bytevector k x endianness)
  procedure
```

$\{k, \dots, k + 3\}$  must be valid indices of *bytevector*. For `bytevector-ieee-single-native-set!`,  $k$  must be a multiple of 4.

These procedures store an IEEE-754 single precision representation of  $x$  into elements  $k$  through  $k + 3$  of *bytevector*, and return unspecified values.

```
(bytevector-ieee-double-native-set! bytevector k x)
  procedure
(bytevector-ieee-double-set! bytevector k x endianness)
  procedure
```

$\{k, \dots, k + 7\}$  must be valid indices of *bytevector*. For `bytevector-ieee-double-native-set!`,  $k$  must be a multiple of 8.

These procedures store an IEEE-754 double precision representation of  $x$  into elements  $k$  through  $k + 7$  of *bytevector*, and return unspecified values.

## 2.9. Operations on strings

This section describes procedures that convert between strings and bytevectors containing Unicode encodings of those strings. When decoding bytevectors, encoding errors are handled as with the `replace` semantics of textual I/O (see section 8.2.4): If an invalid or incomplete character encoding is encountered, then the replacement character U+FFFD is appended to the string being generated, an appropriate number of bytes are ignored, and decoding continues with the following bytes.

```
(string->utf8 string)
  procedure
```

Returns a newly allocated (unless empty) bytevector that contains the UTF-8 encoding of the given string.

```
(string->utf16 string)
  procedure
(string->utf16 string endianness)
  procedure
```

If *endianness* is specified, it must be the symbol `big` or the symbol `little`. The `string->utf16` procedure returns a newly allocated (unless empty) bytevector that contains the UTF-16BE or UTF-16LE encoding of the given string (with no byte-order mark). If *endianness* is not specified or is `big`, then UTF-16BE is used. If *endianness* is `little`, then UTF-16LE is used.

```
(string->utf32 string)
  procedure
(string->utf32 string endianness)
  procedure
```

If *endianness* is specified, it must be the symbol `big` or the symbol `little`. The `string->utf32` returns a newly allocated (unless empty) bytevector that contains the UTF-32BE or UTF-32LE encoding of the given string (with no

byte mark). If endianness is not specified or is `big`, then UTF-32BE is used. If endianness is `little`, then UTF-32LE is used.

```
(utf8->string bytevector)           procedure
Returns a newly allocated (unless empty) string whose
character sequence is encoded by the given bytevector.
```

```
(utf16->string bytevector endianness)           procedure
(utf16->string bytevector endianness endianness-mandatory?)
                                                                procedure
```

*Endianness* is specified must be the symbol `big` or the symbol `little`. The `utf16->string` procedure returns a newly allocated (unless empty) string whose character sequence is encoded by the given bytevector. *Bytevector* is decoded according to UTF-16BE or UTF-16LE: If *endianness-mandatory?* is absent or `#f`, `utf16->string` determines the endianness according to a UTF-16 BOM at the beginning of *bytevector* if a BOM is present; in this case, the BOM is not decoded as a character. Also in this case, if no UTF-16 BOM is present, *endianness* specifies the endianness of the encoding. If *endianness-mandatory?* is a true value, *endianness* specifies the endianness of the encoding, and any UTF-16 BOM in the encoding is decoded as a regular character.

*Note:* A UTF-16 BOM is either a sequence of bytes `#xFE`, `#xFF` specifying `big` and UTF-16BE, or `#xFF`, `#xFE` specifying `little` and UTF-16LE.

```
(utf32->string bytevector endianness)           procedure
(utf32->string bytevector endianness endianness-mandatory?)
                                                                procedure
```

*Endianness* is specified must be the symbol `big` or the symbol `little`. The `utf32->string` procedure returns a newly allocated (unless empty) string whose character sequence is encoded by the given bytevector. *Bytevector* is decoded according to UTF-32BE or UTF-32LE: If *endianness-mandatory?* is absent or `#f`, `utf32->string` determines the endianness according to a UTF-32 BOM at the beginning of *bytevector* if a BOM is present; in this case, the BOM is not decoded as a character. Also in this case, if no UTF-32 BOM is present, *endianness* specifies the endianness of the encoding. If *endianness-mandatory?* is a true value, *endianness* specifies the endianness of the encoding, and any UTF-32 BOM in the encoding is decoded as a regular character.

*Note:* A UTF-32 BOM is either a sequence of bytes `#x00`, `#x00`, `#xFE`, `#xFF` specifying `big` and UTF-32BE, or `#xFF`, `#xFE`, `#x00`, `#x00`, specifying `little` and UTF-32LE.

### 3. List utilities

This chapter describes the `(rnrs lists (6))` library.

```
(find proc list)           procedure
```

*Proc* should accept one argument and return a single value. *Proc* should not mutate *list*. The `find` procedure applies *proc* to the elements of *list* in order. If *proc* returns a true value for an element, `find` immediately returns that element. If *proc* returns `#f` for all elements of the list, `find` returns `#f`. *Proc* is always called in the same dynamic environment as `find` itself.

```
(find even? '(3 1 4 1 5 9)) => 4
```

```
(utf16->string bytevector endianness endianness-mandatory?)
                                                                procedure
(utf16->string bytevector endianness endianness-mandatory?)
                                                                procedure
                                                                procedure
```

*Implementation responsibilities:* The implementation must check that *list* is a chain of pairs up to the found element, or that it is indeed a list if no element is found. It should not check that it is a chain of pairs beyond the found element. The implementation must check the restrictions on *proc* to the extent performed by applying it as described.

```
(for-all proc list1 list2 ... listn)           procedure
(exists proc list1 list2 ... listn)           procedure
```

The *lists* should all have the same length, and *proc* should accept *n* arguments and return a single value. *Proc* should not mutate the *list* arguments.

For natural numbers  $i = 0, 1, \dots$ , the `for-all` procedure successively applies *proc* to arguments  $x_i^1 \dots x_i^n$ , where  $x_i^j$  is the *i*th element of *list<sub>j</sub>*, until `#f` is returned. If *proc* returns true values for all but the last element of *list<sub>1</sub>*, *for-all* performs a tail call of *proc* on the *k*th elements, where *k* is the length of *list<sub>1</sub>*. If *proc* returns `#f` on any set of elements, `for-all` returns `#f` after the first such application of *proc*. If the *lists* are all empty, `for-all` returns `#t`.

For natural numbers  $i = 0, 1, \dots$ , the `exists` procedure applies *proc* successively to arguments  $x_i^1 \dots x_i^n$ , where  $x_i^j$  is the *i*th element of *list<sub>j</sub>*, until a true value is returned. If *proc* returns `#f` for all but the last elements of the *lists*, *exists* performs a tail call of *proc* on the *k*th elements, where *k* is the length of *list<sub>1</sub>*. If *proc* returns a true value on any set of elements, `exists` returns that value after the first such application of *proc*. If the *lists* are all empty, `exists` returns `#f`.

*Proc* is always called in the same dynamic environment as `for-all` or, respectively, `exists` itself.

```
(for-all even? '(3 1 4 1 5 9))
```

```
=> #f
```

```
(for-all even? '(3 1 4 1 5 9 . 2))
```

```
=> #f
```

```
(for-all even? '(2 4 14)) => #t
```

```
(for-all even? '(2 4 14 . 9))
```

```
=> &assertion exception
```

```
(for-all (lambda (n) (and (even? n) n)) '(2 4 14))
```

```
=> 14
```

```

(for-all < '(1 2 3) '(2 3 4))=> #t
(for-all < '(1 2 4) '(2 3 4))=> #f

(exists even? '(3 1 4 1 5 9))
  => #t
(exists even? '(3 1 1 5 9)) => #f
(exists even? '(3 1 1 5 9 . 2))
  => &assertion exception
(exists (lambda (n) (and (even? n) n)) '(2 1 4 14))
  => 2
(exists < '(1 2 4) '(2 3 4))=> #t
(exists > '(1 2 3) '(2 3 4))=> #f

```

*Implementation responsibilities:* The implementation must check that the *lists* are chains of pairs to the extent necessary to determine the return value. If this requires traversing the lists entirely, the implementation should check that the *lists* all have the same length. If not, it should not check that the *lists* are chains of pairs beyond the traversal. The implementation must check the restrictions on *proc* to the extent performed by applying it as described.

```

(filter proc list)           procedure
(partition proc list)       procedure

```

*Proc* should accept one argument and return a single value. *Proc* should not mutate *list*. The `filter` procedure applies *proc* to each element of *list* and returns a list of the elements of *list* for which *proc* returned a true value. The `partition` procedure also applies *proc* to each element of *list*, but returns two values, the first one a list of the elements of *list* for which *proc* returned a true value, and the second a list of the elements of *list* for which *proc* returned #f. In both cases, the elements of the result list(s) are in the same order as they appear in the input list. *Proc* is always called in the same dynamic environment as `filter` or, respectively, `partition` itself. If multiple returns occur from `filter` or `partitions`, the return values returned by earlier returns are not mutated.

```

(filter even? '(3 1 4 1 5 9 2 6))
  => (4 2 6)

(partition even? '(3 1 4 1 5 9 2 6))
  => (4 2 6) (3 1 1 5 9) ; two values

```

*Implementation responsibilities:* The implementation must check the restrictions on *proc* to the extent performed by applying it as described.

```

(fold-left combine nil list1 list2 ... listn) procedure

```

The *lists* should all have the same length. *Combine* must be a procedure. It should accept one more argument than there are *lists* and return a single value. It should not

mutate the *list* arguments. The `fold-left` procedure iterates the *combine* procedure over an accumulator value and the elements of the *lists* from left to right, starting with an accumulator value of *nil*. More specifically, `fold-left` returns *nil* if the *lists* are empty. If they are not empty, *combine* is first applied to *nil* and the respective first elements of the *lists* in order. The result becomes the new accumulator value, and *combine* is applied to the new accumulator value and the respective next elements of the *list*. This step is repeated until the end of the list is reached; then the accumulator value is returned. *Combine* is always called in the same dynamic environment as `fold-left` itself.

```

(fold-left + 0 '(1 2 3 4 5))=> 15

(fold-left (lambda (a e) (cons e a)) '()
  '(1 2 3 4 5))
  => (5 4 3 2 1)

(fold-left (lambda (count x)
  (if (odd? x) (+ count 1) count))
  0
  '(3 1 4 1 5 9 2 6 5 3))
  => 7

(fold-left (lambda (max-len s)
  (max max-len (string-length s)))
  0
  ("longest" "long" "longer"))
  => 7

(fold-left cons '(q) '(a b c))
  => (((q) . a) . b) . c

(fold-left + 0 '(1 2 3) '(4 5 6))
  => 21

```

*Implementation responsibilities:* The implementation should check that the *lists* all have the same length. The implementation must check the restrictions on *combine* to the extent performed by applying it as described.

```

(fold-right combine nil list1 list2 ... listn) procedure

```

The *lists* should all have the same length. *Combine* must be a procedure. It should accept one more argument than there are *lists* and return a single value. *Combine* should not mutate the *list* arguments. The `fold-right` procedure iterates the *combine* procedure over the elements of the *lists* from right to left and an accumulator value, starting with an accumulator value of *nil*. More specifically, `fold-right` returns *nil* if the *lists* are empty. If they are not empty, *combine* is first applied to the respective last elements of the *lists* in order and *nil*. The result becomes the new accumulator value, and *combine* is applied to the respective previous elements of the *lists* and the new accumulator value. This step is repeated until the beginning of

the list is reached; then the accumulator value is returned. *Proc* is always called in the same dynamic environment as `fold-right` itself.

```
(fold-right + 0 '(1 2 3 4 5)) ⇒ 15

(fold-right cons '() '(1 2 3 4 5))
  ⇒ (1 2 3 4 5)

(fold-right (lambda (x l)
              (if (odd? x) (cons x l) l))
            '()
            '(3 1 4 1 5 9 2 6 5))
  ⇒ (3 1 1 5 9 5)

(fold-right cons '(q) '(a b c))
  ⇒ (a b c q)

(fold-right + 0 '(1 2 3) '(4 5 6))
  ⇒ 21
```

*Implementation responsibilities:* The implementation should check that the *lists* all have the same length. The implementation must check the restrictions on *combine* to the extent performed by applying it as described.

```
(remq proc list)           procedure
(remove obj list)         procedure
(remv obj list)           procedure
(remq obj list)           procedure
```

*Proc* should accept one argument and return a single value. *Proc* should not mutate *list*. Each of these procedures returns a list of the elements of *list* that do not satisfy a given condition. The `remq` procedure applies *proc* to each element of *list* and returns a list of the elements of *list* for which *proc* returned `#f`. *Proc* is always called in the same dynamic environment as `remq` itself. The `remove`, `remv`, and `remq` procedures return a list of the elements that are not *obj*. The `remq` procedure uses `eq?` to compare *obj* with the elements of *list*, while `remv` uses `eqv?` and `remove` uses `equal?`. The elements of the result list are in the same order as they appear in the input list. If multiple returns occur from `remq`, the return values returned by earlier returns are not mutated.

```
(remq even? '(3 1 4 1 5 9 2 6 5))
  ⇒ (3 1 1 5 9 5)

(remove 1 '(3 1 4 1 5 9 2 6 5))
  ⇒ (3 4 5 9 2 6 5)

(remv 1 '(3 1 4 1 5 9 2 6 5))
  ⇒ (3 4 5 9 2 6 5)

(remq 'foo '(bar foo baz)) ⇒ (bar baz)
```

*Implementation responsibilities:* The implementation must check the restrictions on *proc* to the extent performed by applying it as described.

```
(memp proc list)           procedure
(member obj list)         procedure
(memv obj list)           procedure
(memq obj list)           procedure
```

*Proc* should accept one argument and return a single value. *Proc* should not mutate *list*.

These procedures return the first sublist of *list* whose car satisfies a given condition, where the sublists of *lists* are the lists returned by `(list-tail list k)` for *k* less than the length of *list*. The `memp` procedure applies *proc* to the cars of the sublists of *list* until it finds one for which *proc* returns a true value, without traversing *list* further. *Proc* is always called in the same dynamic environment as `memp` itself. The `member`, `memv`, and `memq` procedures look for the first occurrence of *obj*. If *list* does not contain an element satisfying the condition, then `#f` (not the empty list) is returned. The `member` procedure uses `equal?` to compare *obj* with the elements of *list*, while `memv` uses `eqv?` and `memq` uses `eq?`.

```
(memp even? '(3 1 4 1 5 9 2 6 5))
  ⇒ (4 1 5 9 2 6 5)

(memq 'a '(a b c))        ⇒ (a b c)
(memq 'b '(a b c))        ⇒ (b c)
(memq 'a '(b c d))        ⇒ #f
(memq (list 'a) '(b (a) c)) ⇒ #f
(member (list 'a)
        '(b (a) c))        ⇒ ((a) c)
(memq 101 '(100 101 102)) ⇒ unspecified
(memv 101 '(100 101 102)) ⇒ (101 102)
```

*Implementation responsibilities:* The implementation must check that *list* is a chain of pairs up to the found element, or that it is indeed a list if no element is found. It should not check that it is a chain of pairs beyond the found element. The implementation must check the restrictions on *proc* to the extent performed by applying it as described.

```
(assp proc alist)         procedure
(assoc obj alist)         procedure
(assv obj alist)         procedure
(assq obj alist)         procedure
```

*Alist* (for “association list”) should be a list of pairs. *Proc* should accept one argument and return a single value. *Proc* should not mutate *alist*.

These procedures find the first pair in *alist* whose car field satisfies a given condition, and returns that pair without traversing *alist* further. If no pair in *alist* satisfies the

condition, then `#f` is returned. The `assp` procedure successively applies `proc` to the car fields of `alist` and looks for a pair for which it returns a true value. `Proc` is always called in the same dynamic environment as `assp` itself. The `assoc`, `assv`, and `assq` procedures look for a pair that has `obj` as its car. The `assoc` procedure uses `equal?` to compare `obj` with the car fields of the pairs in `alist`, while `assv` uses `eqv?` and `assq` uses `eq?`.

*Implementation responsibilities:* The implementation must check that `alist` is a chain of pairs containing pairs up to the found pair, or that it is indeed a list of pairs if no element is found. It should not check that it is a chain of pairs beyond the found element. The implementation must check the restrictions on `proc` to the extent performed by applying it as described.

```
(define d '((3 a) (1 b) (4 c)))

(assp even? d)           => (4 c)
(assp odd? d)           => (3 a)

(define e '((a 1) (b 2) (c 3)))
(assq 'a e)             => (a 1)
(assq 'b e)             => (b 2)
(assq 'd e)             => #f
(assq (list 'a) '((a) ((b)) ((c))))
                        => #f
(assoc (list 'a) '((a) ((b)) ((c))))
                        => ((a))
(assq 5 '((2 3) (5 7) (11 13)))
                        => unspecified
(assv 5 '((2 3) (5 7) (11 13)))
                        => (5 7)
```

```
(cons* obj1 ... objn obj)      procedure
(cons* obj)                     procedure
```

If called with at least two arguments, `cons*` returns a freshly allocated chain of pairs whose cars are `obj1`, ..., `objn`, and whose last cdr is `obj`. If called with only one argument, `cons*` returns that argument.

```
(cons* 1 2 '(3 4 5))          => (1 2 3 4 5)
(cons* 1 2 3)                 => (1 2 . 3)
(cons* 1)                     => 1
```

## 4. Sorting

This chapter describes the `(rnrs sorting (6))` library for sorting lists and vectors.

```
(list-sort proc list)         procedure
(vector-sort proc vector)     procedure
```

*Proc* should accept any two elements of the list or vector, and should not have any side effects. *Proc* should return a true value when its first argument is strictly less than its second, and `#f` otherwise.

The `list-sort` and `vector-sort` procedures perform a stable sort of `list` or `vector` in ascending order according to `proc`, without changing `list` or `vector` in any way. The `list-sort` procedure returns a list, and `vector-sort` returns a vector. The results may be `eq?` to the argument when the argument is already sorted, and the result of `list-sort` may share structure with a tail of the original list. The sorting algorithm performs  $O(n \lg n)$  calls to `proc` where  $n$  is the length of `list` or `vector`, and all arguments passed to `proc` are elements of the list or vector being sorted, but the pairing of arguments and the sequencing of calls to `proc` are not specified.

```
(list-sort < '(3 5 2 1))      => (1 2 3 5)
(vector-sort < '#(3 5 2 1))  => #(1 2 3 5)
```

*Implementation responsibilities:* The implementation must check the restrictions on `proc` to the extent performed by applying it as described.

```
(vector-sort! proc vector)    procedure
```

*Proc* should accept any two elements of the vector, and should not have any side effects. *Proc* should return a true value when its first argument is strictly less than its second, and `#f` otherwise.

The `vector-sort!` procedure destructively sorts `vector` in ascending order according to `proc`. The sorting algorithm performs  $O(n^2)$  calls to `proc` where  $n$  is the length of `vector`, and all arguments passed to `proc` are elements of the vector being sorted, but the pairing of arguments and the sequencing of calls to `proc` are not specified. The sorting algorithm may be unstable. The procedure returns unspecified values.

```
(define v (vector 3 5 2 1))
(vector-sort! v)              => unspecified
v                             => #(1 2 3 5)
```

*Implementation responsibilities:* The implementation must check the restrictions on `proc` to the extent performed by applying it as described.

## 5. Control structures

This chapter describes the `(rnrs control (6))` library.

```
(when (test) <expression1> <expression2> ...)  syntax
(unless (test) <expression1> <expression2> ...) syntax
```

*Syntax:* `<Test>` must be an expression.

*Semantics:* A `when` expression is evaluated by evaluating the `<test>` expression. If `<test>` evaluates to a true value, the remaining `<expression>`s are evaluated in order, and the results of the last `<expression>` are returned as the results of the entire `when` expression. Otherwise, the `when` expression

returns unspecified values. An `unless` expression is evaluated by evaluating the `<test>` expression. If `<test>` evaluates to `#f`, the remaining `<expression>`s are evaluated in order, and the results of the last `<expression>` are returned as the results of the entire `unless` expression. Otherwise, the `unless` expression returns unspecified values.

```
(when (> 3 2) 'greater)    ⇒ greater
(when (< 3 2) 'greater)    ⇒ unspecified
(unless (> 3 2) 'less)     ⇒ unspecified
(unless (< 3 2) 'less)     ⇒ less
```

The `when` and `unless` expressions are derived forms. They could be defined in terms of base library forms by the following macros:

```
(define-syntax when
  (syntax-rules ()
    ((when test result1 result2 ...)
     (if test
         (begin result1 result2 ...))))))
```

```
(define-syntax unless
  (syntax-rules ()
    ((unless test result1 result2 ...)
     (if (not test)
         (begin result1 result2 ...))))))
```

```
(do ((<variable1> <init1> <step1>)          syntax
     ...)
    (<test> <expression> ...)
    <command> ...)
```

*Syntax:* The `<init>`s, `<step>`s, `<test>`s, and `<command>`s must be expressions. The `<variable>`s must be pairwise distinct variables.

*Semantics:* The `do` expression is an iteration construct. It specifies a set of variables to be bound, how they are to be initialized at the start, and how they are to be updated on each iteration.

A `do` expression is evaluated as follows: The `<init>` expressions are evaluated (in some unspecified order), the `<variable>`s are bound to fresh locations, the results of the `<init>` expressions are stored in the bindings of the `<variable>`s, and then the iteration phase begins.

Each iteration begins by evaluating `<test>`; if the result is `#f`, then the `<command>`s are evaluated in order for effect, the `<step>` expressions are evaluated in some unspecified order, the `<variable>`s are bound to fresh locations holding the results, and the next iteration begins.

If `<test>` evaluates to a true value, the `<expression>`s are evaluated from left to right and the values of the last `<expression>` are returned. If no `<expression>`s are present, then the values of the `do` expression are unspecified.

The region of the binding of a `<variable>` consists of the entire `do` expression except for the `<init>`s. It is a syntax

violation for a `<variable>` to appear more than once in the list of `do` variables.

A `<step>` may be omitted, in which case the effect is the same as if `(<variable> <init> <variable>)` had been written instead of `(<variable> <init>)`.

If a `do` expression appears in a tail context, the `<expression>`s are a `<tail sequence>` in the sense of report section 9.21, i.e., the last `<expression>` is also in a tail context.

```
(do ((vec (vec (make-vector 5)))
     (i 0 (+ i 1)))
    ((= i 5) vec)
    (vector-set! vec i i))    ⇒ #(0 1 2 3 4)

(let ((x '(1 3 5 7 9)))
  (do ((x x (cdr x))
      (sum 0 (+ sum (car x))))
      ((null? x) sum)))      ⇒ 25
```

The following definition of `do` uses a trick to expand the variable clauses.

```
(define-syntax do
  (syntax-rules ()
    ((do ((var init step ...) ...)
         (test expr ...)
         command ...)
     (letrec
       ((loop
         (lambda (var ...)
           (if test
              (begin
                #f ; avoid empty begin
                expr ...)
              (begin
                command
                ...
                (loop (do "step" var step ...)
                      ...))))))
        (loop init ...)))
     ((do "step" x)
      x)
     ((do "step" x y)
      y)))
```

```
(case-lambda <clause> ...)          syntax
```

*Syntax:* Each `<clause>` must be of the form

```
((formals) <body>)
```

`<Formals>` must be as in a `lambda` form (report section 9.5.2), and `<body>` is as described in report section 9.4.

*Semantics:* A `case-lambda` expression evaluates to a procedure. This procedure, when applied, tries to match its arguments to the `<clause>`s in order. The arguments match a clause if one of the following conditions is fulfilled:

- $\langle \text{Formals} \rangle$  has the form  $\langle \langle \text{variable} \rangle \dots \rangle$  and the number of arguments is the same as the number of formal parameters in  $\langle \text{formals} \rangle$ .
- $\langle \text{Formals} \rangle$  has the form  $\langle \langle \text{variable}_1 \rangle \dots \langle \text{variable}_n \rangle . \langle \text{variable}_{n+1} \rangle \rangle$  and the number of arguments is at least  $n$ .
- $\langle \text{Formals} \rangle$  has the form  $\langle \text{variable} \rangle$ .

For the first clause matched by the arguments, the variables of the  $\langle \text{formals} \rangle$  are bound to fresh locations containing the argument values in the same arrangement as with `lambda`.

If the arguments match none of the clauses, an exception with condition type `&assertion` is raised.

```
(define foo
  (case-lambda
    (() 'zero)
    ((x) (list 'one x))
    ((x y) (list 'two x y))
    ((a b c d . e) (list 'four a b c d e))
    (rest (list 'rest rest))))

(foo)           ⇒ zero
(foo 1)        ⇒ (one 1)
(foo 1 2)      ⇒ (two 1 2)
(foo 1 2 3)    ⇒ (rest (1 2 3))
(foo 1 2 3 4)  ⇒ (four 1 2 3 4 ())
```

The `case-lambda` keyword can be defined in terms of `lambda` by the following macros:

```
(define-syntax case-lambda
  (syntax-rules ()
    ((_ (fmls b1 b2 ...))
     (lambda fmls b1 b2 ...))
    ((_ (fmls b1 b2 ...) ...)
     (lambda args
       (let ((n (length args)))
         (case-lambda-help args n
          (fmls b1 b2 ...) ...))))))

(define-syntax case-lambda-help
  (syntax-rules ()
    ((_ args n)
     (assertion-violation #f
      "unexpected number of arguments")
     ((_ args n ((x ...) b1 b2 ...) more ...)
      (if (= n (length '(x ...)))
          (apply (lambda (x ...) b1 b2 ...) args)
          (case-lambda-help args n more ...)))
     ((_ args n ((x1 x2 ... . r) b1 b2 ...) more ...)
      (if (>= n (length '(x1 x2 ...)))
          (apply (lambda (x1 x2 ... . r) b1 b2 ...)
                 args)
          (case-lambda-help args n more ...)))
     ((_ args n (r b1 b2 ...) more ...)
      (apply (lambda r b1 b2 ... ) args))))))
```

## 6. Records

This section describes abstractions for creating new data types representing records—data structures with named fields. The record mechanism comes in three libraries:

- the `(rnrs records procedural (6))` library, a procedural layer for creating and manipulating record types and record instances;
- the `(rnrs records syntactic (6))` library, a syntactic layer for defining record types and various procedures to manipulate the record type; and
- the `(rnrs records inspection (6))` library, a set of inspection procedures.

The procedural layer allows programs to construct new record types and the associated procedures for creating and manipulating records dynamically. It is particularly useful for writing interpreters that construct host-compatible record types. It may also serve as a target for expansion of the syntactic layers.

The syntactic layer provides a basic syntactic interface whereby a single record definition serves as a shorthand for the definition of several record creation and manipulation routines: a constructor, a predicate, field accessors, and field mutators. The layer allows the programmer to name each of these procedures explicitly, but also provides shorthands for naming them implicitly through a set of naming conventions.

Each of these layers permits record types to be extended via single inheritance, allowing record types to model hierarchies that occur in applications like algebraic data types as well as single-inheritance class systems.

Each of the layers also supports generative and nongenerative record types.

The inspection procedures allow programs to obtain from a record instance a descriptor for the type and from there obtain access to the fields of the record instance. This facility allows the creation of portable printers and inspectors. A program may prevent access to a record's type—and thereby protect the information stored in the record from the inspection mechanism—by declaring the type opaque. Thus, opacity as presented here can be used to enforce abstraction barriers.

This section uses the *rtd* and *constructor-descriptor* parameter names for arguments that must be record-type descriptors and constructor descriptors, respectively (see section 6.2).

### 6.1. Mutability and equivalence

The fields of a record type are designated *mutable* or *immutable*. Correspondingly, a record type with no mutable

field is called *immutable*, and all records of that type are immutable objects. All other record types are *mutable*, and so are their records.

Each call to a record constructor returns a new record with a fresh location (see report section 4.8). Consequently, for two records *obj<sub>1</sub>* and *obj<sub>2</sub>*, the return value of (`eqv? obj1 obj2`), adheres to the following criteria (see report section 9.6):

- If *obj<sub>1</sub>* and *obj<sub>2</sub>* have different record types (i.e., their record-type descriptors are not `eqv?`), `eqv?` returns `#f`.
- If *obj<sub>1</sub>* and *obj<sub>2</sub>* are both records of the same record type, and are the results of two separate calls to record constructors, then `eqv?` returns `#f`.
- If *obj<sub>1</sub>* and *obj<sub>2</sub>* are both records of the same record type, and both are the result of a single call to a record constructor, then `eqv?` returns `#t`.
- If *obj<sub>1</sub>* and *obj<sub>2</sub>* are both records of the same record type, where applying the same accessor to both yields results for which `eqv?` returns `#f`.

## 6.2. Procedural layer

The procedural layer is provided by the (`rnrs records procedural (6)`) library.

```
(make-record-type-descriptor name procedure
  parent uid sealed? opaque? fields)
```

Returns a *record-type descriptor*, or *rtd*, representing a record type distinct from all built-in types and other record types.

The *name* argument must be a symbol. It names the record type, and is intended purely for informational purposes and may be used for printing by the underlying Scheme system.

The *parent* argument must be either `#f` or an *rtd*. If it is an *rtd*, the returned record type, *t*, extends the record type *p* represented by *parent*. Each record of type *t* is also a record of type *p*, and all operations applicable to a record of type *p* are also applicable to a record of type *t*, except for inspection operations if *t* is opaque but *p* is not. An exception with condition type `&assertion` is raised if *parent* is sealed (see below).

The extension relationship is transitive in the sense that a type extends its parent's parent, if any, and so on. A record type that does not extend another record type is called a *base record type*.

The *uid* argument must be either `#f` or a symbol. If *uid* is a symbol, the record-creation operation is *nongenerative*

i.e., a new record type is created only if no previous call to `make-record-type-descriptor` was made with the *uid*. If *uid* is `#f`, the record-creation operation is *generative*, i.e., a new record type is created even if a previous call to `make-record-type-descriptor` was made with the same arguments.

If `make-record-type-descriptor` is called twice with the same *uid* symbol, the parent arguments in the two calls must be `eqv?`, the *fields* arguments `equal?`, the *sealed?* arguments boolean-equivalent (both `#f` or both true), and the *opaque?* arguments boolean-equivalent. If these conditions are not met, an exception with condition type `&assertion` is raised when the second call occurs. If they are met, the second call returns, without creating a new record type, the same record-type descriptor (in the sense of `eqv?`) as the first call.

*Note:* Users are encouraged to use symbol names constructed using the UUID namespace (for example, using the record-type name as a prefix) for the *uid* argument.

The *sealed?* flag must be a boolean. If true, the returned record type is sealed, i.e., it cannot be extended.

The *opaque?* flag must be a boolean. If true, the record type is opaque. If passed an instance of the record type, `record?` returns `#f`. Moreover, if `record-rtd` (see “Inspection” below) is called an instance of the record type, an exception with condition type `&assertion` is raised. The record type is also opaque if an opaque parent is supplied. If *opaque?* is `#f` and an opaque parent is not supplied, the record is not opaque.

The *fields* argument must be a vector of field specifiers. Each field specifier must be a list of the form (`mutable name`) or a list of the form (`immutable name`). Each name must be a symbol and names the corresponding field of the record type; the names need not be distinct. A field identified as mutable may be modified, whereas, when a program attempts to obtain a mutator for a field identified as immutable, an exception with condition type `&assertion` is raised. Where field order is relevant, e.g., for record construction and field access, the fields are considered to be ordered as specified, although no particular order is required for the actual representation of a record instance.

The specified fields are added to the parent fields, if any, to determine the complete set of fields of the returned record type. If *fields* is modified after `make-record-type` has been called, the effect on the returned *rtd* is unspecified.

A record type is considered immutable if all fields in its complete set of fields is immutable, and is mutable otherwise.

A generative record-type descriptor created by a call to `make-record-type-descriptor` is not `eqv?` to any record-type descriptor (generative or nongenerative) created by

another call to `make-record-type-descriptor`. A generative record-type descriptor is `eqv?` only to itself, i.e.,  $(\text{eqv? } rtd_1 \ rtd_2) \text{ iff } (\text{eq? } rtd_1 \ rtd_2)$ . Also, two nongenerative record-type descriptors are `eqv?` iff they were created by calls to `make-record-type-descriptor` with the same uid arguments.

`(record-type-descriptor? obj)` procedure  
Returns `#t` if the argument is a record-type descriptor, `#f` otherwise.

`(make-record-creator-descriptor rtd procedure parent-creator-descriptor protocol)`

Returns a *record-creator descriptor* (or *creator descriptor* for short) that specifies a *record creator* (or *creator* for short), that can be used to construct record values of the type specified by *rtd*, and which can be obtained via `record-creator`. A creator descriptor can also be used to create other creator descriptors for subtypes of its own record type. *Rtd* must be a record-type descriptor. *Protocol* must be a procedure or `#f`. If it is `#f`, a default *protocol* procedure is supplied.

If *protocol* is a procedure, it is called by `record-creator` with a single argument *p* and should return a procedure that creates and returns an instance of the record type using *p* as described below. The role of *p* differs depending on the kind of record type represented by *rtd*:

If *rtd* is a base record type, then *parent-creator-descriptor* must be `#f`. In this case, *protocol*'s argument *p* is a procedure that expects one argument for every field of *rtd* and returns a record with the fields of *rtd* initialized to these arguments. The procedure returned by *protocol* should call *p* once with the number of arguments it expects and return the resulting record as shown in the simple example below:

```
(lambda (p)
  (lambda (v1 v2 v3)
    (p v1 v2 v3)))
```

Here, the call to `p` returns a record whose fields are initialized with the values of *v1*, *v2*, and *v3*. The expression above is equivalent to `(lambda (p) p)`. Note that the procedure returned by *protocol* is otherwise unconstrained; specifically, it can take any number of arguments.

If *rtd* is an extension of another record type *parent-rtd*, *parent-creator-descriptor* must be a creator descriptor of *parent-rtd* or `#f`. If *parent-creator-descriptor* or *protocol* is `#f`, *protocol* must also be `#f`, and a default creator descriptor is assumed as described below.

If *parent-creator-descriptor* is a creator descriptor and *protocol* is a procedure, then its argument *p* is a procedure that accepts the same number of arguments as the

creator of *parent-creator-descriptor* and returns a procedure *new* that, when called, constructs the record itself. The *new* procedure expects one argument for every field of *rtd* (not including parent fields) and returns a record with the fields of *rtd* initialized to these arguments, and the fields of *parent-rtd* and its parents initialized as specified by *parent-creator-descriptor*.

The procedure returned by *protocol* should call *p* once with the number of arguments it expects, call the procedure it returns once with number of arguments it expects and return the resulting record. A simple *protocol* in this case might be written as follows:

```
(lambda (p)
  (lambda (v1 v2 v3 x1 x2 x3 x4)
    (let ((new (p v1 v2 v3)))
      (new x1 x2 x3 x4))))
```

This passes arguments *v1*, *v2*, *v3* to *p* for *parent-creator-descriptor* and calls `new` with *x1*, ..., *x4* to initialize the fields of *rtd* itself.

Thus, the creator descriptors for a record type form a sequence of protocols exactly parallel to the sequence of record-type parents. Each creator descriptor in the chain determines the field values for the associated record type. Child record creators need not know the number or contents of parent fields, only the number of arguments required by the parent creator.

*Protocol* may be `#f`, specifying a default value that accepts one argument for each field of *rtd* (not including the fields of its parent type, if any). Specifically, if *rtd* is a base type, the default *protocol* procedure behaves as if it were `(lambda (p) p)`. If *rtd* is an extension of another type, then *parent-creator-descriptor* must be either `#f` or itself specify a default creator. In this case, the default *protocol* procedure behaves as if it were:

```
(lambda (p)
  (lambda (v1 ... vj x1 ... xk)
    (let ((new (p v1 ... vj)))
      (new x1 ... xk))))
```

The resulting creator accepts one argument for each of the record type's complete set of fields (including those of the parent record type, the parent's parent record type, etc.) and returns a record with the fields initialized to those arguments, with the field values for the parent coming before those of the extension in the argument list. (In the example, *j* is the complete number of fields of the parent type, and *k* is the number of fields of *rtd* itself.)

*Implementation responsibilities:* If *protocol* is a procedure, the implementation must check the restrictions on it to the extent performed by applying it as described when the creator is called.

`(record-creator creator-descriptor)` procedure  
Calls the *protocol* of *creator-descriptor* (as described for `make-record-creator-descriptor`) and returns

the resulting constructor *constructor* for records of the record type associated with *constructor-descriptor*.

(record-predicate *rtd*) procedure

Returns a procedure that, given an object *obj*, returns a boolean that is #t iff *obj* is a record of the type represented by *rtd*.

(record-accessor *rtd k*) procedure

*K* must be a valid field index of *rtd*. The record-accessor procedure returns a one-argument procedure that, given a record of the type represented by *rtd*, returns the value of the selected field of that record.

The field selected is the one corresponding the *k*th element (0-based) of the *fields* argument to the invocation of `make-record-type-descriptor` that created *rtd*. Note that *k* cannot be used to specify a field of any type *rtd* extends.

If the accessor procedure is given something other than a record of the type represented by *rtd*, an exception with condition type `&assertion` is raised. Records of the type represented by *rtd* include records of extensions of the type represented by *rtd*.

(record-mutator *rtd k*) procedure

*K* must be a valid field index of *rtd*. The record-mutator procedure returns a two-argument procedure that, given a record *r* of the type represented by *rtd* and an object *obj*, stores *obj* within the field of *r* specified by *k*. The *k* argument is as in `record-accessor`. If *k* specifies an immutable field, an exception with condition type `&assertion` is raised. The mutator returns unspecified values.

```
(define :point
  (make-record-type-descriptor
    'point #f
    #f #f #f
    '#((mutable x) (mutable y))))

(define :point-cd
  (make-record-constructor-descriptor :point #f #f))

(define make-point (record-constructor :point-cd))

(define point? (record-predicate :point))
(define point-x (record-accessor :point 0))
(define point-y (record-accessor :point 1))
(define point-x-set! (record-mutator :point 0))
(define point-y-set! (record-mutator :point 1))

(define p1 (make-point 1 2))
(point? p1)           => #t
(point-x p1)         => 1
```

```
(point-y p1)           => 2
(point-x-set! p1 5)   => unspecified
(point-x p1)          => 5
```

```
(define :point2
  (make-record-type-descriptor
    'point2 :point
    #f #f #f '#((mutable x) (mutable y))))

(define make-point2
  (record-constructor
    (make-record-constructor-descriptor :point2
    #f #f)))

(define point2? (record-predicate :point2))
(define point2-xx (record-accessor :point2 0))
(define point2-yy (record-accessor :point2 1))
```

```
(define p2 (make-point2 1 2 3 4))
(point? p2)           => #t
(point-x p2)          => 1
(point-y p2)          => 2
(point2-xx p2)        => 3
(point2-yy p2)        => 4
```

```
(define :point-cd/abs
  (make-record-constructor-descriptor
    :point #f
    (lambda (new)
      (lambda (x y)
        (new (abs x) (abs y))))))
```

```
(define make-point/abs
  (record-constructor :point-cd/abs))
```

```
(point-x (make-point/abs -1 -2))
=> 1
(point-y (make-point/abs -1 -2))
=> 2
```

```
(define :cpoint
  (make-record-type-descriptor
    'cpoint :point
    #f #f #f
    '#((mutable rgb))))

(define make-cpoint
  (record-constructor
    (make-record-constructor-descriptor
    :cpoint :point-cd
    (lambda (p)
      (lambda (x y c)
        ((p x y) (color->rgb c)))))))
```

```
(define make-cpoint/abs
  (record-constructor
    (make-record-constructor-descriptor
    :cpoint :point-cd/abs
    (lambda (p)
      (lambda (x y c)
        ((p x y) (color->rgb c)))))))
```

```

(define cpoint-rgb
  (record-accessor :cpoint 0))

(define (color->rgb c)
  (cons 'rgb c))

(cpoint-rgb (make-cpoint -1 -3 'red)
  ⇒ (rgb . red)
(point-x (make-cpoint -1 -3 'red))
  ⇒ -1
(point-x (make-cpoint/abs -1 -3 'red))
  ⇒ 1

```

### 6.3. Syntactic layer

The syntactic layer is provided by the `(rnrs records syntactic (6))` library.

The record-type-defining form `define-record-type` is a definition and can appear anywhere any other `<definition>` can appear.

```

(define-record-type <name spec> <record clause>*)
                                     syntax

```

A `define-record-type` form defines a record type along with associated constructor descriptor and constructor, predicate, field accessors, and field mutators. The `define-record-type` form expands into a set of definitions in the environment where `define-record-type` appears; hence, it is possible to refer to the bindings (except for that of the record type itself) recursively.

The `<name spec>` specifies the names of the record type, constructor, and predicate. It must take one of the following forms:

```

(<record name> <constructor name> <predicate name>)
<record name>

```

`<Record name>`, `<constructor name>`, and `<predicate name>` must all be identifiers.

`<Record name>`, taken as a symbol, becomes the name of the record type. Additionally, it is bound by this definition to an expand-time or run-time description of the record type for use as parent name in syntactic record-type definitions that extend this definition. It may also be used as a handle to gain access to the underlying record-type descriptor and constructor descriptor (see `record-type-descriptor` and `record-constructor-descriptor` below).

`<Constructor name>` is defined by this definition to be a constructor for the defined record type, with a protocol specified by the `protocol` clause, or, in its absence, using

a default protocol. For details, see the description of the `protocol` clause below.

`<Predicate name>` is defined by this definition to a predicate for the defined record type.

The second form of `<name spec>` is an abbreviation for the first form, where the name of the constructor is generated by prefixing the record name with `make-`, and the predicate name is generated by adding a question mark (?) to the end of the record name. For example, if the record name is `frob`, the name of the constructor is `make-frob`, and the predicate name is `frob?`.

Each `<record clause>` must take one of the following forms; it is a syntax violation if multiple `<record clause>`s of the same kind appear in a `define-record-type` form.

- `(fields <field spec>*)`

where each `<field spec>` has one of the following forms

```

(immutable <field name> <accessor name>)
(mutable <field name>
  <accessor name> <mutator name>)
(immutable <field name>)
(mutable <field name>)
<field name>

```

`<Field name>`, `<accessor name>`, and `<mutator name>` must all be identifiers. The first form declares an immutable field called `<field name>`, with the corresponding accessor named `<accessor name>`. The second form declares a mutable field called `<field name>`, with the corresponding accessor named `<accessor name>`, and with the corresponding mutator named `<mutator name>`.

If `<field spec>` takes the second or third form, the accessor name is generated by appending the record name and field name with a hyphen separator, and the mutator name (for a mutable field) is generated by adding a `-set!` suffix to the accessor name. For example, if the record name is `frob` and the field name is `widget`, the accessor name is `frob-widget` and the mutator name is `frob-widget-set!`.

If `<field spec>` is just a `<field name>` form, it is an abbreviation for `(immutable <field name>)`.

The `<field name>`s become, as symbols, the names of the fields of the record type being created, in the same order. They are not used in any other way.

The `fields` clause may be absent; this is equivalent to an empty `fields` clause.

- `(parent <parent name>)`

Specifies that the record type is to have parent type `<parent name>`, where `<parent name>` is the

`<record name>` of a record type previously defined using `define-record-type`. The absence of a `parent` clause implies a record type with no parent type.

- `(protocol <expression>)`

`<Expression>` is evaluated in the same environment as the `define-record-type` form, and must evaluate to a protocol appropriate for the record type being defined (see the description of `make-record-constructor-descriptor`). The protocol is used to create a record-constructor descriptor where, if the record type being defined has a parent, the parent-type constructor descriptor is the one associated with the parent type specified in the `parent` clause.

If no `protocol` clause is specified, a constructor descriptor is still created using a default protocol. The rules for this are the same as for `make-record-constructor-descriptor`: the clause can be absent only if the record type defined has no parent type, or if the parent definition does not specify a protocol.

- `(sealed #t)`  
`(sealed #f)`

If this option is specified with operand `#t`, the defined record type is sealed. If this option is specified with operand `#f`, or is absent, the defined record type is not sealed.

- `(opaque #t)`  
`(opaque #f)`

If this option is specified with operand `#t`, or if an opaque parent record type is specified, the defined record type is opaque. Otherwise, the defined record type is not opaque.

- `(nongenerative <uid>)`  
`(nongenerative)`

This specifies that the record type is nongenerative with `uid <uid>`, which must be an `<identifier>`. If `<uid>` is absent, a unique `uid` is generated at macro-expansion time. If two record-type definitions specify the same `uid`, then the implied arguments to `make-record-type-descriptor` must be equivalent as described under `make-record-type-descriptor`. If this condition is not met, it is either considered a syntax violation or an exception with condition type `&assertion` is raised. If the condition is met, a single record type is generated for both definitions.

In the absence of a `nongenerative` clause, a new record type is generated every time a `define-record-type` form is evaluated:

```
(let ((f (lambda (x)
           (define-record-type r ...
             (if x r? (make-r ...))))))
      ((f #t) (f #f)))      ⇒ #f
```

All bindings created by `define-record-type` (for the record type, the constructor, the predicate, the accessors, and the mutators) must have names that are pairwise distinct.

The `fields`, `mutable`, `immutable`, `parent`, `protocol`, `sealed`, `opaque`, and `nongenerative` identifiers are all exported by the `(rnrs records syntactic (6))` library with level 0. Referring to one of these identifiers out of place is a syntax violation.

Any definition that takes advantage of implicit naming for the constructor, predicate, accessor, and mutator names, can be rewritten trivially to a definition that specifies all names explicitly. For example, the implicit-naming record definition:

```
(define-record-type frob
  (fields (mutable widget))
  (protocol
    (lambda (c) (lambda (n) (c (make-widget n))))))
```

is equivalent to the following explicit-naming record definition.

```
(define-record-type (frob make-frob frob?)
  (fields (mutable widget
           frob-widget frob-widget-set!))
  (protocol
    (lambda (c) (lambda (n) (c (make-widget n))))))
```

Also, the implicit-naming record definition:

```
(define-record-type point (fields x y))
```

is equivalent to the following explicit-naming record definition:

```
(define-record-type (point make-point point?)
  (fields
    (immutable x point-x)
    (immutable y point-y)))
```

With implicit naming, one can choose to specify just some of the names explicitly; for example, the following overrides the choice of accessor and mutator names for the `widget` field.

```
(define-record-type frob
  (fields (mutable widget getwid setwid!))
  (protocol
    (lambda (c) (c (make-widget n))))))
```

(record-type-descriptor <record name>)      syntax

Evaluates to the record-type descriptor associated with the type specified by <record-name>.

Note that `record-type-descriptor` works on both opaque and non-opaque record types.

(record-constructor-descriptor <record name>)      syntax

Evaluates to the record-creator descriptor associated with <record name>.

```
(define-record-type (point make-point point?)
  (fields (immutable x point-x)
          (mutable y point-y set-point-y!))
  (nongenerative
   point-4893d957-e00b-11d9-817f-00111175eb9e))
```

```
(define-record-type (cpoint make-cpoint cpoint?)
  (parent point)
  (protocol
   (lambda (p)
     (lambda (x y c)
       ((p x y) (color->rgb c)))))
  (fields
   (mutable rgb cpoint-rgb cpoint-rgb-set!)))
```

```
(define (color->rgb c)
  (cons 'rgb c))
```

```
(define p1 (make-point 1 2))
(define p2 (make-cpoint 3 4 'red))
```

```
(point? p1)           => #t
(point? p2)           => #t
(point? (vector))     => #f
(point? (cons 'a 'b)) => #f
(cpoint? p1)          => #f
(cpoint? p2)          => #t
(point-x p1)           => 1
(point-y p1)           => 2
(point-x p2)           => 3
(point-y p2)           => 4
(cpoint-rgb p2)        => (rgb . red)
```

```
(set-point-y! p1 17)
(point-y p1)           => 17)
```

```
(record-rtd p1)
  => (record-type-descriptor point)
```

```
(define-record-type (ex1 make-ex1 ex1?)
  (protocol (lambda (new) (lambda a (new a))))
  (fields (immutable f ex1-f)))
```

```
(define ex1-i1 (make-ex1 1 2 3))
(ex1-f ex1-i1)   => (1 2 3)
```

```
(define-record-type (ex2 make-ex2 ex2?)
```

```
(protocol
  (lambda (new) (lambda (a . b) (new a b))))
(fields (immutable a ex2-a)
        (immutable b ex2-b)))
```

```
(define ex2-i1 (make-ex2 1 2 3))
(ex2-a ex2-i1)   => 1
(ex2-b ex2-i1)   => (2 3)
```

```
(define-record-type (unit-vector
  make-unit-vector
  unit-vector?)
  (protocol
   (lambda (new)
     (lambda (x y z)
       (let ((length
              (sqrt (+ (* x x) (* y y) (* z z)))))
         (new (/ x length)
              (/ y length)
              (/ z length))))))
  (fields (immutable x unit-vector-x)
          (immutable y unit-vector-y)
          (immutable z unit-vector-z)))
```

```
(define *ex3-instance* #f)
```

```
(define-record-type ex3
  (parent cpoint)
  (protocol
   (lambda (p)
     (lambda (x y t)
       (let ((r ((p x y 'red) t)))
         (set! *ex3-instance* r)
         r))))
  (fields
   (mutable thickness))
  (sealed #t) (opaque #t))
```

```
(define ex3-i1 (make-ex3 1 2 17))
(ex3? ex3-i1)   => #t
(cpoint-rgb ex3-i1) => (rgb . red)
(ex3-thickness ex3-i1) => 17
(ex3-thickness-set! ex3-i1 18)
(ex3-thickness ex3-i1) => 18
*ex3-instance*  => ex3-i1
```

```
(record? ex3-i1) => #f
```

## 6.4. Inspection

The inspection layer is provided by the (`rnrs records inspection (6)`) library.

A set of procedures are provided for inspecting records and their record-type descriptors. These procedures are designed to allow the writing of portable printers and inspectors.

On the one hand, `record?` and `record-rtd` treat records of opaque record types as if they were not records. On the other hand, the inspection procedures that operate on record-type descriptors themselves are not affected by opacity. In other words, opacity controls whether a program can obtain an `rtd` from a record. If the program has access to the original `rtd` via `make-record-type-descriptor` or `record-type-descriptor`, it can still make use of the inspection procedures.

Any of the standard types mentioned in this report may or may not be implemented as an opaque record type. Consequently, `record?`, when applied to an object of one of these types, may return `#t`. In this case, inspection is possible for these objects.

`(record? obj)` procedure

Returns `#t` if `obj` is a record, and its record type is not opaque. Returns `#f` otherwise.

`(record-rtd record)` procedure

Returns the `rtd` representing the type of `record` if the type is not opaque. The `rtd` of the most precise type is returned; that is, the type `t` such that `record` is of type `t` but not of any type that extends `t`. If the type is opaque, an exception is raised with condition type `&assertion`.

`(record-type-name rtd)` procedure

Returns the name of the record-type descriptor `rtd`.

`(record-type-parent rtd)` procedure

Returns the parent of the record-type descriptor `rtd`, or `#f` if it has none.

`(record-type-uid rtd)` procedure

Returns the uid of the record-type descriptor `rtd`, or `#f` if it has none. (An implementation may assign a generated uid to a record type even if the type is generative, so the return of a uid does not necessarily imply that the type is nongenerative.)

`(record-type-generative? rtd)` procedure

Returns `#t` if `rtd` is generative, and `#f` if not.

`(record-type-sealed? rtd)` procedure

Returns a boolean value indicating whether the record-type descriptor is sealed.

`(record-type-opaque? rtd)` procedure

Returns a boolean value indicating whether the record-type descriptor is opaque.

`(record-type-field-names rtd)` procedure

Returns a vector of symbols naming the fields of the type represented by `rtd` (not including the fields of parent types) where the fields are ordered as described under `make-record-type-descriptor`. The returned vector may be immutable. If the returned vector is modified, the effect on `rtd` is unspecified.

`(record-field-mutable? rtd k)` procedure

Returns a boolean value indicating whether the field specified by `k` of the type represented by `rtd` is mutable, where `k` is as in `record-accessor`.

## 7. Exceptions and conditions

Scheme allows programs to deal with exceptional situations using two cooperating facilities: The exception system for raising and handling exceptional situations, and the condition system for describing these situations.

The exception system allows the program, when it detects an exceptional situation, to pass control to an exception handler, and to dynamically establish such exception handlers. Exception handlers are always invoked with an object describing the exceptional situation. Scheme's condition system provides a standardized taxonomy of such descriptive objects, as well as a facility for extending the taxonomy.

### 7.1. Exceptions

This section describes Scheme's exception-handling and exception-raising constructs provided by the `(rnrs exceptions (6))` library.

*Note:* This specification follows SRFI 34 [7].

Exception handlers are one-argument procedures that determine the action the program takes when an exceptional situation is signalled. The system implicitly maintains a current exception handler.

The program raises an exception by invoking the current exception handler, passing it an object encapsulating information about the exception. Any procedure accepting one argument may serve as an exception handler and any object may be used to represent an exception.

The system maintains the current exception handler as part of the dynamic environment of the program; see report section 4.10.

When a program begins its execution, the current exception handler is expected to handle all `&serious` conditions by interrupting execution, reporting that an exception has been raised, and displaying information about the condition object that was provided. The handler may then exit, or may provide a choice of other options. Moreover, the exception handler is expected to return when passed any other non-`&serious` condition. Interpretation of these expectations necessarily depends upon the nature of the system in which programs are executed, but the intent is that users perceive the raising of an exception as a controlled escape from the situation that raised the exception, not as a crash.

`(with-exception-handler handler thunk)` procedure

*Handler* must be a procedure and should accept one argument. *Thunk* must be a procedure that accepts zero arguments. The `with-exception-handler` procedure returns the results of invoking *thunk*. *Handler* is installed as the current exception handler for the dynamic extent (as determined by `dynamic-wind`) of the invocation of *thunk*.

*Implementation responsibilities:* The implementation must check the restrictions on *handler* to the extent performed by applying it as described when it is called as a result of a call to `raise` or `raise-continuable`.

`(guard (<variable> <cond clause1> <cond clause2> ...) <body>)`  
syntax

*Syntax:* Each `<cond clause>` is as in the specification of `cond`. (See report section 9.5.5.)

*Semantics:* Evaluating a `guard` form evaluates `<body>` with an exception handler that binds the raised object to `<variable>` and within the scope of that binding evaluates the clauses as if they were the clauses of a `cond` expression. That implicit `cond` expression is evaluated with the continuation and dynamic environment of the `guard` expression. If every `<cond clause>`'s `<test>` evaluates to `#f` and there is no else clause, then `raise` is re-invoked on the raised object within the dynamic environment of the original call to `raise` except that the current exception handler is that of the `guard` expression.

The `=>` and `else` identifiers are exported from the `(rnrs exceptions (6))` library with level 0, and are the same as in the `(rnrs base (6))` library.

`(raise obj)` procedure

Raises a non-continuable exception by invoking the current exception handler on *obj*. The handler is called with a continuation whose dynamic environment is that of the call to `raise`, except that the current exception handler is the one that was in place when the handler being called was

installed. When the handler returns, a non-continuable exception with condition type `&non-continuable` is raised in the same dynamic environment as the handler.

`(raise-continuable obj)` procedure

Raises a *continuable exception* by invoking the current exception handler on *obj*. The handler is called with a continuation that is equivalent to the continuation of the call to `raise-continuable`, with these two exceptions: (1) the current exception handler is the one that was in place when the handler being called was installed, and (2) if the handler being called returns, then it will again become the current exception handler. If the handler returns, the values it returns become the values returned by the call to `raise-continuable`.

```
(guard (con
  ((error? con)
    (if (message-condition? con)
        (display (condition-message con))
        (display "an error has occurred"))
      'error)
  ((violation? con)
    (if (message-condition? con)
        (display (condition-message con))
        (display "the program has a bug"))
      'violation))
  (raise
   (condition
    (&error)
    (&message (message "I am an error")))))
  prints: I am an error
  => error

(guard (con
  ((error? con)
    (if (message-condition? con)
        (display (condition-message con))
        (display "an error has occurred"))
      'error))
  (raise
   (condition
    (&violation)
    (&message (message "I am an error")))))
  => &violation exception

(guard (con
  ((error? con)
    (display "error opening file")
    #f))
  (call-with-input-file "foo.scm" read))
  prints: error opening file
  => #f

(with-exception-handler
 (lambda (con)
  (cond
   ((not (warning? con))
    (raise con))
```



```

(define cond1-x
  (condition-accessor
   (record-type-descriptor &cond1)
   real-cond1-x))

(define foo (make-cond1 'foo))

(condition? foo)           ⇒ #t
(cond1? foo)              ⇒ #t
(cond1-x foo)             ⇒ foo

(define-record-type (&cond2 make-cond2 real-cond2?)
  (parent &condition)
  (fields
   (immutable y real-cond2-y)))

(define cond2?
  (condition-predicate
   (record-type-descriptor &cond2)))
(define cond2-y
  (condition-accessor
   (record-type-descriptor &cond2)
   real-cond2-y))

(define bar (make-cond2 'bar))

(condition? (condition foo bar))
  ⇒ #t
(cond1? (condition foo bar))
  ⇒ #t
(cond2? (condition foo bar))
  ⇒ #t
(cond1? (condition foo)) ⇒ #t
(real-cond1? (condition foo))
  ⇒ unspecified
(real-cond1? (condition foo bar))
  ⇒ #f
(cond1-x (condition foo bar))
  ⇒ foo
(cond2-y (condition foo bar))
  ⇒ bar

(equal? (simple-conditions (condition foo bar))
        (list foo bar)) ⇒ #t

(equal? (simple-conditions
        (condition foo (condition bar)))
        (list foo bar)) ⇒ #t

```

```

(define-condition-type <condition-type>      syntax
  <supertype>
  <constructor> <predicate>
  <field-spec1> ...)

```

*Syntax:* <Condition-type>, <supertypes>, <constructor>, and <predicate> must all be identifiers. Each <field-spec> must be of the form

```
((field) <accessor>)
```

where both <field> and <accessor> must be identifiers.

*Semantics:* The `define-condition-type` form expands into a record-type definition for a record type `&condition-type` (see section 6.3). The record type will be non-opaque, non-sealed, and its fields will be immutable. It will have <supertype> as its parent type. The remaining identifiers will be bound as follows:

- <Constructor> is bound to a default constructor for the type (see section 6.2): It accepts one argument for each of the record type's complete set of fields (including parent types, with the fields of the parent coming before those of the extension in the arguments) and returns a condition object initialized to those arguments.
- <Predicate> is bound to a predicate that identifies conditions of type <condition-type> or any of its subtypes.
- Each <accessor> is bound to a procedure that extracts the corresponding field from a condition of type <condition-type>.

```

(define-condition-type &c &condition
  make-c c?
  (x c-x))

```

```

(define-condition-type &c1 &c
  make-c1 c1?
  (a c1-a))

```

```

(define-condition-type &c2 &c
  make-c2 c2?
  (b c2-b))

```

```

(define v1 (make-c1 "V1" "a1"))

```

```

(c? v1)           ⇒ #t
(c1? v1)          ⇒ #t
(c2? v1)          ⇒ #f
(c-x v1)          ⇒ "V1"
(c1-a v1)         ⇒ "a1"

```

```

(define v2 (make-c2 "V2" "b2"))

```

```

(c? v2)           ⇒ #t
(c1? v2)          ⇒ #f
(c2? v2)          ⇒ #t
(c-x v2)          ⇒ "V2"
(c2-b v2)         ⇒ "b2"

```

```

(define v3 (condition
  (make-c1 "V3/1" "a3")
  (make-c2 "V3/2" "b3")))

```

```

(c? v3)           ⇒ #t
(c1? v3)          ⇒ #t
(c2? v3)          ⇒ #t
(c-x v3)          ⇒ "V3/1"
(c1-a v3)         ⇒ "a3"
(c2-b v3)         ⇒ "b3"

```

```
(define v4 (condition v1 v2))

(c? v4)           ⇒ #t
(c1? v4)          ⇒ #t
(c2? v4)          ⇒ #t
(c-x v4)          ⇒ "V1"
(c1-a v4)         ⇒ "a1"
(c2-b v4)         ⇒ "b2"

(define v5 (condition v2 v3))

(c? v5)           ⇒ #t
(c1? v5)          ⇒ #t
(c2? v5)          ⇒ #t
(c-x v5)          ⇒ "V2"
(c1-a v5)         ⇒ "a3"
(c2-b v5)         ⇒ "b2"
```

### 7.3. Standard condition types

```
&message          condition type
(make-message-condition message) procedure
(message-condition? obj) procedure
(condition-message condition) procedure
```

This condition type could be defined by

```
(define-condition-type &message &condition
  make-message-condition message-condition?
  (message condition-message))
```

It carries a message further describing the nature of the condition to humans.

```
&warning          condition type
(make-warning)    procedure
(warning? obj)    procedure
```

This condition type could be defined by

```
(define-condition-type &warning &condition
  make-warning warning?)
```

This type describes conditions that do not, in principle, prohibit immediate continued execution of the program, but may interfere with the program's execution later.

```
&serious          condition type
(make-serious-condition) procedure
(serious-condition? obj) procedure
```

This condition type could be defined by

```
(define-condition-type &serious &condition
  make-serious-condition serious-condition?)
```

This type describes conditions serious enough that they cannot safely be ignored. This condition type is primarily intended as a supertype of other condition types.

```
&error            condition type
(make-error)      procedure
(error? obj)      procedure
```

This condition type could be defined by

```
(define-condition-type &error &serious
  make-error error?)
```

This type describes errors, typically caused by something that has gone wrong in the interaction of the program with the external world or the user.

```
&violation        condition type
(make-violation)  procedure
(violation? obj) procedure
```

This condition type could be defined by

```
(define-condition-type &violation &serious
  make-violation violation?)
```

This type describes violations of the language standard or a library standard, typically caused by a programming error.

```
&non-continuable condition type
(make-non-continuable-violation) procedure
(non-continuable-violation? obj) procedure
```

This condition type could be defined by

```
(define-condition-type &non-continuable &violation
  make-non-continuable-violation
  non-continuable-violation?)
```

This type indicates that an exception handler invoked via `raise` has returned.

```
&implementation-restriction condition type
(make-implementation-restriction-violation) procedure
(implementation-restriction-violation? obj) procedure
```

This condition type could be defined by

```
(define-condition-type &implementation-restriction
  &violation
  make-implementation-restriction-violation
  implementation-restriction-violation?)
```

This type describes a violation of an implementation restriction allowed by the specification, such as the absence of representations for NaNs and infinities. (See section 11.2.)

```
&lexical          condition type
(make-lexical-violation) procedure
(lexical-violation? obj) procedure
```

This condition type could be defined by

```
(define-condition-type &lexical &violation
  make-lexical-violation lexical-violation?)
```

This type describes syntax violations at the level of the read syntax.

```
&syntax                                condition type
(make-syntax-violation form subform)  procedure
(syntax-violation? obj)                procedure
(syntax-violation-form condition)     procedure
(syntax-violation-subform condition)  procedure
```

This condition type could be defined by

```
(define-condition-type &syntax &violation
  make-syntax-violation syntax-violation?
  (form syntax-violation-form)
  (subform syntax-violation-subform))
```

This type describes syntax violations. The *form* field contains the erroneous syntax object or a datum representing the code of the erroneous form. The *subform* field may contain an optional syntax object or datum within the erroneous form that more precisely locates the violation. It can be *#f* to indicate the absence of more precise information.

```
&undefined                              condition type
(make-undefined-violation)                procedure
(undefined-violation? obj)              procedure
```

This condition type could be defined by

```
(define-condition-type &undefined &violation
  make-undefined-violation undefined-violation?)
```

This type describes unbound identifiers in the program.

```
&assertion                              condition type
(make-assertion-violation)                procedure
(assertion-violation? obj)              procedure
```

This condition type could be defined by

```
(define-condition-type &assertion &violation
  make-assertion-violation assertion-violation?)
```

This type describes an invalid call to a procedure, either passing an invalid number of arguments, or passing an argument of the wrong type.

```
&irritants                              condition type
(make-irritants-condition irritants)    procedure
(irritants-condition? obj)              procedure
(condition-irritants condition)         procedure
```

This condition type could be defined by

```
(define-condition-type &irritants &condition
  make-irritants-condition irritants-condition?
  (irritants condition-irritants))
```

The *irritants* field should contain a list of objects. This condition provides additional information about a condition, typically the argument list of a procedure that detected an exception. Conditions of this type are created by the *error* and *assertion-violation* procedures of report section 9.15.

```
&who                                      condition type
(make-who-condition who)                procedure
(who-condition? obj)                    procedure
(condition-who condition)              procedure
```

This condition type could be defined by

```
(define-condition-type &who &condition
  make-who-condition who-condition?
  (who condition-who))
```

The *who* field should contain a symbol or string identifying the entity reporting the exception. Conditions of this type are created by the *error* and *assertion-violation* procedures (report section 9.15), and the *syntax-violation* procedure (section 12.9).

## 8. I/O

This chapter describes Scheme's libraries for performing input and output:

- The (*rnrs io ports (6)*) library (section 8.2) is an I/O layer for conventional, imperative buffered input and output with mixed text and binary data.
- The (*rnrs io simple (6)*) library (section 8.3) is a convenience library atop the (*rnrs io ports (6)*) library for textual I/O, compatible with the traditional Scheme I/O procedures [6].

Section 8.1 defines a condition-type hierarchy that is exported by both the (*rnrs io ports (6)*) and (*rnrs io simple (6)*) libraries.

### 8.1. Condition types

The procedures described in this chapter, when they detect an exceptional situation that arises from an “I/O errors”, raise an exception with condition type *&i/o*.

The condition types and corresponding predicates and accessors are exported by both the (*rnrs io ports (6)*) and (*rnrs io simple (6)*) libraries. They are also exported by the (*rnrs files (6)*) library described in chapter 9.

```
&i/o                                      condition type
(make-i/o-error)                          procedure
(i/o-error? obj)                          procedure
```

This condition type could be defined by

```
(define-condition-type &i/o &error
  make-i/o-error i/o-error?)
```

This is a supertype for a set of more specific I/O errors.

```
&i/o-read                condition type
(make-i/o-read-error)    procedure
(i/o-read-error? obj)    procedure
```

This condition type could be defined by

```
(define-condition-type &i/o-read &i/o
  make-i/o-read-error i/o-read-error?)
```

This condition type describes read errors that occurred during an I/O operation.

```
&i/o-write                condition type
(make-i/o-write-error)    procedure
(i/o-write-error? obj)    procedure
```

This condition type could be defined by

```
(define-condition-type &i/o-write &i/o
  make-i/o-write-error i/o-write-error?)
```

This condition type describes write errors that occurred during an I/O operation.

```
&i/o-invalid-position    condition type
(make-i/o-invalid-position-error) procedure
(i/o-invalid-position-error? obj) procedure
```

This condition type could be defined by

```
(define-condition-type &i/o-invalid-position &i/o
  make-i/o-invalid-position-error
  i/o-invalid-position-error?
  (position i/o-error-position))
```

This condition type describes attempts to set the file position to an invalid position. The value of the position field is the file position that the program intended to set. This condition describes a range error, but not an assertion violation.

```
&i/o-filename            condition type
(make-i/o-filename-error filename) procedure
(i/o-filename-error? obj) procedure
(i/o-error-filename condition) procedure
```

This condition type could be defined by

```
(define-condition-type &i/o-filename &i/o
  make-i/o-filename-error i/o-filename-error?
  (filename i/o-error-filename))
```

This condition type describes an I/O error that occurred during an operation on a named file. Condition objects belonging to this type must specify a file name in the `filename` field.

```
&i/o-file-protection    condition type
(make-i/o-file-protection-error filename)
(i/o-file-protection-error? obj) procedure
```

This condition type could be defined by

```
(define-condition-type &i/o-file-protection
  &i/o-filename
  make-i/o-file-protection-error
  i/o-file-protection-error?)
```

A condition of this type specifies that an operation tried to operate on a named file with insufficient access rights.

```
&i/o-file-is-read-only  condition type
(make-i/o-file-is-read-only-error filename)
(i/o-file-is-read-only-error? obj) procedure
```

This condition type could be defined by

```
(define-condition-type &i/o-file-is-read-only
  &i/o-file-protection
  make-i/o-file-is-read-only-error
  i/o-file-is-read-only-error?)
```

A condition of this type specifies that an operation tried to operate on a named read-only file under the assumption that it is writeable.

```
&i/o-file-already-exists condition type
(make-i/o-file-already-exists-error filename)
(i/o-file-already-exists-error? obj) procedure
```

This condition type could be defined by

```
(define-condition-type &i/o-file-already-exists
  &i/o-filename
  make-i/o-file-already-exists-error
  i/o-file-already-exists-error?)
```

A condition of this type specifies that an operation tried to operate on an existing named file under the assumption that it did not exist.

```
&i/o-file-does-not-exist condition type
(make-i/o-file-does-not-exist-error filename)
(i/o-file-does-not-exist-error? obj) procedure
```

This condition type could be defined by

```
(define-condition-type &i/o-file-does-not-exist
  &i/o-filename
  make-i/o-file-does-not-exist-error
  i/o-file-does-not-exist-error?)
```

A condition of this type specifies that an operation tried to operate on a non-existent named file under the assumption that it existed.

|   |                |
|---|----------------|
| <code>&amp;i/o-port</code>              | condition type |
| <code>(make-i/o-port-error port)</code> | procedure      |
| <code>(i/o-port-error? obj)</code>      | procedure      |
| <code>(i/o-error-port condition)</code> | procedure      |

This condition type could be defined by

```
(define-condition-type &i/o-port &i/o
  make-i/o-port-error i/o-port-error?
  (port i/o-error-port))
```

This condition type specifies the port with which an I/O error is associated. Except for condition objects provided for encoding and decoding errors, conditions raised by procedures may include an `&i/o-port-error` condition, but are not required to do so.

## 8.2. Port I/O

The `(rnrs io ports (6))` library defines an I/O layer for conventional, imperative buffered input and output. A *port* represents a buffered access object for a data sink or source or both simultaneously. The library allows ports to be created from arbitrary data sources and sinks.

The `(rnrs io ports (6))` library distinguishes between *input ports* and *output ports*. An input port is a source for data, whereas an output port is a sink for data. A port may be both an input port and an output port; such a port typically provides simultaneous read and write access to a file or other data.

The `(rnrs io ports (6))` library also distinguishes between *binary ports*, which are sources or sinks for uninterpreted bytes, and *textual ports*, which are sources or sinks for characters and strings.

This section uses *input-port*, *output-port*, *binary-port*, *textual-port*, *binary-input-port*, *textual-input-port*, *binary-output-port*, *textual-output-port*, and *port* as parameter names for arguments that must be input ports (or combined input/output ports), output ports (or combined input/output ports), binary ports, textual ports, binary input ports, textual input ports, binary output ports, textual output ports, or any kind of port, respectively.

### 8.2.1. File names

Some of the procedures described in this chapter accept a file name as an argument. Valid values for such a file name include strings that name a file using the native notation of filesystem paths on an implementation's underlying operating system, and may include implementation-dependent values as well.

A *filename* parameter name means that the corresponding argument must be a file name.

### 8.2.2. File options

When opening a file, the various procedures in this library accept a `file-options` object that encapsulates flags to specify how the file is to be opened. A `file-options` object is an enum-set (see chapter 14) over the symbols constituting valid file options. A *file-options* parameter name means that the corresponding argument must be a `file-options` object.

`(file-options <file-options name> ...)` syntax

Each `<file-options name>` must be an `<identifier>`. The `file-options` syntax returns a `file-options` object that encapsulates the specified options.

When supplied to an operation that opens a file for output, the `file-options` object returned by `(file-options)` specifies that the file is created if it does not exist and an exception with condition type `&i/o-file-already-exists` is raised if it does exist. The following standard options can be included to modify the default behavior.

- **no-create** If the file does not already exist, it is not created; instead, an exception with condition type `&i/o-file-does-not-exist` is raised. If the file already exists, the exception with condition type `&i/o-file-already-exists` is not raised and the file is truncated to zero length.
- **no-fail** If the file already exists, the exception with condition type `&i/o-file-already-exists` is not raised, even if **no-create** is not included, and the file is truncated to zero length.
- **no-truncate** If the file already exists and the exception with condition type `&i/o-file-already-exists` has been inhibited by inclusion of **no-create** or **no-fail**, the file is not truncated, but the port's current position is still set to the beginning of the file.

These options have no effect when a file is opened only for input. `<Identifiers>`s other than those listed above may be used as `<file-options name>`s; they have implementation-specific meaning, if any.

### 8.2.3. Buffer modes

Each port has an associated buffer mode. For an output port, the buffer mode defines when an output operation flushes the buffer associated with the output port. For an input port, the buffer mode defines how much data will be read to satisfy read operations. The possible buffer modes are the symbols **none** for no buffering, **line** for flushing upon line endings or reading until line endings, and **block** for arbitrary buffering. This section uses the parameter name *buffer-mode* for arguments that must be buffer-mode symbols.

If two ports are connected to the same mutable source, both ports are unbuffered, and reading a byte or character from that shared source via one of the two ports would change the bytes or characters seen via the other port, a lookahead operation on one port will render the peeked byte or character inaccessible via the other port, while a subsequent read operation on the peeked port will see the peeked byte or character even though the port is otherwise unbuffered.

In other words, the semantics of buffering is defined in terms of side effects on shared mutable sources, and a lookahead operation has the same side effect on the shared source as a read operation.

**(buffer-mode <name>)** syntax  
 <Name> must be one of the <identifier>s **none**, **line**, or **block**. The result is the corresponding symbol, denoting the associated buffer mode.

It is a syntax violation if <name> is not one of the valid identifiers.

**(buffer-mode? obj)** procedure

Returns **#t** if the argument is a valid buffer-mode symbol, and returns **#f** otherwise.

### 8.2.4. Transcoders

Several different Unicode encoding schemes describe standard ways to encode characters and strings as byte sequences and to decode those sequences [10]. Within this document, a *codec* is an immutable Scheme object that represents a Unicode or similar encoding scheme.

An *end-of-line style* is a symbol that, if it is not **none**, describes how a textual port transcodes representations of line endings.

A *transcoder* is an immutable Scheme object that combines a codec with an end-of-line style and a method for handling decoding errors. Each transcoder represents some specific

bidirectional (but not necessarily lossless), possibly stateful translation between byte sequences and Unicode characters and strings. Every transcoder can operate in the input direction (bytes to characters) or in the output direction (characters to bytes), but the composition of those directions need not be identity (and often is not). The composition of two transcoders is not defined. A *transcoder* parameter name means that the corresponding argument must be a transcoder.

A *binary port* is a port that supports binary I/O, does not have an associated transcoder and does not support textual I/O. A *textual port* is a port that supports textual I/O, and does not support binary I/O. A textual port may or may not have an associated transcoder.

**(latin-1-codec)** procedure  
**(utf-8-codec)** procedure  
**(utf-16-codec)** procedure

These are predefined codecs for the ISO 8859-1, UTF-8, and UTF-16 encoding schemes [10].

A call to any of these procedures returns a value that is equal in the sense of **eqv?** to the result of any other call to the same procedure.

**(eol-style name)** syntax

If *name* is one of the <identifier>s **lf**, **cr**, **crlf**, **nel**, **crnel**, **ls**, or **none**, the form evaluates to the corresponding symbol. If *name* is not one of these identifiers, the effect and result are implementation-dependent; in particular, the result may be an eol-style symbol acceptable as an *eol-mode* argument to **make-transcoder**. Otherwise, an exception is raised.

All eol-style symbols except **none** describe a specific line-ending encoding:

**lf**      <linefeed>  
**cr**      <carriage return>  
**crlf**    <carriage return> <linefeed>  
**nel**     <next line>  
**crnel**   <carriage return> <next line>  
**ls**      <line separator>

For a textual port with a transcoder, and whose transcoder has an eol-style symbol **none**, no conversion occurs. For a textual input port, any eol-style symbol other than **none** means that all of the above line-ending encodings are recognized and are translated into a single linefeed. For a textual output port, **none** and **lf** are equivalent. Linefeed characters are encoded according to the specified eol-style symbol, and all other characters that participate in possible line endings are encoded as is.

**(native-eol-style)** procedure

Returns the default end-of-line style of the underlying platform, e.g., **lf** on Unix and **crlf** on Windows.

```

&i/o-decoding                condition type
(make-i/o-decoding-error port) procedure
(i/o-decoding-error? obj)    procedure
(i/o-decoding-error-transcoder condition)
                                procedure

```

This condition type could be defined by

```

(define-condition-type &i/o-decoding &i/o-port
  make-i/o-decoding-error i/o-decoding-error?
  (transcoder i/o-decoding-error-transcoder))

```

An exception with this type is raised when one of the operations for textual input from a port encounters a sequence of bytes that cannot be translated into a character or string by the input direction of the port's transcoder. The `transcoder` field contains the port's transcoder.

Exceptions of this type raised by the operations described in this section are continuable. When such an exception is raised, the port's position is at the beginning of the invalid encoding. If the exception handler returns, it should return a character or string representing the decoded text starting at the port's current position, and the exception handler must update the port's position to point past the error.

*Implementation responsibilities:* The implementation must check that the exception handler returns a character or a string only if it actually returns.

```

&i/o-encoding                condition type
(make-i/o-encoding-error port char transcoder)
                                procedure
(i/o-encoding-error? obj)    procedure
(i/o-encoding-error-char condition) procedure
(i/o-encoding-error-transcoder condition)
                                procedure

```

This condition type could be defined by

```

(define-condition-type &i/o-encoding &i/o-port
  make-i/o-encoding-error i/o-encoding-error?
  (char i/o-encoding-error-char)
  (transcoder i/o-encoding-error-transcoder))

```

An exception with this type is raised when one of the operations for textual output to a port encounters a character that cannot be translated into bytes by the output direction of the port's transcoder. The `char` field of the condition object contains the character that could not be encoded, and the `transcoder` field contains the transcoder associated with the port.

Exceptions of this type raised by the operations described in this section are continuable. The handler, if it returns, should output to the port an appropriate encoding for the character that caused the error. The operation that raised the exception continues after that character.

*Implementation responsibilities:* The implementation is not required to check whether the handler has output an encoding.

```

(error-handling-mode name)    syntax

```

If *name* is one of the <identifier>s `ignore`, `raise`, or `replace`, the result is the corresponding symbol. If *name* is not one of these identifiers, effect and result are implementation-dependent: The result may be an error-handling-mode symbol acceptable as a *handling-mode* argument to `make-transcoder`. If it is not acceptable as a *handling-mode* argument to `make-transcoder`, an exception is raised.

The error-handling mode of a transcoder specifies the behavior of textual I/O operations in the presence of encoding or decoding errors.

If a textual input operation encounters an invalid or incomplete character encoding, and the error-handling mode is `ignore`, an appropriate number of bytes of the invalid encoding are ignored and decoding continues with the following bytes. If the error-handling mode is `replace`, the replacement character U+FFFD is injected into the data stream, an appropriate number of bytes are ignored, and decoding continues with the following bytes. If the error-handling mode is `raise`, a continuable exception with condition type `&i/o-decoding` is raised; see the description of `&i/o-decoding` for details on how to handle such an exception.

If a textual output operation encounters a character it cannot encode, and the error-handling mode is `ignore`, the character is ignored and encoding continues with the next character. If the error-handling mode is `replace`, a codec-specific replacement character is emitted by the transcoder, and encoding continues with the next character. The replacement character is U+FFFD for transcoders whose codec is one of the Unicode encodings, but is the ? character for the Latin-1 encoding. If the error-handling mode is `raise`, an exception with condition type `&i/o-encoding` is raised; see the description of `&i/o-decoding` for details on how to handle such an exception.

```

(make-transcoder codec)        procedure
(make-transcoder codec eol-style) procedure
(make-transcoder codec eol-style handling-mode)
                                procedure

```

*Codec* must be a codec; *eol-style*, if present, an eol-style symbol; and *handling-mode*, if present, an error-handling-mode symbol. *Eol-style* may be omitted, in which case it defaults to the native end-of-line style of the underlying platform. *Handling-mode* may be omitted, in which case it defaults to `raise`. The result is a transcoder with the behavior specified by its arguments.

(native-transcoder) procedure

Returns an implementation-dependent transcoder that represents a possibly locale-dependent “native” transcoding.

(transcoder-codec *transcoder*) procedure  
 (transcoder-eol-style *transcoder*) procedure  
 (transcoder-error-handling-mode *transcoder*) procedure

These are accessors for transcoder objects; when applied to a transcoder returned by `make-transcoder`, they return the *codec*, *eol-style*, and *handling-mode* arguments, respectively.

(bytevector->string *bytevector transcoder*) procedure

Returns the string that results from transcoding the *bytevector* according to the input direction of the transcoder.

(string->bytevector *string transcoder*) procedure

Returns the bytevector that results from transcoding the *string* according to the output direction of the transcoder.

### 8.2.5. End of file object

The end of file object is returned by various I/O procedures when they reach end of file.

(eof-object) procedure

Returns the end of file object.

```
(eqv? (eof-object) (eof-object))
      => #t
(eq? (eof-object) (eof-object))
     => #t
```

*Note:* The end of file object is not a datum value, and thus has no external representation.

(eof-object? *obj*) procedure

Returns `#t` if *obj* is the end of file object, `#f` otherwise.

### 8.2.6. Input and output ports

The operations described in this section are common to input and output ports, both binary and textual. A port may also have an associated *position* that specifies a particular place within its data sink or source, and may also provide operations for inspecting and setting that place.

(port? *obj*) procedure

Returns `#t` if the argument is a port, and returns `#f` otherwise.

(port-transcoder *port*) procedure

Returns the transcoder associated with *port* if *port* is textual and has an associated transcoder, and returns `#f` if *port* is binary or does not have an associated transcoder.

(textual-port? *port*) procedure

(binary-port? *port*) procedure

The `textual-port` procedure returns `#t` if *port* is textual, and returns `#f` otherwise. The `binary-port` procedure returns `#t` if *port* is binary, and returns `#f` otherwise.

(transcoded-port *binary-port transcoder*) procedure

The `transcoded-port` procedure returns a new textual port with the specified *transcoder*. Otherwise the new textual port’s state is largely the same as that of the *binary-port*. If the *binary-port* is an input port, the new textual port will be an input port and will transcode the bytes that have not yet been read from the *binary-port*. If the *binary-port* is an output port, the new textual port will be an output port and will transcode output characters into bytes that are written to the byte sink represented by the *binary-port*.

As a side effect, however, `transcoded-port` closes *binary-port* in a special way that allows the new textual port to continue to use the byte source or sink represented by the *binary-port*, even though the *binary-port* itself is closed and cannot be used by the input and output operations described in this chapter.

(port-has-port-position? *port*) procedure

(port-position *port*) procedure

The `port-has-port-position?` procedure returns `#t` if the port supports the `port-position` operation, and `#f` otherwise.

For a binary port, the `port-position` procedure returns the index of the position at which the next byte would be read from or written to the port as an exact non-negative integer object. For a textual port, `port-position` returns an arbitrary value that is acceptable as input for `set-port-position!` (see below).

If the port does not support the operation, `port-position` raises an exception with condition type `&assertion`.

*Note:* For a textual port, the port position may or may not be an integer object. If it is an integer object, the integer object does not necessarily correspond to a byte or character position.

(port-has-set-port-position! *port*) procedure  
 (set-port-position! *port pos*) procedure

If *port* is a binary port, *pos* should be a non-negative exact integer object. If *port* is a textual port, *pos* should be the return value of a call to `port-position` on *port*.

The `port-has-set-port-position?` procedure returns `#t` if the port supports the `set-port-position!` operation, and `#f` otherwise.

The `set-port-position!` procedure raises an exception with condition type `&assertion` if the port does not support the operation. Otherwise, it sets the current position of the port to *pos*. If *port* is an output port, `set-port-position!` first flushes *port*. (See `flush-output-port`, section 8.2.10.)

If *port* is a binary output port and the current position is set beyond the current end of the data in the underlying data sink, the object is not extended until new data is written at that position. The contents of any intervening positions are unspecified. Binary ports created by `open-file-output-port` and `open-file-input/output-port` can always be extended in this manner within the limits of the underlying operating system. In other cases, attempts to set the port beyond the current end of data in the underlying object may result in an exception with condition type `&i/o-invalid-position`.

(close-port *port*) procedure

Closes the port, rendering the port incapable of delivering or accepting data. If *port* is an output port, it is flushed before being closed. This has no effect if the port has already been closed. A closed port is still a port. The `close-port` procedure returns unspecified values.

(call-with-port *port proc*) procedure

*Proc* must accept one argument. The `call-with-port` procedure calls *proc* with *port* as an argument. If *proc* returns, the *port* is closed automatically and the values returned by *proc* are returned. If *proc* does not return, the port is not closed automatically, except perhaps when it is possible to prove that the port will never again be used for an input or output operation.

### 8.2.7. Input ports

An input port allows the reading of an infinite sequence of bytes or characters punctuated by end of file objects. An input port connected to a finite data source ends in an infinite sequence of end of file objects.

It is unspecified whether a character encoding consisting of several bytes may have an end of file between the bytes. If,

for example, `get-char` raises an `&i/o-decoding` exception because the character encoding at the port's position is incomplete up to the next end of file, a subsequent call to `get-char` may successfully decode a character if bytes completing the encoding are available after the end of file.

(input-port? *obj*) procedure

Returns `#t` if the argument is an input port (or a combined input and output port), and returns `#f` otherwise.

(port-eof? *input-port*) procedure

Returns `#t` if the `lookahead-u8` procedure (if *input-port* is a binary port) or the `lookahead-char` procedure (if *input-port* is a textual port) would return the end-of-file object, and `#f` otherwise. The operation may block indefinitely if no data is available but the port cannot be determined to be at end of file.

(open-file-input-port *filename*) procedure  
 (open-file-input-port *filename file-options*)

procedure  
 (open-file-input-port *filename file-options buffer-mode*) procedure

procedure  
 (open-file-input-port *filename file-options buffer-mode maybe-transcoder*)

*Maybe-transcoder* must be either a transcoder or `#f`.

Returns an input port for the named file. The *file-options* and *maybe-transcoder* arguments are optional.

The *file-options* argument, which may determine various aspects of the returned port (see section 8.2.2), defaults to the value of `(file-options)`.

The *buffer-mode* argument, if supplied, must be one of the symbols that name a buffer mode. The *buffer-mode* argument defaults to `block`.

If *maybe-transcoder* is a transcoder, it becomes the transcoder associated with the returned port.

If *maybe-transcoder* is `#f` or absent, the port will be a binary port and will support the `port-position` and `set-port-position!` operations. Otherwise the port will be a textual port, and whether it supports the `port-position` and `set-port-position!` operations will be implementation-dependent (and possibly transcoder-dependent).

(open-bytevector-input-port *bytevector*) procedure  
 (open-bytevector-input-port *bytevector maybe-transcoder*)

*Maybe-transcoder* must be either a transcoder or `#f`.

The `open-bytevector-input-port` procedure returns an input port whose bytes are drawn from the *bytevector*. If

*transcoder* is specified, it becomes the transcoder associated with the returned port.

If *maybe-transcoder* is `#f` or absent, the port will be a binary port and will support the `port-position` and `set-port-position!` operations. Otherwise the port will be a textual port, and whether it supports the `port-position` and `set-port-position!` operations will be implementation-dependent (and possibly transcoder-dependent).

If *bytevector* is modified after `open-bytevector-input-port` has been called, the effect on the returned port is unspecified.

`(open-string-input-port string)` procedure

Returns a textual input port whose characters are drawn from *string*. The port may or may not have an associated transcoder; if it does, the transcoder is implementation-dependent. Whether the port supports the `port-position` and `set-port-position!` operations is implementation-dependent.

If *string* is modified after `open-string-input-port` has been called, the effect on the returned port is unspecified.

`(standard-input-port)` procedure

Returns a fresh binary input port connected to standard input. Whether the port supports the `port-position` and `set-port-position!` operations is implementation-dependent.

`(current-input-port)` procedure

This returns a default textual port for input. Normally, this default port is associated with standard input, but can be dynamically re-assigned using the `with-input-from-file` procedure from the `(rnrs io simple (6))` library (see section 8.3). The port may or may not have an associated transcoder; if it does, the transcoder is implementation-dependent.

`(make-custom-binary-input-port id read! procedure get-position set-position! close)` procedure

Returns a newly created binary input port whose byte source is an arbitrary algorithm represented by the *read!* procedure. *Id* must be a string naming the new port, provided for informational purposes only. *Read!* must be a procedure and should behave as specified below; it will be called by operations that perform binary input.

Each of the remaining arguments may be `#f`; if any of those arguments is not `#f`, it must be a procedure and should behave as specified below.

- (*read! bytevector start count*)

*Start* will be a non-negative exact integer object, *count* will be a positive exact integer object, and *bytevector* will be a bytevector whose length is at least *start* + *count*. The *read!* procedure should obtain up to *count* bytes from the byte source, and should write those bytes into *bytevector* starting at index *start*. The *read!* procedure should return an exact integer object. This integer object should represent the number of bytes that it has read. To indicate an end of file condition, the *read!* procedure should write no bytes and return 0.

- (*get-position*)

The *get-position* procedure (if supplied) should return an exact integer object. The return value should represent the current position of the input port. If not supplied, the custom port will not support the `port-position` operation.

- (*set-position! pos*)

*Pos* will be a non-negative exact integer object. The *set-position!* procedure (if supplied) should set the position of the input port to *pos*. If not supplied, the custom port will not support the `set-port-position!` operation.

- (*close*)

The *close* procedure (if supplied) should perform any actions that are necessary when the input port is closed.

*Implementation responsibilities:* The implementation is required to check the return values of *read!* and *get-position* only when it actually calls them as part of an I/O operation requested by the program. The implementation is not required to check that these procedures otherwise behave as described. If they do not, however, the behavior of the resulting port is unspecified.

`(make-custom-textual-input-port id read! procedure get-position set-position! close)` procedure

Returns a newly created textual input port whose character source is an arbitrary algorithm represented by the *read!* procedure. *Id* must be a string naming the new port, provided for informational purposes only. *Read!* must be a procedure and should behave as specified below; it will be called by operations that perform textual input.

Each of the remaining arguments may be `#f`; if any of those arguments is not `#f`, it must be a procedure and should behave as specified below.

- (*read!* *string start count*)

*Start* will be a non-negative exact integer object, *count* will be a positive exact integer object, and *string* will be a string whose length is at least *start* + *count*. The *read!* procedure should obtain up to *count* characters from the character source, and should write those characters into *string* starting at index *start*. The *read!* procedure must return an exact integer object. This integer object should represent the number of characters that it has written. To indicate an end of file condition, the *read!* procedure should write no bytes and return 0.

- (*get-position*)

The *get-position* procedure (if supplied) should return a single value. The return value should represent the current position of the input port. If not supplied, the custom port will not support the `port-position` operation.

- (*set-position!* *pos*)

The *set-position!* procedure (if supplied) should set the position of the input port to *pos* if *pos* is the return value of a call to *get-position*. If not supplied, the custom port will not support the `set-port-position!` operation.

- (*close*)

The *close* procedure (if supplied) should perform any actions that are necessary when the input port is closed.

The port may or may not have an associated transcoder; if it does, the transcoder is implementation-dependent.

*Implementation responsibilities:* The implementation is required to check the return values of *read!* and *get-position* only when it actually calls them as part of an I/O operation requested by the program. The implementation is not required to check that these procedures otherwise behave as described. If they do not, however, the behavior of the resulting port is unspecified.

### 8.2.8. Binary input

(`get-u8` *binary-input-port*) procedure

Reads from *binary-input-port*, blocking as necessary, until data are available from *binary-input-port* or until an end of file is reached. If a byte becomes available, `get-u8` returns the byte as an octet and updates *binary-input-port* to point just past that byte. If no input byte is seen before an end of file is reached, the end-of-file object is returned.

(`lookahead-u8` *binary-input-port*) procedure

The `lookahead-u8` procedure is like `get-u8`, but it does not update *binary-input-port* to point past the byte.

(`get-bytevector-n` *binary-input-port count*) procedure

*Count* must be an exact, non-negative integer object representing the number of bytes to be read.

Reads from *binary-input-port*, blocking as necessary, until *count* bytes are available from *binary-input-port* or until an end of file is reached. If *count* bytes are available before an end of file, `get-bytevector-n` returns a bytevector of size *count*. If fewer bytes are available before an end of file, `get-bytevector-n` returns a bytevector containing those bytes. In either case, the input port is updated to point just past the bytes read. If an end of file is reached before any bytes are available, `get-bytevector-n` returns the end-of-file object.

(`get-bytevector-n!` *binary-input-port bytevector start count*) procedure

*Count* must be an exact, non-negative integer object, representing the number of bytes to be read. *bytevector* must be a bytevector with at least *start* + *count* elements.

The `get-bytevector-n!` procedure reads from *binary-input-port*, blocking as necessary, until *count* bytes are available from *binary-input-port* or until an end of file is reached. If *count* bytes are available before an end of file, they are written into *bytevector* starting at index *start*, and the result is *count*. If fewer bytes are available before the next end of file, the available bytes are written into *bytevector* starting at index *start*, and the result is a number object representing the number of bytes actually read. In either case, the input port is updated to point just past the data read. If an end of file is reached before any bytes are available, `get-bytevector-n!` returns the end-of-file object.

(`get-bytevector-some` *binary-input-port*) procedure

Reads from *binary-input-port*, blocking as necessary, until data are available from *binary-input-port* or until an end of file is reached. If data become available, `get-bytevector-some` returns a freshly allocated bytevector containing the initial one or more bytes of available data, and it updates *binary-input-port* to point just past that data. If no input bytes are seen before an end of file is reached, the end-of-file object is returned.

(`get-bytevector-all` *binary-input-port*) procedure

Attempts to read all data until the next end of file, blocking as necessary. If one or more bytes are

read, `get-bytevector-all` returns a bytevector containing all bytes up to the next end of file. Otherwise, `get-bytevector-all` returns the end-of-file object. The operation may block indefinitely waiting to see if more data will become available, even if some bytes are already available.

### 8.2.9. Textual input

`(get-char textual-input-port)` procedure

Reads from *textual-input-port*, blocking as necessary, until the complete encoding for a character is available from *textual-input-port*, or until the available input data cannot be the prefix of any valid encoding, or until an end of file is reached.

If a complete character is available before the next end of file, `get-char` returns that character and updates the input port to point past the data that encoded that character. If an end of file is reached before any data are read, `get-char` returns the end-of-file object.

`(lookahead-char textual-input-port)` procedure

The `lookahead-char` procedure is like `get-char`, but it does not update *textual-input-port* to point past the data that encode the character.

*Note:* With some of the standard transcoders described in this document, up to four bytes of lookahead are required. Nonstandard transcoders may require even more lookahead.

`(get-string-n textual-input-port count)` procedure

*Count* must be an exact, non-negative integer object, representing the number of characters to be read.

Reads from *textual-input-port*, blocking as necessary, until the encodings of *count* characters (including invalid encodings, if they don't raise an exception) are available, or until an end of file is reached.

If *count* characters are available before end of file, `get-string-n` returns a string consisting of those *count* characters. If fewer characters are available before an end of file, but one or more characters can be read, `get-string-n` returns a string containing those characters. In either case, the input port is updated to point just past the data read. If no data can be read before an end of file, the end-of-file object is returned.

`(get-string-n! textual-input-port string start count)` procedure

*Start* and *count* must be exact, non-negative integer object, with *count* representing the number of characters to be

read. *String* must be a string with at least *start* + *count* characters.

Reads from *textual-input-port* in the same manner as `get-string-n`. If *count* characters are available before an end of file, they are written into *string* starting at index *start*, and *count* is returned. If fewer characters are available before an end of file, but one or more can be read, those characters are written into string starting at index *start* and the number of characters actually read is returned as an exact integer object. If no characters can be read before an end of file, the end-of-file object is returned.

`(get-string-all textual-input-port)` procedure

Reads from *textual-input-port* until an end of file, decoding characters in the same manner as `get-string-n` and `get-string-n!`.

If data is available before the end of file, a string containing all the text decoded from that data are returned. If no data precedes the end of file, the end-of-file object file object is returned.

`(get-line textual-input-port)` procedure

Reads from *textual-input-port* up to and including the linefeed character or end of file, decoding characters in the same manner as `get-string-n` and `get-string-n!`.

If a linefeed character is read, a string containing all of the text up to (but not including) the linefeed character is returned, and the port is updated to point just past the linefeed character. If an end of file is encountered before any linefeed character is read, but some data have been read and decoded as characters, a string containing those characters is returned. If an end of file is encountered before any data are read, the end-of-file object is returned.

*Note:* The end-of-line style, if not `none`, will cause all line endings to be read as linefeed characters. See section 8.2.4.

`(get-datum textual-input-port)` procedure

Reads an external representation from *textual-input-port* and returns the datum it represents. The `get-datum` procedure returns the next datum that can be parsed from the given *textual-input-port*, updating *textual-input-port* to point exactly past the end of the external representation of the object.

Any ⟨interlexeme space⟩ (see report section 3.2) in the input is first skipped. If an end of file occurs after the ⟨interlexeme space⟩, the end of file object (see section 8.2.5) is returned.

If a character inconsistent with an external representation is encountered in the input, an exception with condition types `&lexical` and `&i/o-read` is raised. Also, if the end

of file is encountered after the beginning of an external representation, but the external representation is incomplete and therefore cannot be parsed, an exception with condition types `&lexical` and `&i/o-read` is raised.

### 8.2.10. Output ports

An output port is a sink to which bytes or characters are written. The written data may control external devices or may produce files and other objects that may subsequently be opened for input.

`(output-port? obj)` procedure

Returns `#t` if the argument is an output port (or a combined input and output port), `#f` otherwise.

`(flush-output-port output-port)` procedure

Flushes any output from the buffer of *output-port* to the underlying file, device, or object. The `flush-output-port` procedure returns unspecified values.

`(output-port-buffer-mode output-port)` procedure

Returns the symbol that represents the buffer mode of *output-port*.

`(open-file-output-port filename)` procedure  
`(open-file-output-port filename file-options)`

procedure  
`(open-file-output-port filename file-options buffer-mode)` procedure

procedure  
`(open-file-output-port filename file-options buffer-mode maybe-transcoder)`

*Maybe-transcoder* must be either a transcoder or `#f`.

The `open-file-output-port` procedure returns an output port for the named file.

The *file-options* argument, which may determine various aspects of the returned port (see section 8.2.2), defaults to the value of `(file-options)`.

The *buffer-mode* argument, if supplied, must be one of the symbols that name a buffer mode. The *buffer-mode* argument defaults to `block`.

If *maybe-transcoder* is a transcoder, it becomes the transcoder associated with the port.

If *maybe-transcoder* is `#f` or absent, the port will be a binary port and will support the `port-position` and `set-port-position!` operations. Otherwise the port will be a textual port, and whether it supports the `port-position` and `set-port-position!` operations will be implementation-dependent (and possibly transcoder-dependent).

`(open-bytevector-output-port)` procedure  
`(open-bytevector-output-port maybe-transcoder)` procedure

*Maybe-transcoder* must be either a transcoder or `#f`.

The `open-bytevector-output-port` procedure returns two values: an output port and an extraction procedure. The output port accumulates the data written to it for later extraction by the procedure.

If *maybe-transcoder* is a transcoder, it becomes the transcoder associated with the port. If *maybe-transcoder* is `#f` or absent, the port will be a binary port and will support the `port-position` and `set-port-position!` operations. Otherwise the port will be a textual port, and whether it supports the `port-position` and `set-port-position!` operations will be implementation-dependent (and possibly transcoder-dependent).

The extraction procedure takes no arguments. When called, it returns a bytevector consisting of all the port's accumulated data (regardless of the port's current position), removes the accumulated data from the port, and resets the port's position.

`(call-with-bytevector-output-port proc)` procedure  
`(call-with-bytevector-output-port proc maybe-transcoder)`

*Proc* must accept one argument. *Maybe-transcoder* must be either a transcoder or `#f`.

The `call-with-bytevector-output-port` procedure creates an output port that accumulates the data written to it and calls *proc* with that output port as an argument. Whenever *proc* returns, a bytevector consisting of all of the port's accumulated data (regardless of the port's current position) is returned and the port is closed.

The transcoder associated with the output port is determined as for a call to `open-bytevector-output-port`.

`(open-string-output-port)` procedure

Returns two values: a textual output port and an extraction procedure. The output port accumulates the characters written to it for later extraction by the procedure.

The port may or may not have an associated transcoder; if it does, the transcoder is implementation-dependent. The port should support the `port-position` and `set-port-position!` operations.

The extraction procedure takes no arguments. When called, it returns a string consisting of all of the port's accumulated characters (regardless of the current position), removes the accumulated characters from the port, and resets the port's position.

`(call-with-string-output-port proc)` procedure

*Proc* must accept one argument. Creates a textual output port that accumulates the characters written to it and calls *proc* with that output port as an argument. Whenever *proc* returns, a string consisting of all of the port's accumulated characters (regardless of the port's current position) is returned and the port is closed.

The port may or may not have an associated transcoder; if it does, the transcoder is implementation-dependent. The port should support the `port-position` and `set-port-position!` operations.

`(standard-output-port)` procedure  
`(standard-error-port)` procedure

Returns a fresh binary output port connected to the standard output or standard error respectively. Whether the port supports the `port-position` and `set-port-position!` operations is implementation-dependent.

`(current-output-port)` procedure  
`(current-error-port)` procedure

These return default textual ports for regular output and error output. Normally, these default ports are associated with standard output, and standard error, respectively. The return value of `current-output-port` can be dynamically re-assigned using the `with-output-to-file` procedure from the `(rnrs io simple (6))` library (see section 8.3). A port returned by one of these procedures may or may not have an associated transcoder; if it does, the transcoder is implementation-dependent.

`(make-custom-binary-output-port id procedure  
write! get-position set-position! close)`

Returns a newly created binary output port whose byte sink is an arbitrary algorithm represented by the *write!* procedure. *Id* must be a string naming the new port, provided for informational purposes only. *Write!* must be a procedure and should behave as specified below; it will be called by operations that perform binary output.

Each of the remaining arguments may be `#f`; if any of those arguments is not `#f`, it must be a procedure and should behave as specified in the description of `make-custom-binary-input-port`.

- (*write! bytevector start count*)

*Start* and *count* will be non-negative exact integer objects, and *bytevector* will be a bytevector whose length is at least *start + count*. The *write!* procedure should read up to *count* bytes from *bytevector* starting at index *start* and forward them to the byte sink. If *count*

is 0, the *write!* procedure should have the effect of passing an end-of-file object to the byte sink. In any case, the *write!* procedure should return the number of bytes that it wrote, as an exact integer object.

*Implementation responsibilities:* The implementation is required to check the return values of *write!* only when it actually calls *write!* as part of an I/O operation requested by the program. The implementation is not required to check that *write!* otherwise behaves as described. If it does not, however, the behavior of the resulting port is unspecified.

`(make-custom-textual-output-port id procedure  
write! get-position set-position! close)`

Returns a newly created textual output port whose byte sink is an arbitrary algorithm represented by the *write!* procedure. *Id* must be a string naming the new port, provided for informational purposes only. *Write!* must be a procedure and should behave as specified below; it will be called by operations that perform textual output.

Each of the remaining arguments may be `#f`; if any of those arguments is not `#f`, it must be a procedure and should behave as specified in the description of `make-custom-textual-input-port`.

- (*write! string start count*)

*Start* and *count* will be non-negative exact integer objects, and *string* will be a string whose length is at least *start + count*. The *write!* procedure should read up to *count* characters from *string* starting at index *start* and forward them to the character sink. If *count* is 0, the *write!* procedure should have the effect of passing an end-of-file object to the character sink. In any case, the *write!* procedure should return the number of characters that it wrote, as an exact integer object.

The port may or may not have an associated transcoder; if it does, the transcoder is implementation-dependent.

*Implementation responsibilities:* The implementation is required to check the return values of *write!* only when it actually calls *write!* as part of an I/O operation requested by the program. The implementation is not required to check that *write!* otherwise behaves as described. If it does not, however, the behavior of the resulting port is unspecified.

### 8.2.11. Binary output

`(put-u8 binary-output-port octet)` procedure

Writes *octet* to the output port and returns unspecified values.

(`put-bytevector binary-output-port bytevector`) procedure  
 (`put-bytevector binary-output-port bytevector start`) procedure  
 (`put-bytevector binary-output-port bytevector start count`) procedure

*Start* and *count* must be non-negative exact integer objects that default to 0 and (`bytevector-length bytevector`) – *start*, respectively. *bytevector* must have a length of at least *start* + *count*. The `put-bytevector` procedure writes the *count* bytes of the bytevector *bytevector* starting at index *start* to the output port. The `put-bytevector` procedure returns unspecified values.

### 8.2.12. Textual output

(`put-char textual-output-port char`) procedure

Writes *char* to the port. The `put-char` procedure returns unspecified values.

(`put-string textual-output-port string`) procedure  
 (`put-string textual-output-port string start`) procedure  
 (`put-string textual-output-port string start count`) procedure

*Start* and *count* must be non-negative exact integer objects. *String* must have a length of at least *start* + *count*. *Start* defaults to 0. *Count* defaults to (`string-length string`) – *start*. Writes the *count* characters of *string* starting at index *start* to the port. The `put-string` procedure returns unspecified values.

(`put-datum textual-output-port datum`) procedure

*Datum* should be a datum value. The `put-datum` procedure writes an external representation of *datum* to *textual-output-port*. The specific external representation is implementation-dependent.

*Note:* The `put-datum` procedure merely writes the external representation, but no trailing delimiter. If `put-datum` is used to write several subsequent external representations to an output port, care should be taken to delimit them properly so they can be read back in by subsequent calls to `get-datum`.

### 8.2.13. Input/output ports

(`open-file-input/output-port filename`) procedure  
 (`open-file-input/output-port filename file-options`) procedure  
 (`open-file-input/output-port filename file-options buffer-mode`) procedure

(`open-file-input/output-port filename file-options buffer-mode transcoder`) procedure

Returns a single port that is both an input port and an output port for the named file. The optional arguments default as described in the specification of `open-file-output-port`. If the input/output port supports `port-position` and/or `set-port-position!`, the same port position is used for both input and output.

(`make-custom-binary-input/output-port id read! write! get-position set-position! close`) procedure

Returns a newly created binary input/output port whose byte source and sink are arbitrary algorithms represented by the *read!* and *write!* procedures. *Id* must be a string naming the new port, provided for informational purposes only. *Read!* and *write!* must be procedures, and should behave as specified for the `make-custom-binary-input-port` and `make-custom-binary-output-port` procedures.

Each of the remaining arguments may be `#f`; if any of those arguments is not `#f`, it must be a procedure and should behave as specified in the description of `make-custom-binary-input-port`.

(`make-custom-textual-input/output-port id read! write! get-position set-position! close`) procedure

Returns a newly created textual input/output port whose textual source and sink are arbitrary algorithms represented by the *read!* and *write!* procedures. *Id* must be a string naming the new port, provided for informational purposes only. *Read!* and *write!* must be procedures, and should behave as specified for the `make-custom-textual-input-port` and `make-custom-textual-output-port` procedures.

Each of the remaining arguments may be `#f`; if any of those arguments is not `#f`, it must be a procedure and should behave as specified in the description of `make-custom-textual-input-port`.

## 8.3. Simple I/O

This section describes the (`rnrs io simple (6)`) library, which provides a somewhat more convenient interface for performing textual I/O on ports. This library implements most of the I/O procedures of the previous version of this report [6].

The ports created by the procedures of this library are textual ports associated implementation-dependent transcoders.

(eof-object) procedure  
(eof-object? *obj*) procedure

These are the same as `eof-object` and `eof-object?` from the (rnrs ports (6)) library.

(call-with-input-file *filename proc*) procedure  
(call-with-output-file *filename proc*) procedure

*Proc* should accept one argument. These procedures open the file named by *filename* for input or for output, with no specified file options, and call *proc* with the obtained port as an argument. If *proc* returns, the port is closed automatically and the values returned by *proc* are returned. If *proc* does not return, the port is not closed automatically, unless it is possible to prove that the port will never again be used for an I/O operation.

(input-port? *obj*) procedure  
(output-port? *obj*) procedure

These are the same as the `input-port?` and `output-port?` procedures in the (rnrs io ports (6)) library.

(current-input-port) procedure  
(current-output-port) procedure  
(current-error-port) procedure

These are the same as the `current-input-port`, `current-output-port`, and `current-error-port` procedures from the (rnrs io ports (6)) library.

(with-input-from-file *filename thunk*) procedure  
(with-output-to-file *filename thunk*) procedure

*Thunk* must be a procedure and should accept zero arguments. The file is opened for input or output using empty file options, and *thunk* is called with no arguments. During the dynamic extent of the call to *thunk*, the obtained port is made the value returned by `current-input-port` or `current-output-port` procedures; the previous default values are reinstated when the dynamic extent is exited. When *thunk* returns, the port is closed automatically, and the previous values for `current-input-port`. The values returned by *thunk* are returned. If an escape procedure is used to escape back into the call to *thunk* after *thunk* is returned, the behavior is unspecified.

(open-input-file *filename*) procedure

This opens *filename* for input, with empty file options, and returns the obtained port.

(open-output-file *filename*) procedure

This opens *filename* for output, with empty file options, and returns the obtained port.

(close-input-port *input-port*) procedure  
(close-output-port *output-port*) procedure

This closes *input-port* or *output-port*, respectively.

(read-char) procedure  
(read-char *textual-input-port*) procedure

This reads from *textual-input-port*, blocking as necessary until a character is available from *textual-input-port*, or the data that are available cannot be the prefix of any valid encoding, or an end of file is reached.

If a complete character is available before the next end of file, `read-char` returns that character, and updates the input port to point past that character. If an end of file is reached before any data are read, `read-char` returns the end-of-file object.

If *textual-input-port* is omitted, it defaults to the value returned by `current-input-port`.

(peek-char) procedure  
(peek-char *textual-input-port*) procedure

This is the same as `read-char`, but does not consume any data from the port.

(read) procedure  
(read *textual-input-port*) procedure

Reads an external representation from *textual-input-port* and returns the datum it represents. The `read` procedure operates in the same way as `get-datum`, see section 8.2.9.

If *textual-input-port* is omitted, it defaults to the value returned by `current-input-port`.

(write-char *char*) procedure  
(write-char *char textual-output-port*) procedure

Writes an encoding of the character *char* to the *textual-output-port*. This returns unspecified values.

If *textual-output-port* is omitted, it defaults to the value returned by `current-output-port`.

(newline) procedure  
(newline *textual-output-port*) procedure

This is equivalent to using `write-char` to write `#\linefeed` to *textual-output-port*.

If *textual-output-port* is omitted, it defaults to the value returned by `current-output-port`.

(display *obj*) procedure  
(display *obj textual-output-port*) procedure

Writes a representation of *obj* to the given *textual-output-port*. Strings that appear in the written representation are not enclosed in doublequotes, and

no characters are escaped within those strings. Character objects appear in the representation as if written by `write-char` instead of by `write`. The `display` procedure returns unspecified values. The `textual-output-port` argument may be omitted, in which case it defaults to the value returned by `current-output-port`.

(`write obj`) procedure  
(`write obj textual-output-port`) procedure

Writes the external representation of *obj* to *textual-output-port*. The `write` procedure operates in the same way as `put-datum`; see section 8.2.12.

If *textual-output-port* is omitted, it defaults to the value returned by `current-output-port`.

## 9. File system

This chapter describes the (`rnrs files (6)`) library for operations on the file system. This library, in addition to the procedures described here, also exports the I/O condition types described in section 8.1.

(`file-exists? filename`) procedure

*Filename* must be a filename (see section 8.2.1). The `file-exists?` procedure returns `#t` if the named file exists at the time the procedure is called, `#f` otherwise.

(`delete-file filename`) procedure

*Filename* must be a filename (see section 8.2.1). The `delete-file` procedure deletes the named file if it exists and can be deleted, and returns unspecified values. If the file does not exist or cannot be deleted, an exception with condition type `&i/o-filename` is raised.

## 10. Command-line access and exit values

The procedures described in this section are exported by the (`rnrs programs (6)`) library.

(`command-line`) procedure

Returns a nonempty list of strings. The first element is an implementation-specific name for the running top-level program. The remaining elements are command-line arguments according to the operating system's conventions.

(`exit`) procedure  
(`exit obj`) procedure

Exits the running program and communicates an exit value to the operating system. If no argument is supplied, the

`exit` procedure should communicate to the operating system that the program exited normally. If an argument is supplied, the `exit` procedure should translate the argument into an appropriate exit value for the operating system. If *obj* is `#f`, the exit is assumed to be abnormal.

## 11. Arithmetic

This chapter describes Scheme's libraries for more specialized numerical operations: `fixnum` and `flonum` arithmetic, as well as bitwise operations on exact integer objects.

### 11.1. Fixnums

Every implementation must define its `fixnum` range as a closed interval

$$[-2^{w-1}, 2^{w-1} - 1]$$

such that *w* is a (mathematical) integer  $w \geq 24$ . Every mathematical integer within an implementation's `fixnum` range must correspond to an exact integer object that is representable within the implementation. A `fixnum` is an exact integer object whose value lies within this `fixnum` range.

This section describes the (`rnrs arithmetic fx (6)`) library, which defines various operations on `fixnums`. `Fixnum` operations perform integer arithmetic on their `fixnum` arguments, but raise an exception with condition type `&implementation-restriction` if the result is not a `fixnum`.

This section uses *fx*, *fx<sub>1</sub>*, *fx<sub>2</sub>*, etc., as parameter names for arguments that must be `fixnums`.

(`fixnum? obj`) procedure

Returns `#t` if *obj* is an exact integer object within the `fixnum` range, `#f` otherwise.

(`fixnum-width`) procedure

(`least-fixnum`) procedure

(`greatest-fixnum`) procedure

These procedures return *w*,  $-2^{w-1}$  and  $2^{w-1} - 1$ : the width, minimum and the maximum value of the `fixnum` range, respectively.

(`fx=? fx1 fx2 fx3 ...`) procedure

(`fx>? fx1 fx2 fx3 ...`) procedure

(`fx<? fx1 fx2 fx3 ...`) procedure

(`fx>=? fx1 fx2 fx3 ...`) procedure

(`fx<=? fx1 fx2 fx3 ...`) procedure

These procedures return `#t` if their arguments are (respectively): equal, monotonically increasing, monotonically decreasing, monotonically nondecreasing, or monotonically nonincreasing, `#f` otherwise.

```
(fxzero? fx)           procedure
(fxpositive? fx)       procedure
(fxnegative? fx)       procedure
(fxodd? fx)            procedure
(fxeven? fx)           procedure
```

These numerical predicates test a fixnum for a particular property, returning **#t** or **#f**. The five properties tested by these procedures are: whether the number object is zero, greater than zero, less than zero, odd, or even.

```
(fxmax fx1 fx2 ...) procedure
(fxmin fx1 fx2 ...) procedure
```

These procedures return the maximum or minimum of their arguments.

```
(fx+ fx1 fx2)         procedure
(fx* fx1 fx2)         procedure
```

These procedures return the sum or product of their arguments, provided that sum or product is a fixnum. An exception with condition type **&implementation-restriction** is raised if that sum or product is not a fixnum.

```
(fx- fx1 fx2)         procedure
(fx- fx)                procedure
```

With two arguments, this procedure returns the difference of its arguments, provided that difference is a fixnum.

With one argument, this procedure returns the additive inverse of its argument, provided that integer object is a fixnum.

An exception with condition type **&assertion** is raised if the mathematically correct result of this procedure is not a fixnum.

```
(fx- (least-fixnum))
  ⇒ &assertion exception
```

```
(fxdiv-and-mod fx1 fx2) procedure
(fxdiv fx1 fx2)         procedure
(fxmod fx1 fx2)         procedure
(fxdiv0-and-mod0 fx1 fx2) procedure
(fxdiv0 fx1 fx2)       procedure
(fxmod0 fx1 fx2)       procedure
```

$fx_2$  must be nonzero. These procedures implement number-theoretic integer division and return the results of the corresponding mathematical operations specified in report section 9.8.3.

```
(fxdiv fx1 fx2)           ⇒ fx1 div fx2
(fxmod fx1 fx2)           ⇒ fx1 mod fx2
(fxdiv-and-mod fx1 fx2)
  ⇒ fx1 div fx2, fx1 mod fx2
```

```
                                ; two return values
(fxdiv0 fx1 fx2)           ⇒ fx1 div0 fx2
(fxmod0 fx1 fx2)           ⇒ fx1 mod0 fx2
(fxdiv0-and-mod0 fx1 fx2)
  ⇒ fx1 fx1 div0 fx2, fx1 mod0 fx2
                                ; two return values
```

```
(fx+/carry fx1 fx2 fx3) procedure
```

Returns the two fixnum results of the following computation:

```
(let* ((s (+ fx1 fx2 fx3))
       (s0 (mod0 s (expt 2 (fixnum-width))))
       (s1 (div0 s (expt 2 (fixnum-width)))))
      (values s0 s1))
```

```
(fx-/carry fx1 fx2 fx3) procedure
```

Returns the two fixnum results of the following computation:

```
(let* ((d (- fx1 fx2 fx3))
       (d0 (mod0 d (expt 2 (fixnum-width))))
       (d1 (div0 d (expt 2 (fixnum-width)))))
      (values d0 d1))
```

```
(fx*/carry fx1 fx2 fx3) procedure
```

Returns the two fixnum results of the following computation:

```
(let* ((s (+ (* fx1 fx2) fx3))
       (s0 (mod0 s (expt 2 (fixnum-width))))
       (s1 (div0 s (expt 2 (fixnum-width)))))
      (values s0 s1))
```

```
(fxnot fx)                procedure
```

Returns the unique fixnum that is congruent mod  $2^w$  to the one's-complement of  $fx$ .

```
(fxand fx1 ...)          procedure
(fxiior fx1 ...)          procedure
(fxxor fx1 ...)           procedure
```

These procedures return the fixnum that is the bit-wise “and”, “inclusive or”, or “exclusive or” of the two’s complement representations of their arguments. If they are passed only one argument, they return that argument. If they are passed no arguments, they return the fixnum (either  $-1$  or  $0$ ) that acts as identity for the operation.

```
(fxif fx1 fx2 fx3)      procedure
```

Returns the fixnum result of the following computation:

```
(fxiior (fxand fx1 fx2)
        (fxand (fxnot fx1) fx3))
```

(**fxbit-count** *fx*) procedure

If *fx* is non-negative, this procedure returns the number of 1 bits in the two's complement representation of *fx*. Otherwise it returns the result of the following computation:

```
(fxnot (fxbit-count (fxnot ei)))
```

(**fxlength** *fx*) procedure

Returns the fixnum result of the following computation:

```
(do ((result 0 (+ result 1))
    (bits (if (fxnegative? fx)
              (fxnot fx)
              fx)
      (fxarithmetic-shift-right bits 1)))
  ((fxzero? bits)
   result))
```

(**fxfirst-bit-set** *fx*) procedure

Returns the index of the least significant 1 bit in the two's complement representation of *fx*. If *fx* is 0, then  $-1$  is returned.

```
(fxfirst-bit-set 0)    => -1
(fxfirst-bit-set 1)    =>  0
(fxfirst-bit-set -4)   =>  2
```

(**fxbit-set?** *fx fx<sub>2</sub>*) procedure

*Fx<sub>2</sub>* must be non-negative and less than (**fixnum-width**). The **fxbit-set?** procedure returns the fixnum result of the following computation:

```
(not
 (fxzero?
  (fxand fx1
   (fxarithmetic-shift-left 1 fx2))))
```

(**fxcopy-bit** *fx<sub>1</sub> fx<sub>2</sub> fx<sub>3</sub>*) procedure

*Fx<sub>2</sub>* must be non-negative and less than (**fixnum-width**). *Fx<sub>3</sub>* must be 0 or 1. The **fxcopy-bit** procedure returns the result of the following computation:

```
(let* ((mask (fxarithmetic-shift-left 1 fx2)))
  (fxif mask
   (fxarithmetic-shift-left fx3 fx2)
   fx1))
```

(**fxbit-field** *fx<sub>1</sub> fx<sub>2</sub> fx<sub>3</sub>*) procedure

*Fx<sub>2</sub>* and *fx<sub>3</sub>* must be non-negative and less than (**fixnum-width**). Moreover, *fx<sub>2</sub>* must be less than or equal to *fx<sub>3</sub>*. The **fxbit-field** procedure returns the fixnum result of the following computation:

```
(let* ((mask (fxnot
              (fxarithmetic-shift-left -1 fx3))))
  (fxarithmetic-shift-right (fxand fx1 mask)
                             fx2))
```

(**fxcopy-bit-field** *fx<sub>1</sub> fx<sub>2</sub> fx<sub>3</sub> fx<sub>4</sub>*) procedure

*Fx<sub>2</sub>* and *fx<sub>3</sub>* must be non-negative and less than (**fixnum-width**). Moreover, *fx<sub>2</sub>* must be less than or equal to *fx<sub>3</sub>*. The **fxcopy-bit-field** procedure returns the fixnum result of the following computation:

```
(let* ((to   fx1)
       (start fx2)
       (end   fx3)
       (from  fx4)
       (mask1 (fxarithmetic-shift-left -1 start))
       (mask2 (fxnot
               (fxarithmetic-shift-left -1 end)))
       (mask  (fxand mask1 mask2)))
  (fxif mask
   (fxarithmetic-shift-left from start)
   to))
```

(**fxarithmetic-shift** *fx<sub>1</sub> fx<sub>2</sub>*) procedure

The absolute value of *fx<sub>2</sub>* must be less than (**fixnum-width**). If

```
(* fx1 (expt 2 fx2))
```

is a fixnum, then that fixnum is returned. Otherwise an exception with condition type **&implementation-restriction** is raised.

(**fxarithmetic-shift-left** *fx<sub>1</sub> fx<sub>2</sub>*) procedure

(**fxarithmetic-shift-right** *fx<sub>1</sub> fx<sub>2</sub>*) procedure

*Fx<sub>2</sub>* must be non-negative. **fxarithmetic-shift-left** behaves the same as **fxarithmetic-shift**, and (**fxarithmetic-shift-right** *fx<sub>1</sub> fx<sub>2</sub>*) behaves the same as (**fxarithmetic-shift** *fx<sub>1</sub> (fixnum- fx<sub>2</sub>)*).

(**fxrotate-bit-field** *fx<sub>1</sub> fx<sub>2</sub> fx<sub>3</sub> fx<sub>4</sub>*) procedure

*Fx<sub>2</sub>*, *fx<sub>3</sub>*, and *fx<sub>4</sub>* must be non-negative and less than (**fixnum-width**). *Fx<sub>4</sub>* must be less than the difference between *fx<sub>3</sub>* and *fx<sub>3</sub>*. The **fxrotate-bit-field** procedure returns the result of the following computation:

```
(let* ((n   fx1)
       (start fx2)
       (end   fx3)
       (count fx4)
       (width (fx- end start)))
  (if (fxpositive? width)
      (let* ((count (fxmod count width))
             (field0
              (fxbit-field n start end))
             (field1
              (fxarithmetic-shift-left
               field0 count)))
        (field2
         (fxarithmetic-shift-right
          field0 (fx- width count)))
         (field (fxior field1 field2)))
      (fxcopy-bit-field n start end field))
      n))
```

(`fxreverse-bit-field`  $fx_1$   $fx_2$   $fx_3$ ) procedure  
 $fx_2$  and  $fx_3$  must be non-negative and less than (`fixnum-width`). Moreover,  $fx_2$  must be less than or equal to  $fx_3$ . The `fxreverse-bit-field` procedure returns the fixnum obtained from  $fx_1$  by reversing the bit field specified by  $fx_2$  and  $fx_3$ .

```
(fxreverse-bit-field #b1010010 1 4)
  => 88 ; #b1011000
(fxreverse-bit-field #b1010010 91 -4)
  => 82 ; #b1010010
```

## 11.2. Flonums

This section describes the (`rnrs arithmetic flonum` (6)) library.

This section uses  $fl$ ,  $fl_1$ ,  $fl_2$ , etc., as parameter names for arguments that must be flonums, and  $ifl$  as a name for arguments that must be integer-valued flonums, i.e., flonums for which the `integer-valued?` predicate returns true.

(`flonum?`  $obj$ ) procedure

Returns `#t` if  $obj$  is a flonum, `#f` otherwise.

(`real->flonum`  $x$ ) procedure

Returns the best flonum representation of  $x$ .

The value returned is a flonum that is numerically closest to the argument.

*Note:* If flonums are represented in binary floating point, then implementations are strongly encouraged to break ties by preferring the floating point representation whose least significant bit is zero.

```
(fl=?  $fl_1$   $fl_2$   $fl_3$  ...) procedure
(fl<?  $fl_1$   $fl_2$   $fl_3$  ...) procedure
(fl<=?  $fl_1$   $fl_2$   $fl_3$  ...) procedure
(fl>?  $fl_1$   $fl_2$   $fl_3$  ...) procedure
(fl>=?  $fl_1$   $fl_2$   $fl_3$  ...) procedure
```

These procedures return `#t` if their arguments are (respectively): equal, monotonically increasing, monotonically decreasing, monotonically nondecreasing, or monotonically nonincreasing, `#f` otherwise. These predicates are required to be transitive.

```
(fl= +inf.0 +inf.0) => #t
(fl= -inf.0 +inf.0) => #f
(fl= -inf.0 -inf.0) => #t
(fl= 0.0 -0.0) => #t
(fl< 0.0 -0.0) => #f
(fl= +nan.0  $fl$ ) => #f
(fl< +nan.0  $fl$ ) => #f
```

```
(flinteger?  $fl$ ) procedure
(flzero?  $fl$ ) procedure
(flpositive?  $fl$ ) procedure
(flnegative?  $fl$ ) procedure
(flodd?  $ifl$ ) procedure
(fleven?  $ifl$ ) procedure
(flfinite?  $fl$ ) procedure
(flinfinite?  $fl$ ) procedure
(flnan?  $fl$ ) procedure
```

These numerical predicates test a flonum for a particular property, returning `#t` or `#f`. The `flinteger?` procedure tests whether the number object is an integer, `flzero?` tests whether it is `fl=?` to zero, `flpositive?` tests whether it is greater than zero, `flnegative?` tests whether it is less than zero, `flodd?` tests whether it is odd, `fleven?` tests whether it is even, `flfinite?` tests whether it is not an infinity and not a NaN, `flinfinite?` tests whether it is an infinity, and `flnan?` tests whether it is a NaN.

```
(flnegative? -0.0) => #f
(flfinite? +inf.0) => #f
(flfinite? 5.0) => #t
(flinfinite? 5.0) => #f
(flinfinite? +inf.0) => #t
```

*Note:* (`flnegative? -0.0`) must return `#f`, else it would lose the correspondence with (`fl< -0.0 0.0`), which is `#f` according to the IEEE standards.

```
(flmax  $fl_1$   $fl_2$  ...) procedure
(flmin  $fl_1$   $fl_2$  ...) procedure
```

These procedures return the maximum or minimum of their arguments. They always return a NaN when one or more of the arguments is a NaN.

```
(fl+  $fl_1$  ...) procedure
(fl*  $fl_1$  ...) procedure
```

These procedures return the flonum sum or product of their flonum arguments. In general, they should return the flonum that best approximates the mathematical sum or product. (For implementations that represent flonums using IEEE binary floating point, the meaning of “best” is defined by the IEEE standards.)

```
(fl+ +inf.0 -inf.0) => +nan.0
(fl+ +nan.0  $fl$ ) => +nan.0
(fl* +nan.0  $fl$ ) => +nan.0
```

```
(fl-  $fl_1$   $fl_2$  ...) procedure
(fl-  $fl$ ) procedure
(fl/  $fl_1$   $fl_2$  ...) procedure
(fl/  $fl$ ) procedure
```

With two or more arguments, these procedures return the flonum difference or quotient of their flonum arguments,

associating to the left. With one argument, however, they return the additive or multiplicative flonum inverse of their argument. In general, they should return the flonum that best approximates the mathematical difference or quotient. (For implementations that represent flonums using IEEE binary floating point, the meaning of “best” is reasonably well-defined by the IEEE standards.)

```
(fl- +inf.0 +inf.0)      ==> +nan.0
```

For undefined quotients, `fl/` behaves as specified by the IEEE standards:

```
(fl/ 1.0 0.0)           ==> +inf.0
(fl/ -1.0 0.0)          ==> -inf.0
(fl/ 0.0 0.0)           ==> +nan.0
```

```
(flabs fl)              procedure
```

Returns the absolute value of *fl*.

```
(fldiv-and-mod fl1 fl2)      procedure
(fldiv fl1 fl2)              procedure
(flmod fl1 fl2)              procedure
(fldiv0-and-mod0 fl1 fl2)    procedure
(fldiv0 fl1 fl2)             procedure
(flmod0 fl1 fl2)            procedure
```

These procedures implement number-theoretic integer division and return the results of the corresponding mathematical operations specified in report section 9.8.3. For zero divisors, these procedures may return a NaN or some meaningless flonum.

```
(fldiv fl1 fl2)              ==> fl1 div fl2
(flmod fl1 fl2)              ==> fl1 mod fl2
(fldiv-and-mod fl1 fl2)
  ==> fl1 div fl2, fl1 mod fl2
  ; two return values
(fldiv0 fl1 fl2)            ==> fl1 div0 fl2
(flmod0 fl1 fl2)            ==> fl1 mod0 fl2
(fldiv0-and-mod0 fl1 fl2)
  ==> fl1 div0 fl2, fl1 mod0 fl2
  ; two return values
```

```
(flnumerator fl)        procedure
(fldenominator fl)      procedure
```

These procedures return the numerator or denominator of *fl* as a flonum; the result is computed as if *fl* was represented as a fraction in lowest terms. The denominator is always positive. The denominator of 0.0 is defined to be 1.0.

```
(flnumerator +inf.0)    ==> +inf.0
(flnumerator -inf.0)    ==> -inf.0
(fldenominator +inf.0)  ==> 1.0
(fldenominator -inf.0)  ==> 1.0
(flnumerator 0.75)      ==> 3.0 ; probably
(fldenominator 0.75)    ==> 4.0 ; probably
```

The following behavior is strongly recommended but not required:

```
(flnumerator -0.0)      ==> -0.0
```

```
(flfloor fl)            procedure
(flceiling fl)          procedure
(fltruncate fl)         procedure
(flround fl)            procedure
```

These procedures return integral flonums for flonum arguments that are not infinities or NaNs. For such arguments, `flfloor` returns the largest integral flonum not larger than *fl*. The `flceiling` procedure returns the smallest integral flonum not smaller than *fl*. The `fltruncate` procedure returns the integral flonum closest to *fl* whose absolute value is not larger than the absolute value of *fl*. The `flround` procedure returns the closest integral flonum to *fl*, rounding to even when *fl* represents a number halfway between two integers.

Although infinities and NaNs are not integer objects, these procedures return an infinity when given an infinity as an argument, and a NaN when given a NaN:

```
(flfloor +inf.0)        ==> +inf.0
(flceiling -inf.0)      ==> -inf.0
(fltruncate +nan.0)     ==> +nan.0
```

```
(flexp fl)              procedure
(fillog fl)             procedure
(fillog fl1 fl2)        procedure
(fl1sin fl)             procedure
(fl1cos fl)            procedure
(fl1tan fl)            procedure
(fl1asin fl)          procedure
(fl1acos fl)          procedure
(fl1atan fl)          procedure
(fl1atan fl1 fl2)    procedure
```

These procedures compute the usual transcendental functions. The `fexp` procedure computes the base-*e* exponential of *fl*. The `fillog` procedure with a single argument computes the natural logarithm of *fl* (not the base ten logarithm); `(fillog fl1 fl2)` computes the base-*fl<sub>2</sub>* logarithm of *fl<sub>1</sub>*. The `fl1sin`, `fl1cos`, and `fl1atan` procedures compute arcsine, arccosine, and arctangent, respectively. `(fl1atan fl1 fl2)` computes the arc tangent of *fl<sub>1</sub>/fl<sub>2</sub>*.

See report section 9.8.3 for the underlying mathematical operations. In the event that these operations do not yield a real result for the given arguments, the result may be a NaN, or may be some meaningless flonum.

Implementations that use IEEE binary floating point arithmetic are encouraged to follow the relevant standards for these procedures.

```

(flexp +inf.0)           => +inf.0
(flexp -inf.0)          => 0.0
(fllog +inf.0)          => +inf.0
(fllog 0.0)             => -inf.0
(fllog -0.0)            => unspecified
                        ; if -0.0 is distinguished
(fllog -inf.0)          => +nan.0
(flatan -inf.0)         => -1.5707963267948965
                        ; approximately
(flatan +inf.0)         => 1.5707963267948965
                        ; approximately

```

(flsqrt *fl*) procedure

Returns the principal square root of *fl*. For  $-0.0$ , flsqrt should return  $-0.0$ ; for other negative arguments, the result may be a NaN or some meaningless flonum.

```

(flsqrt +inf.0)          => +inf.0
(flsqrt -0.0)           => -0.0

```

(flexpt *fl<sub>1</sub>* *fl<sub>2</sub>*) procedure

Returns *fl<sub>1</sub>* raised to the power *fl<sub>2</sub>*. Either *fl<sub>1</sub>* should be non-negative, or, if *fl<sub>1</sub>* is negative, *fl<sub>2</sub>* should be an integer object; otherwise, the result may be a NaN, or may be some meaningless flonum. If *fl<sub>1</sub>* is zero, then the result is zero.

```

&no-infinities          condition type
(make-no-infinities-violation obj)  procedure
(no-infinities-violation? obj)      procedure
&no-nans                condition type
(make-no-nans-violation obj)        procedure
(no-nans-violation? obj)           procedure

```

These condition types could be defined by the following code:

```

(define-condition-type &no-infinities
  &implementation-restriction
  make-no-infinities-violation no-infinities-violation)
(define-condition-type &no-nans
  &implementation-restriction
  make-no-nans-violation no-nans-violation?)

```

These types describe that a program has executed an arithmetic operations that is specified to return an infinity or a NaN, respectively, on a Scheme implementation that is not able to represent the infinity or NaN. (See report section 9.8.2.)

(fixnum->flonum *fx*) procedure

Returns a flonum that is numerically closest to *fx*.

*Note:* The result of this procedure may not be numerically equal to *fx*, because the fixnum precision may be greater than the flonum precision.

### 11.3. Exact bitwise arithmetic

This section describes the (rnrs arithmetic bitwise (6)) library. The exact bitwise arithmetic provides generic operations on exact integer objects. This section uses *ei*, *ei<sub>1</sub>*, *ei<sub>2</sub>*, etc., as parameter names that must be exact integer objects.

Some procedures allow extracting *bit fields*, i.e., number objects representing subsequences of the binary representation of an exact integer object. Bit fields are always positive, and always defined using a finite number of bits, contrary to 2's complement representation which implicitly uses an infinite extension of 0 bits or 1 bits to the left.

(bitwise-not *ei*) procedure

Returns the exact integer object whose two's complement representation is the one's complement of the two's complement representation of *ei*.

(bitwise-and *ei<sub>1</sub>* ...) procedure

(bitwise-ior *ei<sub>1</sub>* ...) procedure

(bitwise-xor *ei<sub>1</sub>* ...) procedure

These procedures return the exact integer object that is the bit-wise "and", "inclusive or", or "exclusive or" of the two's complement representations of their arguments. If they are passed only one argument, they return that argument. If they are passed no arguments, they return the integer object (either  $-1$  or  $0$ ) that acts as identity for the operation.

(bitwise-if *ei<sub>1</sub>* *ei<sub>2</sub>* *ei<sub>3</sub>*) procedure

Returns the exact integer object that is the result of the following computation:

```

(bitwise-ior (bitwise-and ei1 ei2)
             (bitwise-and (bitwise-not ei1) ei3))

```

(bitwise-bit-count *ei*) procedure

If *ei* is non-negative, this procedure returns the number of 1 bits in the two's complement representation of *ei*. Otherwise it returns the result of the following computation:

```

(bitwise-not (bitwise-bit-count (bitwise-not ei)))

```

(bitwise-length *ei*) procedure

Returns the exact integer object that is the result of the following computation:

```

(do ((result 0 (+ result 1))
    (bits (if (negative? ei)
              (bitwise-not ei)
              ei))
    (bitwise-arithmetic-shift bits -1)))
  ((zero? bits)
   result))

```

(bitwise-first-bit-set *ei*) procedure

Returns the index of the least significant 1 bit in the two's complement representation of *ei*. If *ei* is 0, then -1 is returned.

```
(bitwise-first-bit-set 0)  => -1
(bitwise-first-bit-set 1)  =>  0
(bitwise-first-bit-set -4) =>  2
```

(bitwise-bit-set? *ei1 ei2*) procedure

*Ei2* must be non-negative. Returns the result of the following computation:

```
(not (zero?
      (bitwise-and
       (bitwise-arithmetic-shift-left 1 ei2)
       ei1)))
```

(bitwise-copy-bit *ei1 ei2 ei3*) procedure

*Ei2* must be non-negative, and *ei3* must be either 0 or 1. The bitwise-copy-bit procedure returns the result of the following computation:

```
(let* ((mask (bitwise-arithmetic-shift-left 1 ei2)))
      (bitwise-if mask
                  (bitwise-arithmetic-shift-left ei3 ei2)
                  ei1))
```

(bitwise-bit-field *ei1 ei2 ei3*) procedure

*Ei2* and *ei3* must be non-negative, and *ei2* must be less than or equal to *ei3*. This procedure returns the result of the following computation:

```
(let ((mask
      (bitwise-not
       (bitwise-arithmetic-shift-left -1 ei3))))
      (bitwise-arithmetic-shift-right
       (bitwise-and ei1 mask)
       ei2))
```

(bitwise-copy-bit-field *ei1 ei2 ei3 ei4*) procedure

*Ei2* and *ei3* must be non-negative, and *ei2* must be less than or equal to *ei3*. The bitwise-copy-bit-field procedure returns the result of the following computation:

```
(let* ((to   ei1)
      (start ei2)
      (end   ei3)
      (from  ei4)
      (mask1
       (bitwise-arithmetic-shift-left -1 start))
      (mask2
       (bitwise-not
        (bitwise-arithmetic-shift-left -1 end)))
      (mask (bitwise-and mask1 mask2)))
      (bitwise-if mask
                  (bitwise-arithmetic-shift-left from
                                                    start)
                  to))
```

(bitwise-arithmetic-shift *ei1 ei2*) procedure

Returns the result of the following computation:

```
(floor (* ei1 (expt 2 ei2)))
```

Examples:

```
(bitwise-arithmetic-shift -6 -1)
=> -3
(bitwise-arithmetic-shift -5 -1)
=> -3
(bitwise-arithmetic-shift -4 -1)
=> -2
(bitwise-arithmetic-shift -3 -1)
=> -2
(bitwise-arithmetic-shift -2 -1)
=> -1
(bitwise-arithmetic-shift -1 -1)
=> -1
```

(bitwise-arithmetic-shift-left *ei1 ei2*) procedure

(bitwise-arithmetic-shift-right *ei1 ei2*) procedure

*Ei2* must be non-negative. The bitwise-arithmetic-shift-left procedure returns the same result as bitwise-arithmetic-shift, and (bitwise-arithmetic-shift-right *ei1 ei2*) returns the same result as (bitwise-arithmetic-shift *ei1 (-ei2)*).

(bitwise-rotate-bit-field *ei1 ei2 ei3 ei4*) procedure

*Ei2*, *ei3*, *ei4* must be non-negative, *ei2* must be less than or equal to *ei3*, and *ei4* must be non-negative. The procedure returns the result of the following computation:

```
(let* ((n   ei1)
      (start ei2)
      (end   ei3)
      (count ei4)
      (width (- end start)))
      (if (positive? width)
          (let* ((count (mod count width))
                (field0
                 (bitwise-bit-field n start end))
                (field1 (bitwise-arithmetic-shift-left
                        field0 count))
                (field2 (bitwise-arithmetic-shift-right
                        field0
                        (- width count)))
                (field (bitwise-ior field1 field2)))
            (bitwise-copy-bit-field n start end field)
            n))
```

(bitwise-reverse-bit-field *ei1 ei2 ei3*) procedure

*Ei2* and *ei3* must be non-negative, and *ei2* must be less than or equal to *ei3*. The bitwise-reverse-bit-field procedure returns the result obtained from *ei1* by reversing the bit field specified by *ei2* and *ei3*.

```
(bitwise-reverse-bit-field #b1010010 1 4)
  ⇒ 88 ; #b1011000
(bitwise-reverse-bit-field #1010010 91 -4)
  ⇒ &assertion exception
```

## 12. syntax-case

The (`rnrs syntax-case` (6)) library provides support for writing low-level macros in a high-level style, with automatic syntax checking, input destructuring, output restructuring, maintenance of lexical scoping and referential transparency (hygiene), and support for controlled identifier capture.

### 12.1. Hygiene

Barendregt’s *hygiene condition* [1] for the lambda-calculus is an informal notion that requires the free variables of an expression  $N$  that is to be substituted into another expression  $M$  not to be captured by bindings in  $M$  when such capture is not intended. Kohlbecker, et al [8] propose a corresponding *hygiene condition for macro expansion* that applies in all situations where capturing is not explicit: “Generated identifiers that become binding instances in the completely expanded program must only bind variables that are generated at the same transcription step”. In the terminology of this document, the “generated identifiers” are those introduced by a transformer rather than those present in the form passed to the transformer, and a “macro transcription step” corresponds to a single call by the expander to a transformer. Also, the hygiene condition applies to all introduced bindings rather than to introduced variable bindings alone.

This leaves open what happens to an introduced identifier that appears outside the scope of a binding introduced by the same call. Such an identifier refers to the lexical binding in effect where it appears (within a `syntax` (template); see section 12.4) inside the transformer body or one of the helpers it calls. This is essentially the referential transparency property described by Clinger and Rees [3].

Thus, the hygiene condition can be restated as follows:

A binding for an identifier introduced into the output of a transformer call from the expander must capture only references to the identifier introduced into the output of the same transformer call. A reference to an identifier introduced into the output of a transformer refers to the closest enclosing binding for the introduced identifier or, if it appears outside of any enclosing binding for the introduced identifier, the closest enclosing lexical binding where the identifier appears (within a `syntax` (template)) inside the transformer body or one of the helpers it calls.

Explicit captures are handled via `datum->syntax`; see section 12.6.

Operationally, the expander can maintain hygiene with the help of *marks* and *substitutions*. Marks are applied selectively by the expander to the output of each transformer it invokes, and substitutions are applied to the portions of each binding form that are supposed to be within the scope of the bound identifiers. Marks are used to distinguish like-named identifiers that are introduced at different times (either present in the source or introduced into the output of a particular transformer call), and substitutions are used to map identifiers to their expand-time values.

Each time the expander encounters a macro use, it applies an *antimark* to the input form, invokes the associated transformer, then applies a fresh mark to the output. Marks and antimarks cancel, so the portions of the input that appear in the output are effectively left unmarked, while the portions of the output that are introduced are marked with the fresh mark.

Each time the expander encounters a binding form it creates a set of substitutions, each mapping one of the (possibly marked) bound identifiers to information about the binding. (For a `lambda` expression, the expander might map each bound identifier to a representation of the formal parameter in the output of the expander. For a `let-syntax` form, the expander might map each bound identifier to the associated transformer.) These substitutions are applied to the portions of the input form in which the binding is supposed to be visible.

Marks and substitutions together form a *wrap* that is layered on the form being processed by the expander and pushed down toward the leaves as necessary. A wrapped form is referred to as a *wrapped syntax object*. Ultimately, the wrap may rest on a leaf that represents an identifier, in which case the wrapped syntax object is referred to more precisely as an *identifier*. An identifier contains a name along with the wrap. (Names are typically represented by symbols.)

When a substitution is created to map an identifier to an expand-time value, the substitution records the name of the identifier and the set of marks that have been applied to that identifier, along with the associated expand-time value. The expander resolves identifier references by looking for the latest matching substitution to be applied to the identifier, i.e., the outermost substitution in the wrap whose name and marks match the name and marks recorded in the substitution. The name matches if it is the same name (if using symbols, then by `eq?`), and the marks match if the marks recorded with the substitution are the same as those that appear *below* the substitution in the wrap, i.e., those that were applied *before* the substitution. Marks applied after a substitution, i.e., appear over the substitution in the wrap, are not relevant and are ignored.

An algebra that defines how marks and substitutions work more precisely is given in section 2.4 of Oscar Waddell's PhD thesis [11].

## 12.2. Syntax objects

A *syntax object* is a representation of a Scheme form that contains contextual information about the form in addition to its structure. This contextual information is used by the expander to maintain lexical scoping and may also be used by an implementation to maintain source-object correlation.

Syntax objects may be wrapped or unwrapped. A wrapped syntax object (section 12.1) consists of a *wrap* (section 12.1) and some internal representation of a Scheme form. (The internal representation is unspecified, but is typically a datum value or datum value annotated with source information.) A wrapped syntax object representing an identifier is itself referred to as an identifier; thus, the term *identifier* may refer either to the syntactic entity (symbol, variable, or keyword) or to the concrete representation of the syntactic entity as a syntax object. Wrapped syntax objects may or may not be distinct from other types of values, but syntax objects representing identifiers are distinct from other types of values.

An unwrapped syntax object is one that is unwrapped, fully or partially, i.e., whose outer layers consist of lists and vectors and whose leaves are either wrapped syntax objects or nonsymbol values.

The term syntax object is used in this document to refer to a syntax object that is either wrapped or unwrapped. More formally, a syntax object is:

- a pair of syntax objects,
- a vector of syntax objects,
- a nonpair, nonvector, nonsymbol value, or
- a wrapped syntax object.

The distinction between the terms “syntax object” and “wrapped syntax object” is important. For example, when invoked by the expander, a transformer (section 12.3) must accept a wrapped syntax object but may return any syntax object, including an unwrapped syntax object.

## 12.3. Transformers

In `define-syntax` (report section 9.3.2), `let-syntax`, and `letrec-syntax` forms (report section 9.19), a binding for a syntactic keyword must be an expression that evaluates to a *transformer*. (This is only the user's responsibility;

the implementation must check this only if evaluation of a transformer expression actually terminates. See the respective specifications.)

A transformer is a *transformation procedure* or a *variable transformer*. A transformation procedure is a procedure that must accept one argument, a wrapped syntax object (section 12.2) representing the input, and return a *syntax object* (section 12.2) representing the output. The transformer is called by the expander whenever a reference to a keyword with which it has been associated is found. If the keyword appears in the car of a list-structured input form, the transformer receives the entire list-structured form, and its output replaces the entire form. Except with variable transformers (see below), if the keyword is found in any other definition or expression context, the transformer receives a wrapped syntax object representing just the keyword reference, and its output replaces just the reference. Except with variable transformers, an exception with condition type `&syntax` is raised if the keyword appears on the left-hand side of a `set!` expression.

`(make-variable-transformer proc)` procedure

*Proc* should accept one argument, a wrapped syntax object, and return a syntax object.

The `make-variable-transformer` procedure creates a *variable transformer*. A variable transformer is like an ordinary transformer except that, if a keyword associated with a variable transformer appears on the left-hand side of a `set!` expression, an exception is not raised. Instead, *proc* is called with a wrapped syntax object representing the entire `set!` expression as its argument, and its return value replaces the entire `set!` expression.

*Implementation responsibilities:* The implementation must check the restrictions on *proc* only to the extent performed by applying it as described.

## 12.4. Parsing input and producing output

Transformers can destructure their input with `syntax-case` and rebuild their output with `syntax`.

`(syntax-case (expression) (<literal> ...) <clause> ...)`  
syntax

*Syntax:* Each `<literal>` must be an identifier. Each `<clause>` must take one of the following two forms.

`(<pattern> <output expression>)`  
`(<pattern> <fender> <output expression>)`

`<Fender>` and `<output expression>` must be `<expression>`s.

A `<pattern>` is an identifier, constant, or one of the following.

```

⟨pattern⟩ ...
⟨pattern⟩ ⟨pattern⟩ ... . ⟨pattern⟩
⟨pattern⟩ ... ⟨pattern⟩ ⟨ellipsis⟩ ⟨pattern⟩ ...
⟨pattern⟩ ... ⟨pattern⟩ ⟨ellipsis⟩ ⟨pattern⟩ ... . ⟨pattern⟩
#⟨pattern⟩ ...
#⟨pattern⟩ ... ⟨pattern⟩ ⟨ellipsis⟩ ⟨pattern⟩ ...

```

An `⟨ellipsis⟩` is the identifier “...” (three periods).

An identifier appearing within a `⟨pattern⟩` may be an underscore ( `_` ), a literal identifier listed in the list of literals ( `⟨literal⟩ ...` ), or an ellipsis ( `... .` ). All other identifiers appearing within a `⟨pattern⟩` are *pattern variables*. It is a syntax violation if an ellipsis or underscore appears in ( `⟨literal⟩ ...` ).

Pattern variables match arbitrary input subforms and are used to refer to elements of the input. It is a syntax violation if the same pattern variable appears more than once in a `⟨pattern⟩`.

Underscores also match arbitrary input subforms but are not pattern variables and so cannot be used to refer to those elements. Multiple underscores may appear in a `⟨pattern⟩`.

A literal identifier matches an input subform if and only if the input subform is an identifier and either both its occurrence in the input expression and its occurrence in the list of literals have the same lexical binding, or the two identifiers have the same name and both have no lexical binding.

A subpattern followed by an ellipsis can match zero or more elements of the input.

More formally, an input form  $F$  matches a pattern  $P$  if and only if one of the following holds:

- $P$  is an underscore ( `_` ).
- $P$  is a pattern variable.
- $P$  is a literal identifier and  $F$  is an equivalent identifier in the sense of `free-identifier=?` (section 12.5).
- $P$  is of the form  $(P_1 \dots P_n)$  and  $F$  is a list of  $n$  elements that match  $P_1$  through  $P_n$ .
- $P$  is of the form  $(P_1 \dots P_n . P_x)$  and  $F$  is a list or improper list of  $n$  or more elements whose first  $n$  elements match  $P_1$  through  $P_n$  and whose  $n$ th cdr matches  $P_x$ .
- $P$  is of the form  $(P_1 \dots P_k P_e \langle\text{ellipsis}\rangle P_{m+1} \dots P_n)$ , where `⟨ellipsis⟩` is the identifier `...` and  $F$  is a proper list of  $n$  elements whose first  $k$  elements match  $P_1$  through  $P_k$ , whose next  $m - k$  elements each match  $P_e$ , and whose remaining  $n - m$  elements match  $P_{m+1}$  through  $P_n$ .

- $P$  is of the form  $(P_1 \dots P_k P_e \langle\text{ellipsis}\rangle P_{m+1} \dots P_n . P_x)$ , where `⟨ellipsis⟩` is the identifier `...` and  $F$  is a list or improper list of  $n$  elements whose first  $k$  elements match  $P_1$  through  $P_k$ , whose next  $m - k$  elements each match  $P_e$ , whose next  $n - m$  elements match  $P_{m+1}$  through  $P_n$ , and whose  $n$ th and final cdr matches  $P_x$ .
- $P$  is of the form  $\#(P_1 \dots P_n)$  and  $F$  is a vector of  $n$  elements that match  $P_1$  through  $P_n$ .
- $P$  is of the form  $\#(P_1 \dots P_k P_e \langle\text{ellipsis}\rangle P_{m+1} \dots P_n)$ , where `⟨ellipsis⟩` is the identifier `...` and  $F$  is a vector of  $n$  or more elements whose first  $k$  elements match  $P_1$  through  $P_k$ , whose next  $m - k$  elements each match  $P_e$ , and whose remaining  $n - m$  elements match  $P_{m+1}$  through  $P_n$ .
- $P$  is a pattern datum (any nonlist, nonvector, non-symbol datum) and  $F$  is equal to  $P$  in the sense of the `equal?` procedure.

*Semantics:* `syntax-case` first evaluates `⟨expression⟩`. It then attempts to match the `⟨pattern⟩` from the first `⟨clause⟩` against the resulting value, which is unwrapped as necessary to perform the match. If the pattern matches the value and no `⟨fender⟩` is present, `⟨output expression⟩` is evaluated and its value returned as the value of the `syntax-case` expression. If the pattern does not match the value, `syntax-case` tries the second `⟨clause⟩`, then the third, and so on. It is a syntax violation if the value does not match any of the patterns.

If the optional `⟨fender⟩` is present, it serves as an additional constraint on acceptance of a clause. If the `⟨pattern⟩` of a given `⟨clause⟩` matches the input value, the corresponding `⟨fender⟩` is evaluated. If `⟨fender⟩` evaluates to a true value, the clause is accepted; otherwise, the clause is rejected as if the pattern had failed to match the value. Fenders are logically a part of the matching process, i.e., they specify additional matching constraints beyond the basic structure of the input.

Pattern variables contained within a clause’s `⟨pattern⟩` are bound to the corresponding pieces of the input value within the clause’s `⟨fender⟩` (if present) and `⟨output expression⟩`. Pattern variables can be referenced only within `syntax` expressions (see below). Pattern variables occupy the same name space as program variables and keywords.

`(syntax ⟨template⟩)` syntax

*Note:* `#′⟨template⟩` is equivalent to `(syntax ⟨template⟩)`.

A `syntax` expression is similar to a `quote` expression except that (1) the values of pattern variables appearing within

$\langle$ template $\rangle$  are inserted into  $\langle$ template $\rangle$ , (2) contextual information associated both with the input and with the template is retained in the output to support lexical scoping, and (3) the value of a `syntax` expression is a syntax object.

A  $\langle$ template $\rangle$  is a pattern variable, an identifier that is not a pattern variable, a pattern datum, or one of the following.

```
( $\langle$ subtemplate $\rangle$  ...)  
( $\langle$ subtemplate $\rangle$  ... .  $\langle$ template $\rangle$ )  
#( $\langle$ subtemplate $\rangle$  ...)
```

A  $\langle$ subtemplate $\rangle$  is a  $\langle$ template $\rangle$  followed by zero or more ellipses.

The value of a `syntax` form is a copy of  $\langle$ template $\rangle$  in which the pattern variables appearing within the template are replaced with the input subforms to which they are bound. Pattern data and identifiers that are not pattern variables or ellipses are copied directly into the output. A subtemplate followed by an ellipsis expands into zero or more occurrences of the subtemplate. Pattern variables that occur in subpatterns followed by one or more ellipses may occur only in subtemplates that are followed by (at least) as many ellipses. These pattern variables are replaced in the output by the input subforms to which they are bound, distributed as specified. If a pattern variable is followed by more ellipses in the subtemplate than in the associated subpattern, the input form is replicated as necessary. The subtemplate must contain at least one pattern variable from a subpattern followed by an ellipsis, and for at least one such pattern variable, the subtemplate must be followed by exactly as many ellipses as the subpattern in which the pattern variable appears. (Otherwise, the expander would not be able to determine how many times the subform should be repeated in the output.) It is a syntax violation if the constraints of this paragraph are not met.

A template of the form  $\langle$ (ellipsis)  $\langle$ template $\rangle$  $\rangle$  is identical to  $\langle$ template $\rangle$ , except that ellipses within the template have no special meaning. That is, any ellipses contained within  $\langle$ template $\rangle$  are treated as ordinary identifiers. In particular, the template  $\langle$ (... ..) $\rangle$  produces a single ellipsis. This allows macro uses to expand into forms containing ellipses.

The output produced by `syntax` is wrapped or unwrapped according to the following rules.

- the copy of  $\langle$ ( $\langle$ t $\rangle$  .  $\langle$ t $\rangle$ ) $\rangle$  is a pair if  $\langle$ t $\rangle$  or  $\langle$ t $\rangle$  contain any pattern variables,
- the copy of  $\langle$ ( $\langle$ t $\rangle$   $\langle$ ellipsis $\rangle$ ) $\rangle$  is a list if  $\langle$ t $\rangle$  contains any pattern variables,
- the copy of  $\#$ ( $\langle$ t $\rangle$  ...  $\langle$ t $\rangle$ ) is a vector if any of  $\langle$ t $\rangle$ , ...,  $\langle$ t $\rangle$  contain any pattern variables, and
- the copy of any portion of  $\langle$ t $\rangle$  not containing any pattern variables is a wrapped syntax object.

The input subforms inserted in place of the pattern variables are wrapped if and only if the corresponding input subforms are wrapped.

The following definitions of `or` illustrate `syntax-case` and `syntax`. The second is equivalent to the first but uses the `#'` prefix instead of the full `syntax` form.

```
(define-syntax or  
  (lambda (x)  
    (syntax-case x ()  
      [( $\_$ ) (syntax #f)]  
      [( $\_$  e) (syntax e)]  
      [( $\_$  e1 e2 e3 ...)  
       (syntax (let ([t e1])  
                 (if t t (or e2 e3 ...))))]))))
```

```
(define-syntax or  
  (lambda (x)  
    (syntax-case x ()  
      [( $\_$ ) #'#f]  
      [( $\_$  e) #'e]  
      [( $\_$  e1 e2 e3 ...)  
       #'(let ([t e1])  
           (if t t (or e2 e3 ...))))]))
```

The examples below define *identifier macros*, macro uses supporting keyword references that do not necessarily appear in the first position of a list-structured form. The second example uses `make-variable-transformer` to handle the case where the keyword appears on the left-hand side of a `set!` expression.

```
(define p (cons 4 5))  
(define-syntax p.car  
  (lambda (x)  
    (syntax-case x ()  
      [( $\_$  . rest) #'((car p) . rest)]  
      [ $\_$  #'(car p)])))  
p.car            $\implies$  4  
(set! p.car 15)  $\implies$  &syntax exception
```

```
(define p (cons 4 5))  
(define-syntax p.car  
  (make-variable-transformer  
    (lambda (x)  
      (syntax-case x (set!)  
        [(set!  $\_$  e) #'(set-car! p e)]  
        [( $\_$  . rest) #'((car p) . rest)]  
        [ $\_$  #'(car p)]))))  
(set! p.car 15)  
p.car            $\implies$  15  
p                $\implies$  (15 5)
```

## 12.5. Identifier predicates

```
(identifier? obj) procedure  
Returns #t if obj is an identifier, i.e., a syntax object rep-
```

resenting an identifier, and `#f` otherwise.

The `identifier?` procedure is often used within a fender to verify that certain subforms of an input form are identifiers, as in the definition of `rec`, which creates self-contained recursive objects, below.

```
(define-syntax rec
  (lambda (x)
    (syntax-case x ()
      [(_ x e)
       (identifier? #'x)
       #'(letrec ([x e]) x)])))

(map (rec fact
      (lambda (n)
        (if (= n 0)
            1
            (* n (fact (- n 1)))))
      '(1 2 3 4 5))
     => (1 2 6 24 120))

(rec 5 (lambda (x) x))    => &syntax exception
```

The procedures `bound-identifier=?` and `free-identifier=?` each take two identifier arguments and return `#t` if their arguments are equivalent and `#f` otherwise. These predicates are used to compare identifiers according to their *intended use* as free references or bound identifiers in a given context.

`(bound-identifier=? id1 id2)` procedure

*id*<sub>1</sub> and *id*<sub>2</sub> must be identifiers. The procedure `bound-identifier=?` returns `#t` if and only if a binding for one would capture a reference to the other in the output of the transformer, assuming that the reference appears within the scope of the binding. In general, two identifiers are `bound-identifier=?` only if both are present in the original program or both are introduced by the same transformer application (perhaps implicitly—see `datum->syntax`). Operationally, two identifiers are considered equivalent by `bound-identifier=?` if and only if they have the same name and same marks (section 12.1).

The `bound-identifier=?` procedure can be used for detecting duplicate identifiers in a binding construct or for other preprocessing of a binding construct that requires detecting instances of the bound identifiers.

`(free-identifier=? id1 id2)` procedure

*id*<sub>1</sub> and *id*<sub>2</sub> must be identifiers. The `free-identifier=?` procedure returns `#t` if and only if the two identifiers would resolve to the same binding if both were to appear in the output of a transformer outside of any bindings inserted by the transformer. (If neither of two like-named identifiers resolves to a binding, i.e., both are unbound,

they are considered to resolve to the same binding.) Operationally, two identifiers are considered equivalent by `free-identifier=?` if and only the topmost matching substitution for each maps to the same binding (section 12.1) or the identifiers have the same name and no matching substitution.

`syntax-case` and `syntax-rules` use `free-identifier=?` to compare identifiers listed in the literals list against input identifiers.

The following definition of unnamed `let` uses `bound-identifier=?` to detect duplicate identifiers.

```
(define-syntax let
  (lambda (x)
    (define unique-ids?
      (lambda (ls)
        (or (null? ls)
            (and (let notmem?
                   ([x (car ls)] [ls (cdr ls)])
                 (or (null? ls)
                     (and (not (bound-identifier=?
                               x (car ls)))
                           (notmem? x (cdr ls))))))
             (unique-ids? (cdr ls))))))
    (syntax-case x ()
      [(_ ((i v) ...) e1 e2 ...)
       (unique-ids? #'(i ...))
       #'((lambda (i ...) e1 e2 ...) v ...)])))
```

The argument  `#'(i ...)`  to `unique-ids?` is guaranteed to be a list by the rules given in the description of `syntax` above.

With this definition of `let`:

```
(let ([a 3] [a 4]) (+ a a))
     => &syntax exception
```

However,

```
(let-syntax
  ([dolet (lambda (x)
            (syntax-case x ()
              [(_ b)
               #'(let ([a 3] [b 4]) (+ a b))])])])
  (dolet a))
     => 7
```

since the identifier `a` introduced by `dolet` and the identifier `a` extracted from the input form are not `bound-identifier=?`.

The following definition of `case` is equivalent to the one in section 12.4. Rather than including `else` in the literals list as before, this version explicitly tests for `else` using `free-identifier=?`.

```
(define-syntax case
  (lambda (x)
    (syntax-case x ()
```

```

[(_ e0 [(k ...) e1 e2 ...] ...
  [else-key else-e1 else-e2 ...])
 (and (identifier? #'else-key)
  (free-identifier=? #'else-key #'else))
 #'(let ([t e0])
  (cond
   [(memv t '(k ...)) e1 e2 ...]
   ...
   [else else-e1 else-e2 ...]))
[(_ e0 [(ka ...) e1a e2a ...]
  [(kb ...) e1b e2b ...] ...)
 #'(let ([t e0])
  (cond
   [(memv t '(ka ...)) e1a e2a ...]
   [(memv t '(kb ...)) e1b e2b ...]
   ...))))

```

With either definition of `case`, `else` is not recognized as an auxiliary keyword if an enclosing lexical binding for `else` exists. For example,

```

(let ([else #f])
  (case 0 [else (write "oops")]))
⇒ &syntax exception

```

since `else` is bound lexically and is therefore not the same `else` that appears in the definition of `case`.

## 12.6. Syntax-object and datum conversions

(`syntax->datum` *syntax-object*) procedure

The procedure `syntax->datum` strips all syntactic information from a syntax object and returns the corresponding Scheme datum.

Identifiers stripped in this manner are converted to their symbolic names, which can then be compared with `eq?`. Thus, a predicate `symbolic-identifier=?` might be defined as follows.

```

(define symbolic-identifier=?
  (lambda (x y)
    (eq? (syntax->datum x)
         (syntax->datum y))))

```

(`datum->syntax` *template-id datum*) procedure

*Template-id* must be a template identifier and *datum* should be a datum value. The `datum->syntax` procedure returns a syntax object representation of *datum* that contains the same contextual information as *template-id*, with the effect that the syntax object behaves as if it were introduced into the code when *template-id* was introduced.

The `datum->syntax` procedure allows a transformer to “bend” lexical scoping rules by creating *implicit identifiers* that behave as if they were present in the input form,

thus permitting the definition of macros that introduce visible bindings for or references to identifiers that do not appear explicitly in the input form. For example, the following defines a loop expression that uses this controlled form of identifier capture to bind the variable `break` to an escape procedure within the loop body. (The derived `with-syntax` form is like `let` but binds pattern variables—see section 12.8.)

```

(define-syntax loop
  (lambda (x)
    (syntax-case x ()
      [(k e ...)
       (with-syntax
        ([break (datum->syntax #'k 'break)])
        #'(call-with-current-continuation
            (lambda (break)
              (let f () e ... (f)))))))]))

```

```

(let ((n 3) (ls '()))
  (loop
   (if (= n 0) (break ls))
   (set! ls (cons 'a ls))
   (set! n (- n 1))))
⇒ (a a a)

```

Were `loop` to be defined as

```

(define-syntax loop
  (lambda (x)
    (syntax-case x ()
      [( _ e ...)
       #'(call-with-current-continuation
            (lambda (break)
              (let f () e ... (f)))))]))

```

the variable `break` would not be visible in `e ...`.

The datum argument *datum* may also represent an arbitrary Scheme form, as demonstrated by the following definition of `include`.

```

(define-syntax include
  (lambda (x)
    (define read-file
      (lambda (fn k)
        (let ([p (open-file-input-port fn)])
          (let f ([x (get-datum p)])
            (if (eof-object? x)
                (begin (close-port p) '())
                (cons (datum->syntax k x)
                      (f (get-datum p)))))))
      (syntax-case x ()
        [(k filename)
         (let ([fn (syntax->datum #'filename)])
           (with-syntax ([exp ...]
                        (read-file fn #'k))]
             #'(begin exp ...))))))

```

(`include "filename"`) expands into a `begin` expression containing the forms found in the file named by “filename”. For example, if the file `flib.ss` contains

(define f (lambda (x) (g (\* x x)))), and the file `glib.ss` contains (define g (lambda (x) (+ x x))), the expression

```
(let ()
  (include "flib.ss")
  (include "glib.ss")
  (f 5))
```

evaluates to 50.

The definition of `include` uses `datum->syntax` to convert the objects read from the file into syntax objects in the proper lexical context, so that identifier references and definitions within those expressions are scoped where the `include` form appears.

Using `datum->syntax`, it is even possible to break hygiene entirely and write macros in the style of old Lisp macros. The `lisp-transformer` procedure defined below creates a transformer that converts its input into a datum, calls the programmer's procedure on this datum, and converts the result back into a syntax object that is scoped at top level (or, more accurately, wherever `lisp-transformer` is defined).

```
(define lisp-transformer
  (lambda (p)
    (lambda (x)
      (datum->syntax #'lisp-transformer
        (p (syntax->datum x))))))
```

## 12.7. Generating lists of temporaries

Transformers can introduce a fixed number of identifiers into their output simply by naming each identifier. In some cases, however, the number of identifiers to be introduced depends upon some characteristic of the input expression. A straightforward definition of `letrec`, for example, requires as many temporary identifiers as there are binding pairs in the input expression. The procedure `generate-temporaries` is used to construct lists of temporary identifiers.

(`generate-temporaries l`) procedure

`L` must be a list or syntax object representing a list-structured form; its contents are not important. The number of temporaries generated is the number of elements in `l`. Each temporary is guaranteed to be unique, i.e., different from all other identifiers.

A definition of `letrec` equivalent to the one using `syntax-rules` given in report appendix B is shown below.

```
(define-syntax letrec
  (lambda (x)
    (syntax-case x ()
      ((_ ((i e) ...) b1 b2 ...)
```

```
(with-syntax
  ((t ...) (generate-temporaries #'(i ...))))
  #'(let ((i <undefined>) ...)
      (let ((t e) ...)
        (set! i t) ...
        (let () b1 b2 ...))))))
```

This version uses `generate-temporaries` instead of recursively defined helper to generate the necessary temporaries.

## 12.8. Derived forms and procedures

The forms and procedures described in this section are *derived*, i.e., they can be defined in terms of the forms and procedures described in earlier sections of this document.

```
(with-syntax ((<pattern> <expression>) ...) <body>)
                                                    syntax
```

The derived `with-syntax` form is used to bind pattern variables, just as `let` is used to bind variables. This allows a transformer to construct its output in separate pieces, then put the pieces together.

Each `<pattern>` is identical in form to a `syntax-case` pattern. The value of each `<expression>` is computed and de-structured according to the corresponding `<pattern>`, and pattern variables within the `<pattern>` are bound as with `syntax-case` to the corresponding portions of the value within `<body>`.

The `with-syntax` form may be defined in terms of `syntax-case` as follows.

```
(define-syntax with-syntax
  (lambda (x)
    (syntax-case x ()
      ((_ ((p e0) ...) e1 e2 ...)
        (syntax (syntax-case (list e0 ...) ()
                          ((p ...) (let () e1 e2 ...)))))))
```

The following definition of `cond` demonstrates the use of `with-syntax` to support transformers that employ recursion internally to construct their output. It handles all `cond` clause variations and takes care to produce one-armed `if` expressions where appropriate.

```
(define-syntax cond
  (lambda (x)
    (syntax-case x ()
      [( _ c1 c2 ...)
       (let f ([c1 #'c1] [c2* #'(c2 ...)])]
         (syntax-case c2* ()
           [()
            (syntax-case c1 (else =>)
              [(else e1 e2 ...) #'(begin e1 e2 ...)]
              [(e0) #'e0])
```

```

[(e0 => e1)
 #'(let ([t e0]) (if t (e1 t))))]
[(e0 e1 e2 ...)
 #'(if e0 (begin e1 e2 ...)))]
[(c2 c3 ...)
 (with-syntax ([rest (f #'c2 #'(c3 ...))])
 (syntax-case c1 (=>)
  [(e0) #'(let ([t e0]) (if t t rest))]
  [(e0 => e1)
   #'(let ([t e0]) (if t (e1 t) rest))]
  [(e0 e1 e2 ...)
   #'(if e0
        (begin e1 e2 ...)
        rest)))])))]))

```

(quasisyntax <template>)

syntax

The `quasisyntax` form is similar to `syntax`, but it allows parts of the quoted text to be evaluated, in a manner similar to the operation of `quasiquote` (report section 9.18).

Within a `quasisyntax` *template*, subforms of `unsyntax` and `unsyntax-splicing` forms are evaluated, and everything else is treated as ordinary template material, as with `syntax`. The value of each `unsyntax` subform is inserted into the output in place of the `unsyntax` form, while the value of each `unsyntax-splicing` subform is spliced into the surrounding list or vector structure. Uses of `unsyntax` and `unsyntax-splicing` are valid only within `quasisyntax` expressions.

A `quasisyntax` expression may be nested, with each `quasisyntax` introducing a new level of syntax quotation and each `unsyntax` or `unsyntax-splicing` taking away a level of quotation. An expression nested within *n* `quasisyntax` expressions must be within *n* `unsyntax` or `unsyntax-splicing` expressions to be evaluated.

As noted in report section 3.3.5, `#`<template>` is equivalent to `(quasisyntax <template>)`, `#,<template>` is equivalent to `(unsyntax <template>)`, and `#,@<template>` is equivalent to `(unsyntax-splicing <template>)`.

The `quasisyntax` keyword can be used in place of `with-syntax` in many cases. For example, the definition of case shown under the description of `with-syntax` above can be rewritten using `quasisyntax` as follows.

```

(define-syntax case
  (lambda (x)
    (syntax-case x ()
      [(e c1 c2 ...)
       #'(let ([t e])
           #,(let f ([c1 #'c1] [cmore #'(c2 ...)])
              (if (null? cmore)
                  (syntax-case c1 (else)
                    [(else e1 e2 ...)
                     #'(begin e1 e2 ...)]
                    [[(k ...) e1 e2 ...]

```

```

#' (if (memv t '(k ...))
        (begin e1 e2 ...)))]
(syntax-case c1 ()
  [[(k ...) e1 e2 ...]
   #'(if (memv t '(k ...))
         (begin e1 e2 ...)
         #,(f (car cmore)
              (cdr cmore)))])))])))]))

```

Uses of `unsyntax` and `unsyntax-splicing` with zero or more than one subform are valid only in splicing (list or vector) contexts. `(unsyntax template ...)` is equivalent to `(unsyntax template) ...`, and `(unsyntax-splicing template ...)` is equivalent to `(unsyntax-splicing template) ...`. These forms are primarily useful as intermediate forms in the output of the `quasisyntax` expander.

*Note:* Uses of `unsyntax` and `unsyntax-splicing` with zero or more than one subform enable certain idioms [2], such as `#,@#,@`, which has the effect of a doubly indirect splicing when used within a doubly nested and doubly evaluated `quasisyntax` expression, as with the nested `quasiquote` examples shown in section 9.18.

*Note:* Any `syntax-rules` form can be expressed with `syntax-case` by making the `lambda` expression and `syntax` expressions explicit, and `syntax-rules` may be defined in terms of `syntax-case` as follows.

```

(define-syntax syntax-rules
  (lambda (x)
    (syntax-case x ()
      [(k ...) [(p) f ... t] ...]
      #'(lambda (x)
          (syntax-case x (k ...)
            [(p) f ... #'t] ...))))))

```

A more robust implementation would verify that the literals `<literal> ...` are all identifiers, that the first position of each pattern is an identifier, and that at most one fender is present in each clause.

*Note:* The `identifier-syntax` form of the base library (see report section 9.20) may be defined in terms of `syntax-case`, `syntax`, and `make-variable-transformer` as follows.

```

(define-syntax identifier-syntax
  (syntax-rules (set!)
    [(e)
     (lambda (x)
       (syntax-case x ()
         [id (identifier? #'id) #'e]
         [(x (... ...)) #'(e x (... ...))])])
     [(id exp1) ((set! var val) exp2)
      (and (identifier? #'id) (identifier? #'var))
      (make-variable-transformer
       (lambda (x)
         (syntax-case x (set!)
           [(set! var val) #'exp2]
           [(id x (... ...)) #'(exp1 x (... ...))]
           [id (identifier? #'id) #'exp1])])])])

```

## 12.9. Syntax violations

(`syntax-violation who message form`) procedure  
 (`syntax-violation who message form subform`) procedure

*Who* must be `#f` or a string or a symbol. *Message* must be a string. *Form* must be a syntax object or a datum value. *Subform* must be a syntax object or a datum value. The `syntax-violation` procedure raises an exception, reporting a syntax violation. The *who* argument should describe the macro transformer that detected the exception. The *message* argument should describe the violation. The *form* argument is the erroneous source syntax object or a datum value representing a form. The optional *subform* argument is a syntax object or datum value representing a form that more precisely locates the violation.

If *who* is `#f`, `syntax-violation` attempts to infer an appropriate value for the condition object (see below) as follows: When *form* is either an identifier or a list-structured syntax object containing an identifier as its first element, then the inferred value is the identifier's symbol. Otherwise, no value for *who* is provided as part of the condition object.

The condition object provided with the exception (see chapter 7) has the following condition types:

- If *who* is not `#f` or can be inferred, the condition has condition type `&who`, with *who* as the value of the `who` field. In that case, *who* should identify the procedure or entity that detected the exception. If it is `#f`, the condition does not have condition type `&who`.
- The condition has condition type `&message`, with *message* as the value of the `message` field.
- The condition has condition type `&syntax` with *form* as the value of the `form` field, and *subform* as the value of the `subform` field. If *subform* is not provided, the value of the `subform` field is `#f`.

## 13. Hashtables

The (`rnrs hashtables` (6)) library provides a set of operations on hashtables. A *hashtable* is a data structure that associates keys with values. Any object can be used as a key, provided a *hash function* and a suitable *equivalence function* is available. A hash function is a procedure that maps keys to exact integer objects. It is the programmer's responsibility to ensure that the hash function is compatible with the equivalence function, which is a procedure that accepts two keys and returns true if they are equivalent and `#f` otherwise. Standard hashtables for arbitrary objects based on the `eq?` and `equiv?` predicates (see report

section 9.6) are provided. Also, hash functions for arbitrary objects, strings, and symbols are provided.

This section uses the *hashtable* parameter name for arguments that must be hashtables, and the *key* parameter name for arguments that must be hashtable keys.

### 13.1. Constructors

(`make-eq-hashtable`) procedure  
 (`make-eq-hashtable k`) procedure

Returns a newly allocated mutable hashtable that accepts arbitrary objects as keys, and compares those keys with `eq?`. If an argument is given, the initial capacity of the hashtable is set to approximately *k* elements.

(`make-eqv-hashtable`) procedure  
 (`make-eqv-hashtable k`) procedure

Returns a newly allocated mutable hashtable that accepts arbitrary objects as keys, and compares those keys with `equiv?`. If an argument is given, the initial capacity of the hashtable is set to approximately *k* elements.

(`make-hashtable hash-function equiv`) procedure  
 (`make-hashtable hash-function equiv k`) procedure

*Hash-function* and *equiv* must be procedures. *Hash-function* should accept a key as an argument and should return a non-negative exact integer object. *Equiv* should accept two keys as arguments and return a single value. Neither procedure should mutate the hashtable returned by `make-hashtable`. The `make-hashtable` procedure returns a newly allocated mutable hashtable using *hash-function* as the hash function and *equiv* as the equivalence function used to compare keys. If a third argument is given, the initial capacity of the hashtable is set to approximately *k* elements.

Both *hash-function* and *equiv* should behave like pure functions on the domain of keys. For example, the `string-hash` and `string=?` procedures are permissible only if all keys are strings and the contents of those strings are never changed so long as any of them continues to serve as a key in the hashtable. Furthermore, any pair of keys for which *equiv* returns true should be hashed to the same exact integer objects by *hash-function*.

*Implementation responsibilities:* The implementation must check the restrictions on *hash-function* and *equiv* to the extent performed by applying them as described.

*Note:* Hashtables are allowed to cache the results of calling the hash function and equivalence function, so programs cannot rely on the hash function being called for every lookup or update. Furthermore any hashtable operation may call the hash function more than once.

## 13.2. Procedures

`(hashtable? hashtable)` procedure  
Returns `#t` if *hashtable* is a hashtable, `#f` otherwise.

`(hashtable-size hashtable)` procedure  
Returns the number of keys contained in *hashtable* as an exact integer object.

`(hashtable-ref hashtable key default)` procedure  
Returns the value in *hashtable* associated with *key*. If *hashtable* does not contain an association for *key*, *default* is returned.

`(hashtable-set! hashtable key obj)` procedure  
Changes *hashtable* to associate *key* with *obj*, adding a new association or replacing any existing association for *key*, and returns unspecified values.

`(hashtable-delete! hashtable key)` procedure  
Removes any association for *key* within *hashtable* and returns unspecified values.

`(hashtable-contains? hashtable key)` procedure  
Returns `#t` if *hashtable* contains an association for *key*, `#f` otherwise.

`(hashtable-update! hashtable key proc default)` procedure  
*Proc* should accept one argument, should return a single value, and should not mutate *hashtable*. The `hashtable-update!` procedure applies *proc* to the value in *hashtable* associated with *key*, or to *default* if *hashtable* does not contain an association for *key*. The *hashtable* is then changed to associate *key* with the value returned by *proc*.

The behavior of `hashtable-update!` is equivalent to the following code, but may be implemented more efficiently in cases where the implementation can avoid multiple lookups of the same key:

```
(hashtable-set!
 hashtable key
 (proc (hashtable-ref
        hashtable key default)))
```

`(hashtable-copy hashtable)` procedure  
`(hashtable-copy hashtable mutable)` procedure

Returns a copy of *hashtable*. If the *mutable* argument is provided and is true, the returned hashtable is mutable; otherwise it is immutable.

`(hashtable-clear! hashtable)` procedure  
`(hashtable-clear! hashtable k)` procedure

Removes all associations from *hashtable* and returns unspecified values.

If a second argument is given, the current capacity of the hashtable is reset to approximately *k* elements.

`(hashtable-keys hashtable)` procedure  
Returns a vector of all keys in *hashtable*. The order of the vector is unspecified.

`(hashtable-entries hashtable)` procedure  
Returns two values, a vector of the keys in *hashtable*, and a vector of the corresponding values.

```
(let ((h (make-eqv-hashtable)))
 (hashtable-set! h 1 'one)
 (hashtable-set! h 2 'two)
 (hashtable-set! h 3 'three)
 (hashtable-entries h))
 ⇒ #(1 2 3), #(one two three)
 ; two return values
```

## 13.3. Inspection

`(hashtable-equivalence-function hashtable)` procedure

Returns the equivalence function used by *hashtable* to compare keys. For hashtables created with `make-eq-hashtable` and `make-eqv-hashtable`, returns `eq?` and `eqv?` respectively.

`(hashtable-hash-function hashtable)` procedure  
Returns the hash function used by *hashtable*. For hashtables created by `make-eq-hashtable` or `make-eqv-hashtable`, `#f` is returned.

`(hashtable-mutable? hashtable)` procedure  
Returns `#t` if *hashtable* is mutable, otherwise `#f`.

### 13.4. Hash functions

The `equal-hash`, `string-hash`, and `string-ci-hash` procedures of this section are acceptable as the hash functions of a hashtable only if the keys on which they are called are not mutated while they remain in use as keys in the hashtable.

`(equal-hash obj)` procedure

Returns an integer hash value for *obj*, based on its structure and current contents. This hash function is suitable for use with `equal?` as an equivalence function.

*Note:* Like `equal?`, the `equal-hash` procedure must always terminate, even if its arguments contain cycles.

`(string-hash string)` procedure

Returns an integer hash value for *string*, based on its current contents. This hash function is suitable for use with `string=?` as an equivalence function.

`(string-ci-hash string)` procedure

Returns an integer hash value for *string* based on its current contents, ignoring case. This hash function is suitable for use with `string-ci=?` as an equivalence function.

`(symbol-hash symbol)` procedure

Returns an integer hash value for *symbol*.

## 14. Enumerations

This chapter describes the `(rnrs enum (6))` library for dealing with enumerated values and sets of enumerated values. Enumerated values are represented by ordinary symbols, while finite sets of enumerated values form a separate type, known as the *enumeration sets*. The enumeration sets are further partitioned into sets that share the same *universe* and *enumeration type*. These universes and enumeration types are created by the `make-enumeration` procedure. Each call to that procedure creates a new enumeration type.

This library interprets each enumeration set with respect to its specific universe of symbols and enumeration type. This facilitates efficient implementation of enumeration sets and enables the complement operation.

In the descriptions of the following procedures, *enum-set* ranges over the enumeration sets, which are defined as the subsets of the universes that can be defined using `make-enumeration`.

`(make-enumeration symbol-list)` procedure

*Symbol-list* must be a list of symbols. The `make-enumeration` procedure creates a new enumeration type whose universe consists of those symbols (in canonical order of their first appearance in the list) and returns that universe as an enumeration set whose universe is itself and whose enumeration type is the newly created enumeration type.

`(enum-set-universe enum-set)` procedure

Returns the set of all symbols that comprise the universe of its argument, as an enumeration set.

`(enum-set-indexer enum-set)` procedure

Returns a unary procedure that, given a symbol that is in the universe of *enum-set*, returns its 0-origin index within the canonical ordering of the symbols in the universe; given a value not in the universe, the unary procedure returns `#f`.

```
(let* ((e (make-enumeration '(red green blue)))
      (i (enum-set-indexer e)))
      (list (i 'red) (i 'green) (i 'blue) (i 'yellow)))
      => (0 1 2 #f))
```

The `enum-set-indexer` procedure could be defined as follows using the `memq` procedure from the `(rnrs lists (6))` library:

```
(define (enum-set-indexer set)
  (let* ((symbols (enum-set->list
                    (enum-set-universe set)))
        (cardinality (length symbols)))
    (lambda (x)
      (let ((probe (memq x symbols)))
        (if probe
            (- cardinality (length probe))
            #f))))))
```

`(enum-set-constructor enum-set)` procedure

Returns a unary procedure that, given a list of symbols that belong to the universe of *enum-set*, returns a subset of that universe that contains exactly the symbols in the list. The values in the list must all belong to the universe.

`(enum-set->list enum-set)` procedure

Returns a list of the symbols that belong to its argument, in the canonical order of the universe of *enum-set*.

```
(let* ((e (make-enumeration '(red green blue)))
      (c (enum-set-constructor e)))
      (enum-set->list (c '(blue red))))
      => (red blue))
```

(enum-set-member? *symbol enum-set*) procedure  
 (enum-set-subset? *enum-set<sub>1</sub> enum-set<sub>2</sub>*) procedure  
 (enum-set=? *enum-set<sub>1</sub> enum-set<sub>2</sub>*) procedure

The `enum-set-member?` procedure returns `#t` if its first argument is an element of its second argument, `#f` otherwise.

The `enum-set-subset?` procedure returns `#t` if the universe of *enum-set<sub>1</sub>* is a subset of the universe of *enum-set<sub>2</sub>* (considered as sets of symbols) and every element of *enum-set<sub>1</sub>* is a member of *enum-set<sub>2</sub>*. It returns `#f` otherwise.

The `enum-set=?` procedure returns `#t` if *enum-set<sub>1</sub>* is a subset of *enum-set<sub>2</sub>* and vice versa, as determined by the `enum-set-subset?` procedure. This implies that the universes of the two sets are equal as sets of symbols, but does not imply that they are equal as enumeration types. Otherwise, `#f` is returned.

```
(let* ((e (make-enumeration '(red green blue)))
      (c (enum-set-creator e)))
  (list
   (enum-set-member? 'blue (c '(red blue)))
   (enum-set-member? 'green (c '(red blue)))
   (enum-set-subset? (c '(red blue)) e)
   (enum-set-subset? (c '(red blue)) (c '(blue red)))
   (enum-set-subset? (c '(red blue)) (c '(red)))
   (enum-set=? (c '(red blue)) (c '(blue red))))
  => (#t #f #t #t #f #t)
```

(enum-set-union *enum-set<sub>1</sub> enum-set<sub>2</sub>*) procedure  
 (enum-set-intersection *enum-set<sub>1</sub> enum-set<sub>2</sub>*) procedure  
 (enum-set-difference *enum-set<sub>1</sub> enum-set<sub>2</sub>*) procedure

*Enum-set<sub>1</sub>* and *enum-set<sub>2</sub>* must be enumeration sets that have the same enumeration type. If their enumeration types differ, a `&assertion` violation is raised.

The `enum-set-union` procedure returns the union of *enum-set<sub>1</sub>* and *enum-set<sub>2</sub>*. The `enum-set-intersection` procedure returns the intersection of *enum-set<sub>1</sub>* and *enum-set<sub>2</sub>*. The `enum-set-difference` procedure returns the difference of *enum-set<sub>1</sub>* and *enum-set<sub>2</sub>*.

```
(let* ((e (make-enumeration '(red green blue)))
      (c (enum-set-creator e)))
  (list (enum-set->list
        (enum-set-union (c '(blue)) (c '(red))))
        (enum-set->list
        (enum-set-intersection (c '(red green))
                              (c '(red blue))))
        (enum-set->list
        (enum-set-difference (c '(red green))
                            (c '(red blue))))))
  => ((red blue) (red) (green))
```

(enum-set-complement *enum-set*) procedure  
 Returns *enum-set*'s complement with respect to its universe.

```
(let* ((e (make-enumeration '(red green blue)))
      (c (enum-set-creator e)))
  (enum-set->list
   (enum-set-complement (c '(red))))
  => (green blue)
```

(enum-set-projection *enum-set<sub>1</sub> enum-set<sub>2</sub>*) procedure

Projects *enum-set<sub>1</sub>* into the universe of *enum-set<sub>2</sub>*, dropping any elements of *enum-set<sub>1</sub>* that do not belong to the universe of *enum-set<sub>2</sub>*. (If *enum-set<sub>1</sub>* is a subset of the universe of its second, no elements are dropped, and the injection is returned.)

```
(let ((e1 (make-enumeration
          '(red green blue black)))
      (e2 (make-enumeration
          '(red black white))))
  (enum-set->list
   (enum-set-projection e1 e2)))
  => (red black)
```

(define-enumeration <type-name> syntax  
 (<symbol> ...) <constructor-syntax>)

The `define-enumeration` form defines an enumeration type and provides two macros for constructing its members and sets of its members.

A `define-enumeration` form is a definition and can appear anywhere any other <definition> can appear.

<Type-name> is an identifier that is bound as a syntactic keyword; <symbol> ... are the symbols that comprise the universe of the enumeration (in order).

<(type-name) <symbol>> checks at macro-expansion time whether <symbol> is in the universe associated with <type-name>. If it is, <(type-name) <symbol>> is equivalent to <symbol>. It is a syntax violation if it is not.

<Constructor-syntax> is an identifier that is bound to a macro that, given any finite sequence of the symbols in the universe, possibly with duplicates, expands into an expression that evaluates to the enumeration set of those symbols.

<<constructor-syntax> <symbol> ...> checks at macro-expansion time whether every <symbol> ... is in the universe associated with <type-name>. It is a syntax violation if one or more is not. Otherwise

```
<<constructor-syntax> <symbol> ...>
```

is equivalent to

```
((enum-set-constructor ((constructor-syntax))
  '(<symbol> ...)).
```

Example:

```
(define-enumeration color
  (black white purple maroon)
  color-set)

(color black)           => black
(color purple)         => &syntax exception
(enum-set->list (color-set)) => ()
(enum-set->list
  (color-set maroon white)) => (white maroon)
```

## 15. Composite library

The `(rnrs (6))` library is a composite of most of the libraries described in this report. The only exceptions are:

- `(rnrs eval (6))` (chapter 16)
- `(rnrs mutable-pairs (6))` (chapter 17)
- `(rnrs mutable-strings (6))` (chapter 18)
- `(rnrs r5rs (6))` (chapter 19)

The library exports all procedures and syntactic forms provided by the component libraries.

All of the bindings exported by `(rnrs (6))` are exported for both `run` and `expand`; see report section 6.2.

## 16. eval

The `(rnrs eval (6))` library allows a program to create Scheme expressions as data at run time and evaluate them.

```
(eval expression environment-specifier) procedure
```

Evaluates *expression* in the specified environment and returns its value. *Expression* must be a valid Scheme expression represented as a datum value, and *environment-specifier* must be a *library specifier*, which can be created using the `environment` procedure described below.

If the first argument to `eval` is determined not to be a syntactically correct expression, then `eval` must raise an exception with condition type `&syntax`. Specifically, if the first argument to `eval` is a definition or a splicing `begin` form containing a definition, it must raise an exception with condition type `&syntax`.

```
(environment import-spec ...) procedure
```

*Import-spec* must be a datum representing an `<import spec>` (see report section 6.1). The `environment` procedure returns an environment corresponding to *import-spec*.

The bindings of the environment represented by the specifier are immutable: If `eval` is applied to an expression that is determined to contain an assignment to one of the variables of the environment, then `eval` must raise an exception with a condition type `&assertion`.

```
(library (foo)
  (export)
  (import (rnrs (6))))
(write
  (eval '(let ((x 3)) x)
    (environment '(rnrs (6))))))
  writes 3
```

```
(library (foo)
  (export)
  (import (rnrs (6))))
(write
  (eval
    '(eval:car (eval:cons 2 4))
    (environment
      '(prefix (only (rnrs (6)) car cdr cons null?)
        eval:))))))
  writes 2
```

## 17. Mutable pairs

The procedures provided by the `(rnrs mutable-pairs (6))` library allow new values to be assigned to the `car` and `cdr` fields of previously allocated pairs.

```
(set-car! pair obj) procedure
```

Stores *obj* in the `car` field of *pair*. The `set-car!` procedure returns unspecified values.

```
(define (f) (list 'not-a-constant-list))
(define (g) '(constant-list))
(set-car! (f) 3)           => unspecified
(set-car! (g) 3)           => unspecified
; should raise &assertion exception
```

If an immutable pair is passed to `set-car!`, an exception with condition type `&assertion` should be raised.

```
(set-cdr! pair obj) procedure
```

Stores *obj* in the `cdr` field of *pair*. The `set-cdr!` procedure returns unspecified values.

If an immutable pair is passed to `set-cdr!`, an exception with condition type `&assertion` should be raised.

```
(let ((x (list 'a 'b 'c 'a))
      (y (list 'a 'b 'c 'a 'b 'c 'a)))
  (set-cdr! (list-tail x 2) x)
  (set-cdr! (list-tail y 5) y)
  (list
   (equal? x x)
   (equal? x y)
   (equal? (list x y 'a) (list y x 'b))))
⇒ (#t #t #f)
```

## 18. Mutable strings

The `string-set!` procedure provided by the `(rnrs mutable-strings (6))` library allows mutating the characters of a string in-place.

```
(string-set! string k char) procedure
```

$K$  must be a valid index of *string*. The `string-set!` procedure stores *char* in element  $k$  of *string* and returns unspecified values.

Passing an immutable string to `string-set!` should cause an exception with condition type `&assertion` to be raised.

```
(define (f) (make-string 3 #\*))
(define (g) "****")
(string-set! (f) 0 #\?) ⇒ unspecified
(string-set! (g) 0 #\?) ⇒ unspecified
; should raise &assertion exception
(string-set! (symbol->string 'immutable)
 0
#\?) ⇒ unspecified
; should raise &assertion exception
```

*Note:* Implementors are encouraged to make `string-set!` run in constant time.

```
(string-fill! string char) procedure
```

Stores *char* in every element of the given *string* and returns unspecified values.

## 19. R<sup>5</sup>RS compatibility

The features described in this chapter are exported from the `(rnrs r5rs (6))` library and provide some functionality of the preceding revision of this report [6] that was omitted from the main part of the current report.

```
(exact->inexact z) procedure
(inexact->exact z) procedure
```

These are the same as the `inexact` and `exact` procedures; see report section 9.8.4.

```
(quotient n1 n2) procedure
(remainder n1 n2) procedure
(modulo n1 n2) procedure
```

These procedures implement number-theoretic (integer) division.  $N_2$  must be non-zero. All three procedures return integer objects. If  $n_1/n_2$  is an integer object:

```
(quotient n1 n2) ⇒ n1/n2
(remainder n1 n2) ⇒ 0
(modulo n1 n2) ⇒ 0
```

If  $n_1/n_2$  is not an integer object:

```
(quotient n1 n2) ⇒ nq
(remainder n1 n2) ⇒ nr
(modulo n1 n2) ⇒ nm
```

where  $n_q$  is  $n_1/n_2$  rounded towards zero,  $0 < |n_r| < |n_2|$ ,  $0 < |n_m| < |n_2|$ ,  $n_r$  and  $n_m$  differ from  $n_1$  by a multiple of  $n_2$ ,  $n_r$  has the same sign as  $n_1$ , and  $n_m$  has the same sign as  $n_2$ .

Consequently, for integer objects  $n_1$  and  $n_2$  with  $n_2$  not equal to 0,

```
(= n1 (+ (* n2 (quotient n1 n2))
          (remainder n1 n2)))
⇒ #t
```

provided all number object involved in that computation are exact.

```
(modulo 13 4) ⇒ 1
(remainder 13 4) ⇒ 1

(modulo -13 4) ⇒ 3
(remainder -13 4) ⇒ -1

(modulo 13 -4) ⇒ -3
(remainder 13 -4) ⇒ 1

(modulo -13 -4) ⇒ -1
(remainder -13 -4) ⇒ -1

(remainder -13 -4.0) ⇒ -1.0 ; inexact
```

*Note:* These procedures could be defined in terms of `div` and `mod` (see report section 9.8.4) as follows (without checking of the argument types):

```
(define (sign n)
  (cond
   ((negative? n) -1)
   ((positive? n) 1)
   (else 0)))

(define (quotient n1 n2)
  (* (sign n1) (sign n2) (div (abs n1) (abs n2))))

(define (remainder n1 n2)
  (* (sign n1) (mod (abs n1) (abs n2))))
```

```
(define (modulo n1 n2)
  (* (sign n2) (mod (* (sign n2) n1) (abs n2))))
```

```
(delay <expression>)          syntax
```

The `delay` construct is used together with the procedure `force` to implement *lazy evaluation* or *call by need*. `(delay <expression>)` returns an object called a *promise* which at some point in the future may be asked (by the `force` procedure) to evaluate `<expression>`, and deliver the resulting value. The effect of `<expression>` returning multiple values is unspecified.

```
(force promise)              procedure
```

*Promise* must be a promise.

Forces the value of *promise*. If no value has been computed for the promise, then a value is computed and returned. The value of the promise is cached (or “memoized”) so that if it is forced a second time, the previously computed value is returned.

```
(force (delay (+ 1 2)))      ⇒ 3
(let ((p (delay (+ 1 2))))
  (list (force p) (force p)))
                               ⇒ (3 3)
```

```
(define a-stream
  (letrec ((next
            (lambda (n)
              (cons n (delay (next (+ n 1)))))))
    (next 0)))
(define head car)
(define tail
  (lambda (stream) (force (cdr stream))))
```

```
(head (tail (tail a-stream)))
                               ⇒ 2
```

Promises are mainly intended for programs written in functional style. The following examples should not be considered to illustrate good programming style, but they illustrate the property that only one value is computed for a promise, no matter how many times it is forced.

```
(define count 0)
(define p
  (delay (begin (set! count (+ count 1))
                (if (> count x)
                    count
                    (force p)))))
(define x 5)
p                               ⇒ a promise
(force p)                       ⇒ 6
p                               ⇒ a promise, still
(begin (set! x 10)
  (force p))                    ⇒ 6
```

Here is a possible implementation of `delay` and `force`. Promises are implemented here as procedures of no arguments, and `force` simply calls its argument:

```
(define force
  (lambda (object)
    (object)))
```

The expression

```
(delay <expression>)
```

has the same meaning as the procedure call

```
(make-promise (lambda () <expression>))
```

as follows

```
(define-syntax delay
  (syntax-rules ()
    ((delay expression)
     (make-promise (lambda () expression))))),
```

where `make-promise` is defined as follows:

```
(define make-promise
  (lambda (proc)
    (let ((result-ready? #f)
          (result #f))
      (lambda ()
        (if result-ready?
            result
            (let ((x (proc)))
              (if result-ready?
                  result
                  (begin (set! result-ready? #t)
                         (set! result x)
                         result))))))))))
```

```
(null-environment n)          procedure
```

*N* must be the exact integer object 5. The `null-environment` procedure returns an environment specifier suitable for use with `eval` (see chapter 16) representing an environment that is empty except for the (syntactic) bindings for all keywords described in the previous revision of this report [6].

```
(scheme-report-environment n) procedure
```

*N* must be the exact integer object 5. The `scheme-report-environment` procedure returns an environment specifier for an environment that is empty except for the bindings for the identifiers described in the previous revision of this report [6], omitting `load`, `transcript-on`, `transcript-off`, and `char-ready?`. The bindings have as values the procedures of the same names described in this report.

## REFERENCES

- [1] Henk P. Barendregt. Introduction to the lambda calculus. *Nieuw Archief voor Wetenschap*, 4(2):337–372, 1984.
- [2] Alan Bawden. Quasiquote in Lisp. In Olivier Danvy, editor, *Proc. ACM SIGPLAN Workshop on Partial Evaluation and Semantics-Based Program Manipulation PEPM '99*, pages 4–12, San Antonio, Texas, USA, January 1999. BRICS Notes Series NS-99-1.
- [3] William Clinger and Jonathan Rees. Macros that work. In *Proc. 1991 ACM SIGPLAN Symposium on Principles of Programming Languages*, pages 155–162, Orlando, Florida, January 1991. ACM Press.
- [4] Danny Cohen. On holy wars and a plea for peace. <http://www.ietf.org/rfc/ien/ien137.txt>, April 1980. Internet Engineering Note 137.
- [5] Mark Davis. Unicode Standard Annex #29: Text boundaries. <http://www.unicode.org/reports/tr29/>, 2006.
- [6] Richard Kelsey, William Clinger, and Jonathan Rees. Revised<sup>5</sup> report on the algorithmic language Scheme. *Higher-Order and Symbolic Computation*, 11(1):7–105, 1998.
- [7] Richard Kelsey and Michael Sperber. SRFI 34: Exception handling for programs. <http://srfi.schemers.org/srfi-34/>, 2002.
- [8] Eugene E. Kohlbecker, Daniel P. Friedman, Matthias Felleisen, and Bruce Duba. Hygienic macro expansion. In *Proceedings of the 1986 ACM Conference on Lisp and Functional Programming*, pages 151–161, 1986.
- [9] Michael Sperber, William Clinger, R. Kent Dybvig, Matthew Flatt, Anton van Straaten, Richard Kelsey, and Jonathan Rees. Revised<sup>6</sup> report on the algorithmic language Scheme. <http://www.r6rs.org/>, 2007.
- [10] The Unicode Consortium. The Unicode standard, version 5.0.0. defined by: *The Unicode Standard, Version 5.0* (Boston, MA, Addison-Wesley, 2007. ISBN 0-321-48091-0), 2007.
- [11] Oscar Waddell. *Extending the Scope of Syntactic Abstraction*. PhD thesis, Indiana University, August 1999. <http://www.cs.indiana.edu/~owaddell/papers/thesis.ps.gz>.

## ALPHABETIC INDEX OF DEFINITIONS OF CONCEPTS, KEYWORDS, AND PROCEDURES

... 50

antimark 48

&assertion 27

assertion-violation? 27

assoc 12

assp 12

assq 12

assv 12

base record type 16

big-endian 5

binary port 29, 30

binary-port? 32

bit fields 46

bitwise-and 46

bitwise-arithmetic-shift 47

bitwise-arithmetic-shift-left 47

bitwise-arithmetic-shift-right 47

bitwise-bit-count 46

bitwise-bit-field 47

bitwise-bit-set? 47

bitwise-copy-bit 47

bitwise-copy-bit-field 47

bitwise-first-bit-set 47

bitwise-if 46

bitwise-ior 46

bitwise-length 46

bitwise-not 46

bitwise-reverse-bit-field 47

bitwise-rotate-bit-field 47

bitwise-xor 46

bound-identifier=? 52

buffer-mode 30

buffer-mode? 30

byte 5

bytevector 5

bytevector->sint-list 7

bytevector->string 32

bytevector->u8-list 6

bytevector->uint-list 7

bytevector-copy 6

bytevector-copy! 6

bytevector-fill! 6

bytevector-ieee-double-native-ref 9

bytevector-ieee-double-native-set! 9

bytevector-ieee-double-ref 9

bytevector-ieee-single-native-ref 9

bytevector-ieee-single-native-set! 9

bytevector-ieee-single-ref 9

bytevector-length 5

bytevector-s16-native-ref 7

bytevector-s16-native-set! 7

bytevector-s16-ref 7

bytevector-s16-set! 7

bytevector-s32-native-ref 8

bytevector-s32-native-set! 8

bytevector-s32-ref 8

bytevector-s32-set! 8

bytevector-s64-native-ref 8

bytevector-s64-native-set! 8

bytevector-s64-ref 8

bytevector-s64-set! 8

bytevector-s8-ref 6

bytevector-s8-set! 6

bytevector-sint-ref 6

bytevector-sint-set! 6

bytevector-u16-native-ref 7

bytevector-u16-native-set! 7

bytevector-u16-ref 7

bytevector-u16-set! 7

bytevector-u32-native-ref 8

bytevector-u32-native-set! 8

bytevector-u32-ref 8

bytevector-u32-set! 8

bytevector-u64-native-ref 8

bytevector-u64-native-set! 8

bytevector-u64-ref 8

bytevector-u64-set! 8

bytevector-u8-ref 6

bytevector-u8-set! 6

bytevector-uint-ref 6

bytevector-uint-set! 6

bytevector=? 6

bytevector? 5

call by need 62

call-with-bytevector-output-port 37

call-with-input-file 40

call-with-output-file 40

call-with-port 33

call-with-string-output-port 38

case-lambda 14, 15

char-alphabetic? 3

char-ci<=? 3

char-ci<? 3

char-ci=? 3

char-ci>=? 3

char-ci>? 3

char-downcase 3

char-foldcase 3

char-general-category 4

char-lower-case? 3

char-numeric? 3

char-title-case? 3  
 char-titlecase 3  
 char-upcase 3  
 char-upper-case? 3  
 char-whitespace? 3  
 close-input-port 40  
 close-output-port 40  
 close-port 33  
 codec 30  
 command-line 41  
 compound condition 24  
 condition 24  
 &condition 24  
 condition 24  
 condition-accessor 24  
 condition-irritants 27  
 condition-message 26  
 condition-predicate 24  
 condition-who 27  
 condition? 24  
 cons\* 13  
 constructor descriptor 17  
 continuable exception 23  
 current exception handler 22  
 current-error-port 38, 40  
 current-input-port 34, 40  
 current-output-port 38, 40  
  
 datum->syntax 53  
 define-condition-type 25  
 define-enumeration 59  
 define-record-type 19  
 delay 62  
 delete-file 41  
 display 40  
 do 14  
  
 end of file object 32  
 end-of-line style 30  
 endianness 5  
 endianness 5  
 enum-set->list 58  
 enum-set-complement 59  
 enum-set-constructor 58  
 enum-set-difference 59  
 enum-set-indexer 58  
 enum-set-intersection 59  
 enum-set-member? 59  
 enum-set-projection 59  
 enum-set-subset? 59  
 enum-set-union 59  
 enum-set-universe 58  
 enum-set=? 59  
 enumeration 58  
 enumeration sets 58  
 enumeration type 58  
  
 environment 60  
 eof-object 32, 40  
 eof-object? 32, 40  
 eol-style 30  
 equal-hash 58  
 equivalence function 56  
 &error 26  
 error-handling-mode 31  
 error? 26  
 eval 60  
 exact->inexact 61  
 exception 24  
 exceptional situation 24  
 exceptions 22  
 exists 10  
 exit 41  
  
 file options 29  
 file-exists? 41  
 file-options 29  
 filter 11  
 find 10  
 fixnum->flonum 46  
 fl\* 44  
 fl+ 44  
 fl- 44  
 fl/ 44  
 fl<=? 44  
 fl<? 44  
 fl=? 44  
 fl>=? 44  
 fl>? 44  
 flabs 45  
 flacos 45  
 flasin 45  
 flatan 45  
 flceiling 45  
 flcos 45  
 fldenominator 45  
 fldiv 45  
 fldiv-and-mod 45  
 fldiv0 45  
 fldiv0-and-mod0 45  
 fleven? 44  
 flexp 45  
 flexpt 46  
 flfinite? 44  
 flfloor 45  
 flinfinite? 44  
 flinteger? 44  
 fllog 45  
 flmax 44  
 flmin 44  
 flmod 45  
 flmod0 45

flnan? 44  
 flnegative? 44  
 flnumerator 45  
 flodd? 44  
 flonum? 44  
 flpositive? 44  
 flround 45  
 flsin 45  
 flsqrt 46  
 fltan 45  
 fltruncate 45  
 flush-output-port 37  
 flzero? 44  
 fold-left 11  
 fold-right 11  
 for-all 10  
 force 62  
 free-identifier=? 52  
 fx\* 42  
 fx\*/carry 42  
 fx+ 42  
 fx+/carry 42  
 fx- 42  
 fx-/carry 42  
 fx<=? 41  
 fx<? 41  
 fx=? 41  
 fx>=? 41  
 fx>? 41  
 fxand 42  
 fxarithmetic-shift 43  
 fxarithmetic-shift-left 43  
 fxarithmetic-shift-right 43  
 fxbit-count 43  
 fxbit-field 43  
 fxbit-set? 43  
 fxcopy-bit 43  
 fxcopy-bit-field 43  
 fxdiv 42  
 fxdiv-and-mod 42  
 fxdiv0 42  
 fxdiv0-and-mod0 42  
 fxeven? 42  
 fxfirst-bit-set 43  
 fxif 42  
 fxior 42  
 fxlength 43  
 fxmax 42  
 fxmin 42  
 fxmod 42  
 fxmod0 42  
 fxnegative? 42  
 fxnot 42  
 fxodd? 42  
 fxpositive? 42  
 fxreverse-bit-field 44  
 fxrotate-bit-field 43  
 fxxor 42  
 fxzero? 42  
 generate-temporaries 54  
 get-bytevector-all 35  
 get-bytevector-n 35  
 get-bytevector-n! 35  
 get-bytevector-some 35  
 get-char 36  
 get-datum 36  
 get-line 36  
 get-string-all 36  
 get-string-n 36  
 get-string-n! 36  
 get-u8 35  
 guard 23  
 hash function 56  
 hashtable 56  
 hashtable-clear! 57  
 hashtable-contains? 57  
 hashtable-copy 57  
 hashtable-delete! 57  
 hashtable-entries 57  
 hashtable-equivalence-function 57  
 hashtable-hash-function 57  
 hashtable-keys 57  
 hashtable-mutable? 57  
 hashtable-ref 57  
 hashtable-set! 57  
 hashtable-size 57  
 hashtable-update! 57  
 hashtable? 57  
 &i/o 27  
 &i/o-decoding 31  
 i/o-decoding-error-transcoder 31  
 i/o-decoding-error? 31  
 &i/o-encoding 31  
 i/o-encoding-error-char 31  
 i/o-encoding-error-transcoder 31  
 i/o-encoding-error? 31  
 i/o-error-filename 28  
 i/o-error-port 29  
 i/o-error? 27  
 &i/o-file-already-exists 28  
 i/o-file-already-exists-error? 28  
 &i/o-file-does-not-exist 28  
 i/o-file-does-not-exist-error? 28  
 &i/o-file-is-read-only 28  
 i/o-file-is-read-only-error? 28  
 &i/o-file-protection 28  
 i/o-file-protection-error? 28  
 &i/o-filename 28

i/o-filename-error? 28  
&i/o-invalid-position 28  
i/o-invalid-position-error? 28  
&i/o-port 29  
i/o-port-error? 29  
&i/o-read 28  
i/o-read-error? 28  
&i/o-write 28  
i/o-write-error? 28  
identifier 49  
identifier macro 51  
identifier? 51  
immutable record type 16  
&implementation-restriction 26  
implementation-restriction-violation? 26  
implicit identifier 53  
inexact->exact 61  
input port 29  
input-port? 33  
&irritants 27  
irritants-condition? 27  
  
latin-1-codec 30  
lazy evaluation 62  
&lexical 26  
lexical-violation? 26  
library specifier 60  
list-sort 13  
little-endian 5  
lookahead-char 36  
lookahead-u8 35  
  
macro transformer 49  
make-assertion-violation 27  
make-bytevector 5  
make-custom-binary-input-port 34  
make-custom-binary-input/output-port 39  
make-custom-binary-output-port 38  
make-custom-textual-input-port 34  
make-custom-textual-input/output-port 39  
make-custom-textual-output-port 38  
make-enumeration 58  
make-eq-hashtable 56  
make-eqv-hashtable 56  
make-error 26  
make-hashtable 56  
make-i/o-decoding-error 31  
make-i/o-encoding-error 31  
make-i/o-error 27  
make-i/o-file-already-exists-error 28  
make-i/o-file-does-not-exist-error 28  
make-i/o-file-is-read-only-error 28  
make-i/o-file-protection-error 28  
make-i/o-filename-error 28  
make-i/o-invalid-position-error 28  
make-i/o-port-error 29  
  
make-i/o-read-error 28  
make-i/o-write-error 28  
make-implementation-restriction-violation 26  
make-irritants-condition 27  
make-lexical-violation 26  
make-message-condition 26  
make-no-infinities-violation 46  
make-no-nans-violation 46  
make-non-continuable-violation 26  
make-record-constructor-descriptor 17  
make-record-type-descriptor 16  
make-serious-condition 26  
make-syntax-violation 27  
make-transcoder 31  
make-undefined-violation 27  
make-variable-transformer 49  
make-violation 26  
make-warning 26  
make-who-condition 27  
mark 48  
member 12  
memp 12  
memq 12  
memv 12  
&message 26  
message-condition? 26  
modulo 61  
mutable record type 16  
  
native-endianness 5  
native-eol-style 30  
native-transcoder 32  
newline 40  
&no-infinities 46  
no-infinities-violation? 46  
&no-nans 46  
no-nans-violation? 46  
&non-continuable 26  
non-continuable-violation? 26  
null-environment 62  
number 41  
  
octet 5  
open-bytevector-input-port 33  
open-bytevector-output-port 37  
open-file-input-port 33  
open-file-input/output-port 39  
open-file-output-port 37  
open-input-file 40  
open-output-file 40  
open-string-input-port 34  
open-string-output-port 37  
output ports 29  
output-port-buffer-mode 37  
output-port? 37

partition 11  
 pattern variable 50  
 peek-char 40  
 port 29  
 port-eof? 33  
 port-has-port-position? 32  
 port-has-set-port-position!? 33  
 port-position 32  
 port-transcoder 32  
 port? 32  
 position 32  
 promise 62  
 protocol 17  
 put-bytevector 39  
 put-char 39  
 put-datum 39  
 put-string 39  
 put-u8 38  
  
 quasisyntax 55  
 quotient 61  
  
 raise 23  
 raise-continuable 23  
 read 40  
 read-char 40  
 real->flonum 44  
 record 15  
 record constructor 17  
 record-accessor 18  
 record-constructor 17  
 record-constructor descriptor 17  
 record-constructor-descriptor 21  
 record-field-mutable? 22  
 record-mutator 18  
 record-predicate 18  
 record-rtd 22  
 record-type descriptor 16  
 record-type-descriptor 21  
 record-type-descriptor? 17  
 record-type-field-names 22  
 record-type-generative? 22  
 record-type-name 22  
 record-type-opaque? 22  
 record-type-parent 22  
 record-type-sealed? 22  
 record-type-uid 22  
 record? 22  
 region 14  
 remainder 61  
 remove 12  
 remp 12  
 remq 12  
 remv 12  
 (rnrs (6)) 60  
 (rnrs arithmetic bitwise (6)) 46  
 (rnrs arithmetic flonum (6)) 44  
 (rnrs arithmetic fx (6)) 41  
 (rnrs bytevector (6)) 5  
 (rnrs conditions (6)) 24  
 (rnrs control (6)) 13  
 (rnrs enum (6)) 58  
 (rnrs exceptions (6)) 22  
 (rnrs files (6)) 41  
 (rnrs hashtables (6)) 56  
 (rnrs io ports (6)) 29  
 (rnrs io simple (6)) 39  
 (rnrs lists (6)) 10  
 (rnrs mutable-pairs (6)) 60  
 (rnrs mutable-strings (6)) 61  
 (rnrs programs (6)) 41  
 (rnrs r5rs (6)) 61  
 (rnrs records inspection (6)) 21  
 (rnrs records procedural (6)) 16  
 (rnrs records syntactic (6)) 19  
 (rnrs sorting (6)) 13  
 (rnrs syntax-case (6)) 48  
 (rnrs unicode (6)) 3  
 rtd 16  
  
 scheme-report-environment 62  
 &serious 26  
 serious-condition? 26  
 set-car! 60  
 set-cdr! 60  
 set-port-position! 33  
 simple condition 24  
 simple-conditions 24  
 sint-list->bytevector 7  
 standard-error-port 38  
 standard-input-port 34  
 standard-output-port 38  
 string->bytevector 32  
 string->utf16 9  
 string->utf32 9  
 string->utf8 9  
 string-ci-hash 58  
 string-ci<=? 4  
 string-ci<? 4  
 string-ci=? 4  
 string-ci>=? 4  
 string-ci>? 4  
 string-downcase 4  
 string-fill! 61  
 string-foldcase 4  
 string-hash 58  
 string-normalize-nfc 4  
 string-normalize-nfd 4  
 string-normalize-nfkc 4  
 string-normalize-nfkd 4  
 string-set! 61

- string-titlecase 4
- string-upcase 4
- substitution 48
- symbol-hash 58
- &syntax 27
- syntax 50
- syntax object 49
- syntax->datum 53
- syntax-case 49
- syntax-violation 56
- syntax-violation-form 27
- syntax-violation-subform 27
- syntax-violation? 27
  
- textual port 30
- textual ports 29
- textual-port? 32
- transcoded-port 32
- transcoder 30
- transcoder-codec 32
- transcoder-eol-style 32
- transcoder-error-handling-mode 32
- transformation procedure 49
- transformer 49
  
- u8-list->bytevector 6
- uint-list->bytevector 7
- &undefined 27
- undefined-violation? 27
- universe 58
- unless 13, 14
- utf-16-codec 30
- utf-8-codec 30
- utf16->string 10
- utf32->string 10
- utf8->string 10
  
- variable transformer 49
- vector-sort 13
- vector-sort! 13
- &violation 26
- violation? 26
  
- &warning 26
- warning? 26
- when 13, 14
- &who 27
- who-condition? 27
- with-exception-handler 23
- with-input-from-file 40
- with-output-to-file 40
- with-syntax 54
- wrap 48
- wrapped syntax object 48
- write 41
- write-char 40